



Fireball® Strobe Warning Lights

- Very bright and compact strobe light
- Emits a powerful "lightning bolt" flash of light
- Approximately 5" tall and 4" in diameter
- Rated at 300-effective candlepower, can be used in a variety of stationary and vehicular warning requirements
- Available in 12-24 VDC, 120 VAC, and 240 VAC
- 10000 hour strobe tube
- UL and cUL Listed, CSA Certified for indoor/outdoor use
- Type 4X, IP66 enclosure



Model No.	Mfg. No.	Colour	Price/Each
XC135	FB2PST-120A	Amber	
XC136	FB2PST-120R	Red	
XC256	FB2PST-120B	Blue	
XC257	FB2PST-120C	Clear	
XC258	FB2PST-120G	Green	

StreamLine® Low Profile LED Lights

- 120 VAC
- 1/2" male pipe mount
- 100 000-hour LED lamp life
- Screw-on lens
- Type 4X enclosure
- Optional wire lens guard
- UL and cUL Listed, CSA Certified



LED



Model No.	Mfg. No.	Colour	Price/Each
XC420	LP3ML-120A	Amber	
XC421	LP3ML-120B	Blue	
XC422	LP3ML-120R	Red	
XC423	LP3ML-120C	Clear	
XC424	LP3ML-120G	Green	

Note: Also available in 24 VDC

Battery Powered Strobe Warning Lights

- Portable, battery powered warning light flashes 65 times per minute
- Solid-state flasher features components which are moisture-proof and reverse polarity protected to ensure extended battery life and trouble-free performance
- 12 VDC - uses two standard 6 VDC lantern batteries
- 4000-hour, strobe tube with magnetic base
- Type 3R weather proof enclosure



Model No.	Mfg. No.	Description	Price/Each
XC139	BPL26ST-A	Strobe Tube, Amber	
XC140	BPL26ST-R	Strobe Tube, Red	
XC268	BPL26ST-B	Strobe Tube, Blue	
XC269	BPL26ST-C	Strobe Tube, Clear	
XC270	BPL26ST-G	Strobe Tube, Green	
XA430		Replacement 6 V Battery	

Streamline® Low Profile Strobe Lights

- Features a state-of-the-art strobe rated for 7000 hours
- High-quality, long-life strobe tubes are designed to reduce tungsten build-up for longer lamp maintenance cycles
- Screw-on lens provides easy access
- Low profile
- Available in 120VAC and 12-48VDC
- Type 4X, IP66
- UL and cUL Listed, CSA Certified
- PLC and triac compatible



Model No.	Mfg. No.	Description	Price/Each
XC125	LP3P-120A	Amber, Pipe Mount	
XC126	LP3P-120R	Red, Pipe Mount	
XC286	LP3P-120B	Blue, Pipe Mount	
XC287	LP3P-120C	Clear, Pipe Mount	
XC288	LP3P-120G	Green, Pipe Mount	
XC127	LP3T-012-048A	Amber, T Mount	
XC128	LP3T-012-048B	Blue, T Mount	
XC129	LP3T-012-048R	Red, T Mount	
XC289	LP3T-012-048C	Clear, T Mount	
XC290	LP3T-012-048G	Green, T Mount	
XC130	LP3E-120A	Amber, Edison Base	
XC131	LP3E-120R	Red, Edison Base	
XC262	LP3E-120B	Blue, Edison Base	
XC263	LP3E-120C	Clear, Edison Base	
XC264	LP3E-120G	Green, Edison Base	
XC132	LP3M-120A	Amber, Male Pipe Mount	
XC133	LP3M-120B	Blue, Male Pipe Mount	
XC134	LP3M-120R	Red, Male Pipe Mount	
XC265	LP3M-012-048B	Blue Male Pipe Mount	
XC266	LP3M-012-048C	Clear Male Pipe Mount	
XC267	LP3M-012-048G	Green Male Pipe Mount	

Flashing Combination Audible/Visual Signals

- Features 100% polycarbonate housing rated for Type 3R rain-tight applications
- Surface mount, integrated 1/2" pipe mount and 4" electrical box mount
- Twist-off lens for easy access
- Internal buzzer produces 85 dB at 10'
- 120 VAC
- UL and cUL Listed, CSA Certified
- Type 3R enclosure



Model No.	Mfg. No.	Description	Price/Each
XC119	AVIST-120A	Strobe Tube, Amber	
XC120	AVIST-120R	Strobe Tube, Red	
XC278	AVIST-120B	Strobe Tube, Blue	
XC279	AVIST-120C	Strobe Tube, Clear	
XC280	AVIST-120G	Strobe Tube, Green	