

Drum Closures

STEEL DRUM CLOSURES

- Made from premium deep-drawing quality steel
- Visegrip® plugs have a hexagonal shoulder for easy opening (no tools required)
- $\label{eq:total_total_total} \mbox{Titegrip}^{\mbox{\tiny TM}} \mbox{ plugs compatible with other opening types also available}$

STEEL DRUM FUSIBLE CLOSURES

- Used for drums containing combustible materials
- Made of reinforced nylon material
- Centre melts away when exposed to extreme heat allowing venting, thus reducing risk of explosion
- Titegrip™ plugs compatible with other opening types also available

POLY-DRUM CLOSURES

- Poly-Visegrip® closure specially designed for use in lined containers
- Requires no gaskets

STEEL DRUM CLOSURES

Model No.	Size"	Price/Each
DB891	3/4	
DC648	2	

STEEL DRUM FUSIBLE CLOSURES

Model No.	Size"	Torque req. (ft-lbs.)	Price/Each
DB893	3/4	9	
DB894	2	20	

POLY-DRUM CLOSURES

Model No.	Size"	Threads	Price/Each
DB895	2	NPS	
DB896	2	BSP	









Manual Crimping Tools

- **DB903** is used for 2" cap seals
- DB904 is used for 3/4" cap seals

Model No. DB903 Price/Each

Model No. DB904 Price/Each



Tamper-Evident Cap Seals

SAFESEAL® PLASTIC CAP SEALS

- Requires DB903 or DB904 tool to be applied
- Titegrip™ compatible Safeseal® plastic caps also available

ALL PLASTIC CAP SEALS

- · Easy-to-use pop-on feature
- · Can be applied without tools

Model No.	Size"	Price/Each			
SAFESEAL®	PLASTIC CAP SEALS				
DB899	3/4				
DB900	2				
ALL PLASTIC CAP SEALS					
DB901	3/4				
DB902	2				





Horizontal Drum Gauges

information on the amount of liquid in a 45-gallon drum. Mounts through 2" bung hole: seals tight, won't leak. Reads in 5-gallon intervals. Wt. 2 lbs.





Vertical Drum Gauges

Accurate "At-A-Glance" monitoring. Graduated in gallons, litres, quarters and eighths full. Heavy steel and plastic construction with leak-proof duro nitrite gaskets. Resistant to oil and many chemicals. Weight: 1 lb

Model No.	Size"	
DA068	2	
DA069	3/4	

Safety Funnels with Fill Vent 9" diameter polyethylene funnel

comes with brass safety vent and 6" flame arrestor. Cap comes with safety chain to prevent loss. 2" NPS. FM approved.



Model No.	Wt. lbs.
DA103	2.5



Price/	Each

Graduated Drum Gauges

Combination gauge and faucet permits uninterrupted draining of drum contents with gauge in place. Mounts through 3/4" bung hole. Constructed of heavy gauge glass in plated steel body with Buna-N seals. Weight: 3 lbs.



Zinc Die Cast Faucet FM approved for viscous liquids only; no flame arrestor.

Drum Fill Gauges

Provides a low cost solution to over-filling drums. When the drum is almost full, the indicator "Pops-up" to warn you. Fits in standard 3/4" bung opening. Bright red and yellow molded polyethylene. 5" length. Weight: 0.20 oz.

Model No. DA066 Price/Each \$





Safety Drum Funnels

Suitable for handling flammables. Large 10 3/4" mouth provides quick dumping. Steel construction

with 6" flame arrestor for the DA102 and 32" flame arrestor for the DA101. Hinged cover with fusible link reduces spread of vapours. 2" NPS/NPT.FM approved.



№ Justrite

Model		Wt.	Price
No.	Description	lbs.	/Each
DA102	6" flame arrestor w/funnel	7.5	
DA101	32" flame arrestor w/funnel	12	

Horizontal Brass Vents

- Horizontal vents are for use with drums in the horizontal pouring position
- Automatically relieves pressure at 5 PSI
- Flame arrestor prevents sparks and flame from igniting contents
- Manual vacuum relief by lifting and rotating the valve stem.
- Maximum flow of 220 CFM at 20 PSI
- Fits 2" NPS bung in steel or plastic drums

Model No. PE362 Price/Each \$





Vertical Vents

FM approved vents are for use with drums in the upright position. Valve automatically opens to relieve internal pressure at 5 PSI. Automatic vacuum relief permits 4 GPM flow through 3/4" faucet.

rits 2 INF i builg opening.				
Model No.	Description	Application	Wt. Ibs.	Price /Each
DA607	Brass Vent	Petroleum-Based	0.5	
DA605	Non-metallic Vent, Cad-plated flame arrestor	Petroleum-Based	0.5	
DA606	Non-metallic Vent, Stainless steel flame arrestor	Chlorinated Solvents	1.0	

