



Pull Type Drum Pumps

Chemical compatibility of a drum or barrel pump should be checked for EACH LIQUID BY CHEMICAL NAME!

No single drum pump can be universally chemical resistant. Some blends of chemicals may not be suitable for any of these drum pumps. Remember to have your MSDS for each chemical that will be pumping when calling your our representative. We will be able to help you select the right pump for your application.

Polypropylene



Wetted components:

Polyethylene, polypropylene, silicone and steel

- For use with most corrosive chemicals and non-flammable solvents
- Adapts to 3/4" or 2" bung adaptor for 5 to 55-gallon drums
- 360° discharge spout orientation
- Transfer rate: 16 oz. per stroke

Model No. DC115
Price/Each \$



Wetted components:

Polypropylene, steel and Viton®

- For use with most antifreeze, detergents, windshield fluids, glycerin, and mild acids
- Fits 15 to 55-gallon drums with a 2" bung adaptor
- Transfer rate: 14 oz. per stroke

Model No. DC127
Price/Each \$



Wetted components:

Polyethylene, polypropylene and nylon

- For use with most corrosive chemicals, water, and non-flammable solvents
- Good insulation from spark and fire
- Fits 55-gallon drums with a 2" bung adaptor
- Transfer rate: 22 oz. per stroke

Model No. DC117
Price/Each \$



Wetted components:

Polypropylene, polyethylene, silicone and steel

- For use with most corrosive chemicals and non-flammable solvents
- Adapts to 3/4" or 2" bung adaptor for 5 to 55-gallon drums
- 360° discharge spout orientation
- Transfer rate: 8 oz. per stroke

Model No. DA532
Price/Each \$



PVC



Wetted components:

Polypropylene, PVC, nylon and Viton®

- For use with most mild acids, detergents, water and solvents
- Good insulation from spark and fire
- Transfer rate: 8 oz. per stroke

Model No. DC116
Price/Each \$



Wetted components:

PVC, nylon and Viton®

- For use with most mild acids, detergents, water and solvents
- Good insulation from spark and fire
- Fits 55-gallon drums with a 2" bung adaptor
- Transfer rate: 22 oz. per stroke

Model No. DC118
Price/Each \$



Nylon

Wetted components:

Polypropylene, nylon, 304 stainless steel and PTFE

- For use with most lacquer thinners, mild acids, detergents, water and light viscosity petroleum liquids
- Fits 15 to 55-gallon drums with 2" bung adaptor
- Transfer rate: 14 oz. per stroke

Model No. DC128
Price/Each \$



Safety Pumps

- FM approved for handling flammables
- Comes complete with internal flame arrestor, steel bung adaptor to aid static grounding, and heavy-duty bonding wires to remove hazardous static charge
- Steel pickup tube with internal screen keeps debris out of pump
- Constructed of highly polished carbon steel with Teflon® piston, packing and gasket for exceptional chemical and solvent resistance
- Pumps 8 oz. per stroke, designed to fit 45-gallon drums
- Also available in stainless steel for corrosive flammable liquids
- Weight: 5 lbs.

Model No. DA513 Carbon Steel
Price/Each \$

Model No. DB831 Stainless Steel
Price/Each \$

