

#### **Small Submersible** Oil Filled Pumps

- 1/160 HP oil-filled motor, 115 V, 60 Hz, 0.5 A
- Corrosion resistant nylon body
- 4.6' maximum lift
- 1/4" MNPT discharge
- Intermittent liquid temp up to 120°F
- 10' power cord length
- For submersible use only

Model No. DA342 Price/Each \$

#### Submersible Pumps

- 1/4 HP, 115 V, 60 Hz, 8.5 A
- 3/8" solid handling capacity
- 1-1/4" FNPT outlet with a garden hose adapter
- Automatic operation has 7" to 10" "On" level range and 2" to 5" "Off" level range
- 8' power cord length
- Thermally protected

Model No. DA333 Price/Fach \$



# **Sump/Effluent Pumps**

- 2/5 HP. 115 V. 9 A
- Handles liquids and solid waste materials up to 3/4" diameter
- Cast iron pump housing and cover with protective epoxy coating for corrosion resistance
- Oil-filled motor housing for lifetime lubrication and rapid heat dissipation
- Stainless steel fasteners
- Bearings: Upper and lower sintered sleeve
- 20' power cord
- Thermal overload protection

Model No. DC432 Price/Each \$

# **High Temperature** Sump/Effluent Pumps

- 1/3 HP, 115 V, 60 Hz, 10.1 A
- Handles liquids up to 200° F and solids up to 1/2"
- Cast iron pump housing with protective epoxy coating for corrosion resistance
- Oil-filled motor housing for lifetime lubrication and rapid heat dissipation
- Integral mechanical float switch
- Stainless steel screws, bolts and lifting ring to protect against corrosion
- Bearings: Upper and lower sintered sleeve bearings for extended motor life
- 15' Power cord
- Thermal overload protection
- Automatic operation has 10" to 12" "On" level range

Model No. DA336 Price/Each \$

#### **Automatic Switches**

- Converts manual pump up through 1/2 HP to automatic operation
- Turns on at 6 9" and off at 1 4"
- 18' power cord
- CSA listed

Model No. DA357 Price/Each \$

Little GIANT.



Little GIANT.











Little GIANT.



#### Submersible Sump Pumps

- 1/6 HP shaded pole motor with overload protection, 115 V, 60 Hz, 5 A
- Designed for continuous duty
- Pumps down to 1/8"
- Epoxy coated cast aluminum housing, Viton® shaft seal
- 18' power cord length
- · Includes: garden hose adapter and removable inlet screen for easy cleaning

Model No. DA332 Price/Each \$

# Little GIANT.

# Submersible Pumps

- 1/3 HP shaded pole motor, 115 V, 9 A
- 1/2" 1-1/4"FNPT x 1-1/2" MNPT adapter
- Cast iron pump housing with protective epoxy coating for corrosion resistance
- Oil-filled motor housing for lifetime lubrication and rapid heat dissipation
- Stainless steel screws, bolts and
- handle to protect against corrosion
- Bearings: Upper and lower sintered sleeve bearings for extended motor life
- 8' Power cord
- Thermal overload protection
- Automatic operation with pressure switch activates pump when water level is between 7" and 10"
- Pump shuts off when water level falls to between 1" and 4"

Model No. DA334 Price/Each \$



#### **Sump/Effluent Pumps**

- 1/3 HP shaded pole motor, 115 V, 5 A Handles liquid and solid waste materials up to 1/2" diameter
- Cast iron pump housing with protective epoxy coating for corrosion and rust resistance
- Oil-filled motor housing for lifetime lubrication and rapid heat dissipation
- Stainless steel screws, bolts and handle
- Bearings: Upper and lower sintered sleeve bearings
- 10' Power cord
- Thermal overload protection
- Automatic operation has 8" to 11" "On" level range and 2" to 5" "Off" level range
- Integral snap action float switch
- Base material: Polypropylene

Model No. DC431 Price/Each \$



Little GIANT.

### Sewage Pumps

- 1/2 HP split-phase type motor, 115 V, 9.5 A
- Handles liquids and solid waste materials up to 2" diameter
- Cast iron pump housing with protective epoxy coating for corrosion resistance
- Oil-filled motor housing for lifetime lubrication and rapid heat dissipation
- Stainless steel screws, bolts, handle and switch guard
- Thermal overload protection
- Piggyback mechanical float switch
- Automatic operation has 9" to 14" "On" level range and 2" to 6" "Off" level range

20' power cord Model No. DC438 Price/Each \$

FLOW CHART:



Model No.	Performance (GPM @ Head)					
	1'	31	5'	10'	15'	20'
DA342	2	1.16	-	-	-	-
DA334	-	-	46	29	12.5	-
DA333	40	-	35	30	-	10
DA332	20	19.5	18.3	16.6	-	8.6
DC432	-	-	80	70	60	45
DC438	-	-	120	95	70	30
DC431	-	-	50	42	30	-
DA336	_	-	50	42	27	-