



Cleco® 19 Series - Stall Screwdrivers

- Tool weight: 1.16 lbs.
- Tool length: 5.9"
- Free speed: 1100 RPM
- Max Torque: 40 in.-lbs.
- Engineered for heavy duty applications in the most demanding environment
- Adjustable reverse lever for true one-hand - left-handed or right-handed - operation
- Trigger start
- "P" handle style
- Interchangeable soft-touch grip sizes
- Air consumption: 11 CFM
- Air inlet: 1/4"
- Sound level (dBA): 80
- Chuck Size: 1/4"
- Chuck Type: Keyless

Model No. TYN249
Mfg. No. 19PTS04Q
Price/Each \$

Cleco®



Cleco® 19 Series - Pistol Grip Screwdrivers w/Adjustable Torque Settings

- Tool weight: 1.41 lbs.
- Tool length: 8.0"
- Free speed: 1100 RPM
- Max Torque: 40 in.-lbs.
- Engineered for heavy duty applications in the most demanding environment
- Class-leading accuracy and repeatability
- Adjustable reverse lever for true one-hand - left-handed or right-handed - operation
- "P" handle style
- Interchangeable soft-touch grip sizes
- Trigger and Push & Trigger start
- External torque adjustment from 10 - 40 in.-lbs.
- Air consumption: 11 CFM
- Air inlet: 1/4"
- Sound level (dBA): 80
- Chuck Size: 1/4"
- Chuck Type: Keyless

Model No. TYN248
Mfg. No. 19PTA04Q
Price/Each \$

Cleco®



Cleco® Right Angle Grinders

- Compact, yet powerful motor
- Reversible safety lever throttle
- Dual auxiliary handle positions
- Maximum material removal for a right angle grinder
- Streamlined all metal housing
- Performance rated @ 90 PSI / 620 kPa air pressure
- Air consumption: 15 CFM
- Air inlet: 1/2"
- No load RPM: 12000

Cleco®

Model No.	Mfg. No.	Wheel Size"	Spindle Size	Motor Power HP	Price /Each
1660 SERIES					
TYM371	1660AGL-04	4	3/8"	1.6	
TYM374	1660AGL-45	4 1/2	5/8"	1.6	
TYM372	1660AGL-05	5	5/8"	1.6	
TYM373	1660AGL-05-M14	5	M14	1.6	
2260 SERIES					
TYM396	2260AGL-06	6	5/8"	2.2	
TYM397	2260AGL-07	7	5/8"	2.2	



Cleco® CWC Premium Composite Series - Impact Wrenches

- The ultimate balance of performance, ergonomics and durability
- Composite housing with a high output motor that delivers a maximum power-to-weight ratio
- On hand push button forward/reverse with variable speed trigger, dial speed settings
- Twin hammer impact mechanism

TYN507



Cleco®

Model No.	Mfg. No.	Air Consumption CFM	Retainer Type	Drive"	Impacts Per Minute	Free Speed RPM	Max Torque ft.-lbs.	Price /Each
TYN508	CWC-250QC	2.7	Quick Change Chuck	1/4	1200	13000	50	
TYN507	CWC-250R	2.7	Ring	1/4	1200	13000	50	
TYN501	CWC-375R	5.3	Ring	3/8	1600	10000	450	
TYN503	CWC-375P	5.3	Pin	3/8	1600	10000	450	
TYN509	CWC-500R	5.7	Ring	1/2	1250	8000	800	
TYN512	CWC-500P	5.7	Pin	1/2	1250	8000	800	
TYN511	CWC-500RE	5.7	Ring*	1/2	1250	8000	800	
TYN514	CWC-500PE	5.7	Pin*	1/2	1250	8000	800	
TYN505	CWC-750P	9.7	Pin	3/4	1200	6500	1400	

*Extended anvil

Cleco® CWM Premium Metal Series - Impact Wrenches

- Engineered for heavy duty applications in the most demanding environment
- Rugged all-metal construction
- Withstands heavy abuse with twin impact mechanism
- Large lever forward/reverse and speed settings with variable speed trigger
- Soft touch grip protects against slip, temperature and vibration

TYN499



Cleco®

Model No.	Mfg. No.	Air Consumption CFM	Retainer Type	Drive"	Impacts Per Minute	Free Speed RPM	Max Torque ft.-lbs.	Price /Each
TYN496	CWM-375R	3.8	Ring	3/8	1400	12000	340	
TYN497	CWM-375P	3.8	Pin	3/8	1400	12000	340	
TYN499	CWM-500R	5.6	Ring	1/2	1200	9000	850	
TYN500	CWM-500P	5.6	Pin	1/2	1200	9000	850	
TYN498	CWM-750P	7.6	Pin	3/4	1200	6000	1350	

Dotco® 15LF Series - Right Angle Drills

- Tool weight: 1.7 lbs.
- Tool length: 11.0"
- Motor power: 0.4 HP (0.30 kW)
- Engineered for heavy duty applications in the most demanding environment
- Reinforced angle head for added durability
- Comfortable and ergonomic handle
- Performance rated @ 90 PSI / 620 kPa air pressure
- Air consumption: 22 CFM
- Air inlet: 1/4"
- Sound level (dBA): 80
- Chuck Size: 1/4"
- No load RPM: 3700

Model No. TYM161
Mfg. No. 15LF281-52
Price/Each \$

DOTCO®

