



Self-Levelling Five-Beam Laser Pointers

- Simultaneously projects five self-levelling beams
- Alarm when unit is beyond accurate range
- Low power indicator
- Locking mechanism protects unit in transport
- Includes: Laser level, multifunction mount, three AA batteries, tinted glasses, magnetic target, strap and carrying case

JOHNSON



TECHNICAL SPECIFICATIONS

Model No.	TGZ560
Mfg. No.	40-6680
Laser wave length:	635 nm ± 10 nm
Laser classification:	Class 111A
Accuracy:	± 1/4" @ 100' (± 2 mm @ 10 m)
Working range:	Max. 100' (30 m) depending on light conditions
Working temperature:	14°F to 113°F (-10°C to 40°C)
Price/Each	\$

Automatic-Levelling Rotary Laser Levels

- Automatic-levelling vertical plane and horizontal beam
- Automatic-levelling horizontal plane and plumb beam
- Red beam
- Rotates at two speeds: 120 and 500 RPM
- Integral vertical mount
- Electronically controlled slope feature
- Alarm when unit is beyond accurate range
- Includes: Laser level, NiMH battery pack, 6 V adapter, remote control, beam detector, magnetic target, tinted glasses and carrying case

JOHNSON



TECHNICAL SPECIFICATIONS

Model No.	TGZ551
Mfg. No.	40-6522
Laser wave length:	635 nm ± 10 nm
Laser classification:	Class 111A
Accuracy:	Horizontal: ± 1/8" @ 100' (± 2 mm @ 10 m) Vertical: ± 3/16" @ 100' (± 5 mm @ 10 m)
Working range:	Max. 100' (30 m) depending on light conditions
Measuring range:	Max. 984' (300 m) radius with detector
Working temperature:	14°F to 113°F (-10°C to 45°C)
Price/Each	\$

Manual-Leveling Rotary Laser Levels

- Emits horizontal or vertical laser plane with simultaneous 90° split beam
- Large and small scan modes achieve a chalk line
- Scan line can be moved clockwise or counter-clockwise
- Includes: Manual-leveling rotary laser level, 4 x AA alkaline batteries, wall/ceiling mount, 8' grade rod, detector with 2 x AAA batteries and clamp, tinted glasses, magnetic target, elevating tripod, instruction manual with warranty card, hard-shell carrying case
- Variable rotation speed

JOHNSON



TECHNICAL SPECIFICATIONS

Model No.	TLV309
Mfg. No.	40-6512
Laser wave length:	635 nm ± 10 nm
Laser classification:	Class 111A
Accuracy:	+/-1/4"/100' (+/-2 mm/10 m)
Max. working range:	Up to 800' diameter (240 m) with detector
Working temperature:	14°F to 113°F (-10-45°C)
Price/Each	\$

3 Beam Self-Leveling Line Laser

- 3 Beam Line Laser to aid in 90° layout
- 2x Brighter diode to increase visibility in bright job site conditions
- Built-in magnetic pivot bracket mounts easily on metal surfaces
- 1-button operation and control panel for ease of use
- Micro adjust knob for precise alignment of 90° intersecting lines over greater distances
- Includes: 4 AA batteries for 30 hours of run-time, Ceiling Mount and Kit Box

DEWALT



TECHNICAL SPECIFICATIONS

Model No.	TMB038
Mfg. No.	DW089K
Accuracy:	±1/8" @ 30'
Power:	6 V, 4-AA Battery
Run Time:	30 hours
Price/Each	\$