



Desiccants

Moisture control: The desiccant absorbs moisture vapour through the capillary action of the absorbent particles. Neither the particles, nor the bag that contains the particles, is changed physically by the absorption action. As well, the container does not become saturated, therefore it doesn't soften or liquefy during use. And metal parts touching the bag will not corrode.

Dust-free: Tyvek bags are ideal for applications where dust must be kept to a minimum. Examples include computer components, packaged chemicals, and photographic and optical devices.



Priced per Package

Model No.	Size	Type of Container	Type of Bag	Dimensions of Pouch*	Qty /Pkg.	Price /Each
PB339	1/6	5 Gal. Pail	Tyvek	1 x 2 1/2 x 1/4	1200	
PB340	1/3	5 Gal. Pail	Tyvek	1 x 3 1/2 x 1/4	700	
PB341	1/2	5 Gal. Pail	Tyvek	3 1/4 x 1 1/2 x 1/4	550	
PB343	2	5 Gal. Pail	Tyvek	3 x 6 1/2 x 3/8	150	
PB326	2	30 Gal. Drum	Tyvek	3 x 6 1/2 x 3/8	800	
PB327	4	30 Gal. Drum	Tyvek	5 x 5 1/2 x 1/2	500	
PB328	8	30 Gal. Drum	Tyvek	5 x 8 x 1 1/8	300	
PB330	16	30 Gal. Drum	Tyvek	5 3/4 x 10 x 1 1/2	150	
PB345	80	30 Gal. Drum	Tyvek	8 3/4 x 12 1/2 x 2 1/2	30	

Humidity Indicators

REGISTER THE HYGROSCOPIC LEVEL IN PACKAGES

- 3 point humidity indicator
- Long lasting protection to items very sensitive to humidity
- Meets MS-20003-2 requirements
- 125 cards per box

Model No. PB329 Price/Each \$
Qty Qty Price/Each \$



Pre-Printed Message Tape


- 3M™ #371 box sealing tape
- All messages are red on white
- Trilingual (English, French, Spanish)
- 48 mm x 100 m rolls



PA601



PA600



PA604

Priced per Roll

Model No.	Message	Thickness Microns	Mils	Rolls /Case	Price /Each	Qty Price /Each
PA600	If seal is broken...	30	2.0	36		
PA601	Fragile handle with care	30	2.0	36		
PA604	Mixed merchandise enclosed	30	2.0	36		

Coldmark MONITORS DAMAGING COLD TEMPERATURES

- Accurately shows if your product has been exposed to cold below a selected temperature
- Colourless indicator bulb turns an irreversible violet colour as the temperature falls below the indicator's activation temperature
- Can be placed on the exterior or interior of shipping container
- Adheres easily to any dry surface

Specifications:
Product Sizes: 3.25" x .75" x .38"
Exposure Time: 30 minutes
Shelf Life: 1 year
Storage Temperature Range: Store product above activation temperatures up to 110°F/43°C

Model No.	Activation Temperature	Price /Each	Qty	Qty Price /Each
PB791	32°F/0°C			
PB669	26°F/-3°C			

Other activation temperatures are available



Temperature/Humidity Data Loggers

- Monitors both ambient temperature and relative humidity
- Stores up to 16000 temperature and 16000 humidity readings
- User selectable measurement rate from 2 seconds to 24 hours
- Alarm display if user-defined max-min values are exceeded
- Displays all status information through two LEDs
- Simply plug the logger into the USB port of your computer to begin downloading – no cables or wires are required
- Includes wall mount bracket and Windows compatible software

Specifications:
Temperature Range: -40 to 70°C (-40 to 158°F)
Resolution: 0.1°C/°F
Accuracy: ± 0.5°C (± 0.9°F): -4 to 122°F (-20 to 50°C); ± 1.0°F (± 1.8°F): all other ranges
Humidity Range: 0 to 100% RH
Resolution: 0.1% RH
Accuracy: ± 2% RH
Sampling Rate: User selectable rate: 2 s, 5 s, 10 s, 30 s, 2 m, 5 m, 10 m, 30 m, 1 h, 2 h, 3 h, 6 h, 12 h, 24 h
Power Supply: 3.6 V lithium battery
Battery Life: 1-yr: 5 s sample rate; 2.5-yr: 10 s sample rate
Dimensions: 130 x 30 x 25 mm
Weight: 20 g

Model No. IA449 Mfg. No. ST-171
 Price/Each \$



Tape Dispensers

- Retractable safety blade protects operator from injury
- Industrial quality tape guns constructed of steel and high impact plastic frame
- Adjustable brake lets you choose the desired release tension



Model No.	Description	Replacement Blade Model No.	Replacement Window Model No.	Price /Each
PE321	2" Standard-Duty	PE325	PE327	
PE322	2" Heavy-Duty	PE325	PE327	
PE323	3" Heavy-Duty	PE326	PE329	