

DEWALT

1/2" Dual Range Hammer Drills w/Carrying Case

- 1/2" capacity; 7.5 Amp motor
- Trigger-lock, trigger speed control in two ranges:
 0-1350 RPM, 0-22000 BPM; 0-2500 RPM, 0-40 000 BPM; reversing
- · Hammer with rotation or rotation only
- Self-stop brush system
- Includes: Depth gauge, side handle, chuck key and case

Model No. TEA141 Mfg. No. 5378-21 Price/Each \$

SPECIFICATIONS

Chuck Size: 1/2"
Amperage: 7.5
No Load RPM: 0-1350/0-2500
No Load BPM: 0-20000/0-40000
Chuck Type: Keyed
Tool Weight: 6.0 lbs.



Milwaukee

Milwaukee

Milwaukee

1/2" VSR Hammer Drills

- · Lightweight design for less user fatigue
- Dual mode hammer drill/drill for wood, steel or masonry applications
- Variable speed allows for precise hole placement on work surface
- Includes: 360° side handle, depth rod and chuck key with holder

Model No. TSW576 Mfg. No. DW511 Price/Each \$

SPECIFICATIONS

Chuck Size: 1/2"
Amperage: 6.7
No Load RPM: 0-2700
No Load BPM: 0-46000
Chuck Type: Keyed
Tool Weight: 4.3 lbs.



1/2" Dual Range Hammer Drills

- Trigger speed control in two ranges: 0-1350 RPM, 0-22 000 BPM, 0-2500 RPM, 0-40 000 BPM, reversing
- A removable side handle assists in setting the depth rod for pre-set hole drilling
- Hammer with rotation or rotation only
- Includes: Depth gauge, side handle and chuck key

Model No. TT928 Mfg. No. 5378-20 Price/Each \$

SPECIFICATIONS

Chuck Size: 1/2"
Amperage: 7.5
No Load RPM: 0-1350/0-2500
No Load BPM: 0-20000/0-40000
Chuck Type: Keyed
Tool Weight: 6.0 lbs.



1/2" VSR Dual Range Hammer Drills

- High/low speed for high speed drilling or high torque applications
- Lightweight design for less user fatigue
 360° side handle with depth
- rod offers greater control
- Includes: Side handle, chuck key and plastic carrying case

Model No. TD944 Mfg. No. DW505K Price/Each \$

SPECIFICATIONS

Chuck Size: 1/2"
Amperage: 7.8
No Load RPM: 0-1100/0-2700
No Load BPM: 0-1900/0-46000
Chuck Type: Keyed
Tool Weight: 4.8 lbs.



DEWALT

1/2" Hammer Drills with Carrying Case

- Anti-vibration system (AVS): Delivers maximum comfort by minimizing vibration
- 2-mode operation: Hammer drill/drill for maximum versatility in wood, metal, and concrete
- 2-speed gear box: Allows the user to select the correct drilling speed for the material and accessory
- 360° side handle with depth gauge
- Includes: Depth gauge, removable side handle and carrying case

Model No. TLZ439 Mfg. No. 5380-21 Price/Each \$

SPECIFICATIONS

Chuck Size: 1/2"
Amperage: 9.0
No Load RPM: 0-1500/0-3500
No Load BPM: 0-24000/0-56000
Chuck Type: Keyed
Tool Weight: 7.3 lbs.



1" D-Handle SDS Rotary Hammer

- SHOCKS Active Vibration Control® reduces vibration felt by the user at the handles
- Variable speed trigger allows user to instantly control speed
- Mode selector allows for usage in rotary hammer, rotary only, and chiseling applications
- Reversing feature helps release tool from bind up situations, and assists with removal of fasteners
- · 360 degree side handle adjusts easily for preference or use in tight spaces

Model No. TLV939 Mfg. No. D25263K Price/Each \$

SPECIFICATIONS



