



Plain Bearing Chucks

- For medium or heavy-duty portable, bench or floor-mounted power tools
- Exceptionally high accuracy, gripping power and durability
- Wide range of capacities for use on threaded and taper-mounted spindles
- Jaws treated to ensure thread life and high gripping surface hardness
- 1-piece sleeve



TAPER-MOUNTED – HEAVY-DUTY MODELS

- Fluted sleeve standard except model **TB844**, which is smooth and ground
- Models **TB839** and **TB846** are equipped with a positive drive slot
- Models **TB840** and **TB847** are equipped with a pin-type positive drive
- Model **TB844** is equipped with locking collar - 1 1/16-20 thread

Model No.	Mfg. No.	Cap. Min."	Cap. Max."	Mount	Key No.	Price /Each
TB838	3A	0.125	0.625	3JT	K3	
TB839	3KD	0.125	0.625	3JT	K3	
TB840	3PD	0.125	0.625	3JT	K3	
TB841	34-02	0.040	0.500	2JT	K3	
TB842	34-06	0.040	0.500	6JT	K3	
TB002	34-33	0.040	0.500	33JT	K3	
TB844	34-33C	0.040	0.500	33JT	K3C	
TB845	36	0.180	0.800	3JT	K4	



Taper-Mounted

TAPER-MOUNTED – MEDIUM-DUTY MODELS

- Fluted sleeve standard except models **TB848** and **TB849**, which are smooth and ground
- All series 33 Plain Bearing Chucks are hammer capable
- Model **TB855** is equipped with a positive drive slot

Model No.	Mfg. No.	Capacity Min."	Capacity Max."	Mount	Key No.	Price /Each
TB848	6200	0.135	0.156	0JT	K0	
UAJ969	JCM6206	0.040	0.250	1JT	K1	
UAD808	JCM6214	0.040	0.375	2JT	K2	
TB853	33	0.08	0.500	33JT	K32	
TB854	3326A	0.08	0.500	0.6250 Straight	K32	
UAJ970	JCM6281	0.08	0.500	33JT	K32	

THREAD-MOUNTED – HEAVY-DUTY MODELS

- Fluted sleeve standard on all models

Model No.	Mfg. No.	Cap. Min."	Cap. Max."	Mount	Key No.	Price /Each
TB856	3B 5/8	0.125	0.625	5/8-16	K3	
UAJ971	JCM6255	0.04	0.250	3/8-24	K7	
TB859	3B 1/2	0.125	0.625	1/2-20	K3	
UAJ973	JCM6316	0.188	0.800	3/4-16	K4	
UAJ974	JCM6314	0.188	0.800	5/8-16	K4	



Thread-Mounted

THREAD-MOUNTED – MEDIUM-DUTY MODELS

Model No.	Mfg. No.	Capacity Min."	Capacity Max."	Mount	Key No.	Price /Each
UAJ975	JCM6204	0.014	0.156	5/16-24	K0	
UAJ976	JCM6208	0.040	0.250	3/8-24	K1	
TB864	2BA 3/8	0.040	0.375	3/8-24	K2	
TB865	41BA 3/8	0.040	0.375	3/8-24	K30	
TB866	41BA 3/8-S	0.040	0.375	3/8-24	K30	
TB867	41BA 1/2	0.040	0.375	1/2-20	K30	
TB868	33BA1/2	0.08	0.500	1/2-20	K32	
UAD807	JCM6283	0.08	0.500	3/8-24	K32	
TB870	33BA 5/8	0.08	0.500	5/8-16	K32	

Ball Bearing Chucks

- For heavy-duty, close tolerance production drilling
- Fits jig borers, milling machines, lathes and radials
- Ball thrust bearings reduce friction
- Jaws are centre-ground for absolute straightness and alignment
- Jaws treated to ensure extended life and high gripping surface hardness
- 1-piece sleeve
- Fluted sleeve standard



Model No.	Mfg. No.	Capacity Min."	Capacity Max."	Mount	Key No.	Price /Each
TB832	8 1/2N	0.040	0.250	2JT	K30	
TB833	11N	0.040	0.375	2JT	K32	
TB834	14N	0.040	0.500	3JT	K3	
TB835	16N	0.125	0.625	3JT	K4	
TB836	18N	0.125	0.750	4JT	K4	
TB837	20N	0.375	1.000	5JT	K5	

Portable Tool Chucks

- Hand-Tite® keyless drill chucks
- Keyless operation
- Made from high performance materials
- Durable, long lasting performance
- Fits all variable speed corded and cordless portable drill



Model No.	Mfg. No.	Capacity	Cap. Min. "	Cap. Max. "	Mount	Wt. lbs.	Price /Each
TT566	30354	3/8" (10 mm)	0.040	0.375	3/8 - 24	1/2	
TT567	31038D	1/2" (13 mm)	0.062	0.50	1/2 - 20	3/4	
TT568	31037D	1/2" (13 mm)	0.062	0.50	3/8 - 24	3/4	

Stainless Keyed Chucks

- For special applications on either portable drills or stationary machine tools
- Mainly used in medical and chemical industries
- Resists chemical corrosion
- Reduces potential for hazardous sparking
- Minimises risk of ferrous contamination in sterile environment
- Stainless steel chucks available in both thread mounting and taper mounting
- **TBR876** and **TBR878** take **TLV651** key
- **UAJ977** and **UAJ978** take **TLV652** key



Model No.	Mfg. No.	Capacity Min."	Capacity Max."	Mount	Price /Each
TDR876	0M	0.028	5/32	#0 JT	
TDR878	0BM 5/16	0.028	5/32	5/16-24	
UAJ977	JCM6627Z	0.028	1/4	5/16-24	

Jacobs®

Jacobs®