



14" Wood Bandsaws w/Resaw Guide

- Adjustable upper/lower ball bearing blade guide system
- Excellent for cutting curves and compound angles
- 10° left, 45° right square tilting table
- Hinged doors for quick access to blade
- Quick connect motor to switch plug for easy-set up
- Includes: Induction motor, built-in drive wheel brush, dust chute, blade, mitre gauge, cabinet stand, rip fence with resaw guide



Model No.	BB552
Mfg. No.	KC-1433FXR
Cutting capacity frame to blade:	13 5/8"
Maximum depth of cut:	6"
Table size:	14" x 14"
Blade size:	93" x (1/8" - 3/4") x 0.025
Speeds:	3 (735-1470-2350 SFPM)
Motor:	10 A @ 110 V, 5 A @ 220 V, 1 phase, 60 Hz
Voltage:	110/220 V
Prewired:	110 V
Dimensions:	26" L x 19" W x 68" H
Weight:	210 lbs.
Price/Each	\$

14" Wood Bandsaws w/12" Resaw Capacity

- Adjustable upper/lower ball bearing blade guide system
- Rack and pinion height adjustment system
- 2 speeds
- 2 - 4" dust chutes for dust collector hook-up
- Quick release blade change lever
- Cutting height indicator
- Square cast-iron table tilts 5° to the left and 45° to the right
- Magnetic switch
- Safety foot brake slows down blade and disconnects electrical circuit for emergency shut-off
- Motor, blade, miter gauge and precision Tru-Rip aluminum rip fence with resaw guide included



Model No.	TMA061
Mfg. No.	KC-1502FXB
Cutting capacity frame to blade:	13 5/8"
Table size:	18" x 18"
Table height from floor:	36 1/2"
Blade size:	112" x (1/8" - 1") x 0.025"
Height of cut:	12"
Motor:	12.8/6.2 A
Voltage:	110 V/ 220 V, 1 phase, 60 Hz
Prewired:	110 V
Speed:	2 (2300-3250) SFPM
Dimensions:	33" L x 44 1/2" W x 73" H
Weight:	230 lbs.
Price/Each	\$

17" Wood Bandsaws w/Resaw Guide

- Improved adjustable upper/lower ball bearing blade guide system
- Rack and pinion height adjustment system
- 2 speeds
- 2 - 4" dust chutes for dust collector hook-up
- Quick release blade change lever
- Cutting height indicator
- Blade tension meter and tracking can be seen through conveniently placed windows
- 10° left/ 45° right square cast iron tilting table
- Hinged doors for quick access to the blade
- Motor, blade, miter gauge and precision Tru-Rip aluminum rip fence with resaw guide included



Model No.	TMA062
Mfg. No.	KC-1702FXB
Cutting capacity frame to blade:	16 1/4"
Table size:	17" x 17"
Table height from floor:	35 1/2"
Blade size:	131 5/8" x (1/8" - 1") x 0.025"
Height of cut:	12"
Motor:	16/8 A
Voltage:	110 V/ 220 V, 1 phase, 60 Hz
Prewired:	110 V
Speed:	2 (1600-3300) SFPM
Dimensions:	32" L x 26" W x 74" H
Weight:	325 lbs.
Price/Each	\$

2-Speed 14" Wood Band Saw

- Adjustable upper/lower ball bearing blade guide system
- Large 21-3/8" x 15-5/8" tilting table with rack & pinion adjustment
- Flexible LED light increases workpiece visibility
- Features a belt tension adjustment knob and rack and pinion height adjustment system
- Features circle cutting guide for diameters up to 27-1/2"
- Dust chute accepts 2", 3" and 4" dust collector hoses
- Includes: Cast aluminum miter gauge, Rip fence with 5" high face, Push stick, Adjustment wrench, Hex keys
- Overall Width: 22-3/4"
- Overall Length: 30"
- Overall Height: 67-3/4"
- Voltage: 120 V
- No Load Speed: 1476 SFPM, 3280 SFPM
- Amps: 9.5 A
- Style: Vertical
- Table Height: 40-1/2"
- Blade Size: 100-5/8" x (1/8" - 1") x 0.025"
- Motor: 1 HP

Model No. UAF567
Mfg. No. KC-1402FX
Price/Each \$



CANADA'S LEADING MATERIAL HANDLING SUPPLIER