



14" x 43" Variable Speed Wood Lathes w/Digital Readout

- Heavy-duty precision cast-iron bed and stand legs ensure stability and minimize operating vibrations
- Spindle tachometer with digital readout
- Variable speed from 600 - 2400 RPM
- Pivoting headstock turns 180° and locks into position for outboard turning
- Quick release headstock, tailstock and tool rest assembly for easy adjustments
- Comes complete with 6" face plate, 12" tool rest with offset and base, MT #2 headstock and tailstock centers and adjustment wrenches



Model No. TMA023
Mfg. No. KWL-1443VS
Swing: 14 1/2"
Distance between centres: 43"
Headstock and tailstock taper: MT #2
Spindle size: 1" x 8 TPI
Spindle bore: 3/8"
Speeds: 600-2400 RPM
Motor: 6.6 A, 1 phase, 60 Hz
Voltage: 110 V
Dimensions: 62" L x 14 1/2" W x 48" H
Weight: 310 lbs.
Price/Each \$

Variable Speed Wood Lathe

- 1 HP high performance induction motor
- Reliable single board computer microprocessor for precise control
- Precise spindle speed digital readout
- 24 indexing positions with spindle lock
- Work light with 18" flex shaft for improved visibility during intricate work
- Heavy-duty precision cast iron bed ensures stability, accepts optional extension bed for turning operations up to 44"
- Comes complete with 4" faceplate, 6" & 12" tool rests with 5/8" post diameter, MT#2 spur centre and MT#2 heavy-duty live centre, safety goggles, knock-out rod, tool storage rack, screwdriver and 4 hex. keys



Model No. TMA104
Mfg. No. KWL-1218VS
Swing Over Bed: 12"
Distance Between Centres: 18"
Spindle Size: 1" x 8 TPI
Spindle Bore: 3/8"
Voltage: 110 V
Spindle Speeds: 2 (450-1800, 950-3800 RPM)
Headstock and tailstock taper: MT#2
Gap in bed: 1-1/4"
Price/Each \$

16" Scroll Saws

- Table tilts to allow angle cutting up to 45°
- Blade holders accept standard 5" pinless and pin type blades
- Adjustable blade tension knob
- Built-in dust blower system



Model No. TBM421
Mfg. No. KC-163SSC-V
Capacity: 16"
Maximum thickness: 2"
Blade length: 5"
Speed: Variable (400-1500 SPM)
Motor: 1.5 A, 1 phase, 60 Hz
Voltage: 110 V
Dimensions: 25" L x 13" W x 12 1/2" H
Weight: 42 lbs.
Price/Each \$

Professional Scroll Saws

- Built-in dust blower system
- Tool free blade change system with blade holders accepts standard 5" pin-less blades
- Large stationary table with built-in 2-1/2" dust chute for dust collector hook-up
- Includes:
 - (5) 5" Pin-less blades,
 - (1) Replacement blade tension lever kit,
 - (1) Adjustment hex key



Model No.	Mfg. No.	Dimensions W" x L" x H"	No Load Speed RPM	Maximum Throat Capacity "	Variable Speed SPM	Price /Each
UA1718	KXL-16	15 x 27 x 17	1400	16	400-1400	
UA1719*	KXL-21/100	15 x 32 x 15	1550	21	400-1550	
UA1720*	KXL-30/100	15.5 x 43.25 x 15.25	1550	30	400-1550	

*Includes (1) foot pedal switch

Foot Pedal

- Fits 16" and 21" scroll saws
- Designed for operation of a Scroll Saw or any other 120V (Max 15 amp.) power tool



Model No.	Mfg. No.	Dimensions W" x L" x H"	Price /Each
TYY153	XL-100	3 x 5 x 2	