



Industrial Screwdrivers



REVERSIBLE, PISTOL GRIP SCREWDRIVERS

- One hand operation reverse valve
- Compact pistol grip
- Roller clutch
- Shut-off clutch



Model No. TG090
Model No. TG091

REVERSIBLE IN-LINE SCREWDRIVERS

- Progressive lever start
- Ideal for centering screws during the fastening cycle
- Roller clutch
- Reversible
- Use for disassembly

Model No. TG092



REVERSIBLE IN-LINE SCREWDRIVERS

- Push-to-start operation
- Quick change reverse operation
- Shut-off clutch
- Ideal for continuous operation
- Positive shut-off at preset torque

Model No. TG093



Model No.	Mfg No.	Free Speed RPM	Torque Range in.-lbs. (Nm) Soft-pull-up Work		CFM	dBA	Vibration m/s ²	Overall Length in. (mm)	Net Weight lbs. (kg)	Price /Each
			Min.	Max.						
TG090	CP2612	1470	3.5 (0.4)	39 (4.4)	14	75	2.3-3.9	72 (182)	1.8 (0.8)	
TG091	CP2611	1000	3.5 (0.4)	38 (4.3)	20	76	<2.5	72 (182)	1.8 (0.8)	
TG092	CP2621	1000	3.5 (0.4)	39 (4.4)	14	77	9-35	9.6 (224)	2.58 (1.2)	
TG093	CP2622	1700	3.5 (0.4)	38 (4.3)	14	81	<2.5	8.8 (223)	1.39 (.7)	

1/4" (NPTF) air inlet thread; 3/8" min. hose size.
Noise levels are at 1.0 m per Pneurop Standard 8N-1. Vibration levels are per ISO 8662-1.

371 Pistol-Grip Screwdriver

- Variable speed control
- Option for top or bottom air inlets
- Chuck Size: 1/4"
- Chuck Type: Keyless



Model No.	Mfg. No.	Air Consumption	Air Inlet	Sound Level (dBA)	No Load RPM	Price /Each
TZ935	371	29	1/4 NPT/1/4" NPTF	78	1800	

41 Series Air Screwdriver

- Features a Pistol Cushion Clutch that limits torque to minimize the amount of vibration experienced by the operator
- Designed for heavy-duty work
- Torque Range: 0 - 64.6 in.-lbs.
- Weight: 2.4 lbs.
- Length: 7.6" (193mm)
- Spindle Type: 1/4" Hex Quick Change



Model No.	Mfg. No.	Air Consumption	Air Inlet	Sound Level (dBA)	No Load RPM	Price /Each
UAE944	41PP17TSQ4	20 CFM	1/4" NPT	78	1700	

Die Grinders Straight & Offset (7°)

- Gearless motor reduces downtime and lessens repair expense compared to geared tools
- Governor-controlled to maintain RPM under heavy load
- Lightweight thermal-insulated housing reduces cold air transmission and vibration to the operator



TGZ172



TGZ073

Model No.	TGZ172	TGZ174	TGZ175	TGZ073
Mfg. No.	52666	52668	52669	48205
Head type	Straight	Straight	Straight	7°
Collet Insert Size:	1/4"	1/4"	1/4"	1/4"
Free Speed (RPM):	12 000	18 000	20 000	25 000
HP (W):	1.0 (746)	1.0 (746)	1.0 (746)	0.4 (224)
Motor Characteristic:	Gearless	Gearless	Gearless	Gearless
Exhaust Type:	Rear	Rear	Rear	Rear
Wt. lbs.:	2.3	2.4	2.4	1.5
Price/Each:				

4" Lightweight Dyninger® Finishing Tools (1/4" Collet)



- Mount 4" dia. spindle-mount dry-cut sanding stars with 1/4" shank. Order stars separately
- Tool includes air-flow control Dynaswivel® fitting for maximum tool manoeuvrability and control
- Eliminates raised grain and removes loose fibres when whitewood sanding as well as scuffing sealer coats



Model No	TGZ792
Mfg. No.	52050
Abrasive Information:	-
Order Separately:	3/4", 1", 1-1/2", 2", 3", & 4", dia. sanding stars (19, 25, 38, 51, 76, & 102 mm)
Air Flow Rate @ 90 PSI:	21 SCFM
Sound Level:	81 dB (A)
Horsepower:	0.40 HP
Free Speed:	0 to 3200 RPM
Air Pressure:	90 PSI
Air Inlet Thread:	1/4 NPT
Hose Size (I.D.):	1/4" (6 mm)
Max. SFPM:	3350 SFPM
Tool Spindle Thread:	3/8"-24 male
Length:	8 3/4" (222 mm)
Height Diameter:	2 3/8" (60 mm)
Weight:	2.2 lbs. (1 kg)
Price/Each:	\$