



Coil Roofing Nailer

- Improved trigger valve design provides quick nail driving in bump fire mode
- 6 Nailing depth settings with adjustment knob for maximum precision
- Tool-less shingle guide provides easy adjustments and consistent shingle placement
- Nail path magnet prevents last nail from falling out
- Convenient adjustable belt hook
- One-touch, magazine is easy to load
- Easy to remove contact top to clear nail/debris jams
- Rubberized grip for increased comfort during prolonged use

Model No. UAG291
Mfg. No. AN454
Operating Air Pressure: 70 - 120 PSI
Nail Length: 3/4 - 1-3/4"
Magazine Capacity: 120 nails
Dimensions: 10 3/8" L x 4 5/8" W x 10 5/8" H
Firing Modes: Bump & Sequential
Price/Each: \$



3 1/2" Framing Nailers

- 3 modes: Sequential, bump, lock-off
- 9 depth nailing setting in 1/16" increments with adjustment knob
- Convenient collapsible rafter hook
- Nose piece with sure-grip spikes
- Dry fire prevention system prolongs life of tool
- Includes: Hook assy, oil supply 30 cc, safety goggles

Model No. TLV232
Mfg. No. AN923
Operating Air Pressure: 65-120 PSI
Nail Size: 2" - 3 1/2"
Nail Type: 0.113" - 0.162" 22° round head
Magazine Capacity: 64-74 nails
Dimensions: 22" L x 4 1/4" W x 13 11/16" H
Tool Weight: 8.7 lbs.
Price/Each: \$



Slim Contact Tip Brad Nailer

- Slim contact tip design enables precise fastening in wood trim, crown moulding, baseboard, casing, cabinetry and other woodworking applications
- Air blower feature cleans material of dust and debris
- Quick-release nose enables fast and easy clearing of jammed nails
- Quick release, side loading magazine holds up to 100 18-gauge brad nails
- Dual windows enable fast identification of remaining nail capacity
- Convenient, adjustable belt hook for operator convenience
- Non-marring nose and side bumpers protect materials from damage
- Soft rubber grip design for comfortable operation

Model No. UAG258
Mfg. No. AF506
Operating Air Pressure: 70 - 120 PSIG
Nail Length: 5/8" - 2"
Nail Gauge: 18 Gauge
Power Type: Pneumatic
Vibration Level: 2.5 m/s2
Noise Level: 86 dB(A)
Price/Each: \$



1/4" Crown Staplers

- 18-gauge crown stapler
- 360° exhaust system directs exhaust away from operator
- Quick release magazine: staples load from the top
- Convenient adjustable belt hook
- Clear window allows operator to see number of remaining staples
- Includes: Oil dispenser, plastic carrying case, safety glasses, wrench 3, wrench 4

Model No. VK854
Mfg. No. AT638A
Operating Air Pressure: 60 - 115 PSI
Staple Size: 5/8" - 1 1/2"
Magazine Capacity: 100 nails
Dimensions: 9 3/4" L x 2 7/16" W x 9 3/4" H
Tool Weight: 3.2 lbs.
Price/Each: \$



3 1/2" Framing Nailers

- 31° clipped head framing strip nailer
- 3 modes: Sequential, bump, lock-off
- 9 depth nailing setting in 1/16" increments with adjustment knob
- Convenient collapsible rafter hook
- Nose piece with sure-grip spikes prevents slipping
- Dry fire prevention system prolongs life of tool
- Includes: Hook assembly, oil supply 30 cc, safety goggles

Model No. TLV234
Mfg. No. AN943
Operating Air Pressure: 65 - 120 PSI
Nail Type: 0.113" - 0.131" 31° clipped head
Nail Size: 2" - 3 1/2"
Magazine Capacity: 60 - 84 Nails
Dimensions: 17 7/8" L x 4 1/4" W x 14 3/8" H
Tool Weight: 8.4 lbs.
Price/Each: \$



2 1/2" Coil Siding Nailers

- 15° round head coil siding nailer
- 360° exhaust system directs exhaust away from the operator
- 3 modes: Sequential, bump, lock-off
- 9 depth nailing settings in 1/16" increments with adjustment knob
- Convenient adjustable belt hook
- Rubberized grip for increased comfort
- Built-in air filter prevents dust or foreign matter from entering the tool
- Includes: Hex wrench 4, plastic carrying case, safety goggles, oil supply

Model No. TDU796
Mfg. No. AN611
Operating Air Pressure: 65 - 120 PSI
Nail Type: 0.80" - 0.99" 15° round head
Nail Size: Wire Collated: 1 1/4" - 2 1/2"
Nail Size: Plastic Collated: 1 1/4" - 2"
Magazine Capacity: 200 - 400 Nails
Dimensions: 13 1/16" L x 5" W x 12 1/2" H
Tool Weight: 4.9 lbs.
Price/Each: \$



Looking for nails? Please see pages 292 - 295

