



Portable Contractor Series Compressors - Oil Lube, Direct Drive

- For professional, farm, home and hobbyists
- Quiet running and low 1720 RPM pump
- Die cast aluminum pump with cast iron sleeves and stainless steel valves for longer life
- All electrical units draw 15 amps or under
- Manual reset for overload protection
- Includes: Regulator, pressure gauge, pressure switch with on/off, universal coupler, filter silencer with replacement element and pump oil
- Air outlet accepts 1/4" industrial male quick connector
- Factory tested prior to shipment
- Not intended for commercial use
- CSA approved
- 1-year limited manufacturer's warranty



TFA008



TFA009



TFA010



Model No.	Mfg. No.	Peak HP	Running HP @ 90 PSI	Actual FAD-CFM 90 PSI	125 PSI	Voltage /Phase	Amp Draw @ 125 PSI	Tank Size (gal.)	Pump RPM	Dimensions L" x W" x H"	Wt. lbs.	Price /Each
TFA008	DD-1004	1	1	4.5	4	115 V/1 PH	15	4	1720	16 x 16 x 23	65	
TFA009	DD-1503	1.5	1.5	6	4.6	115 V/1 PH	14	3.2	1720	22 x 9 x 23	55	
TFA010	DD-2022B	2	1.5	6	4.6	115 V/1 PH	15	4	1720	21 x 20 x 20	80	

King Canada Industrial Compressors

- 2-cylinder cast iron single stage oil lubricated pump
- ASME registered tank and safety valve
- Large intake filters
- Pump with V-style design minimizes vibration, improves cooling and extends compressor life
- Portable units are equipped with 9 1/2" pneumatics wheels and front handle
- Gas units are equipped with a 4-stroke air cooled OHV Honda gas engine



UAJ179



TLV742



UAK066



UAG293



TLV741



Model No.	Mfg. No.	Peak HP	Air Delivery CFM	Max. PSI	Voltage/Phase	Tank Size (gal.)	Amp Draw Motor	Pump RPM	Wt. lbs.	Remarks	Price /Each
UAJ179	KC-2051H2	5.5	7.6 at 40 PSI 6.0 at 90 PSI	150	120/1/240/1	20	N/A	3450	145	Horizontal	
UAG293	KC-3124V2	5.5	- 6.0 at 90 PSI	150	120/1/240/1	24	N/A	3450	160	Vertical	
TLV742	KC-6160V2	6.5	13.4 at 40 PSI 11.2 at 90 PSI	135	240 V/1 PH	60	15	3450	260	Vertical	
UAK066	KC-5160V3	6.5	22.6 at 40 PSI 18.5 at 100 PSI	150	240/1	50	N/A	3450	280	Vertical	
TLV741*	KC-5510G1	5.5	14.1 at 40 PSI 11.2 at 90 PSI	150	5.5 HP Gas	10(2x5)	N/A	3600	165	Twin Horizontal	

*Gas powered