



## Airflo Modular Filter/Regulators

- Removes water through centrifugal force
- Filters contaminants down to 5 micrometres
- Accurate pressure control
- Pressure gauge and mounting bracket included

**TOPRING**

Model No.	Mfg. No.	Port Size"	Max Air Flow @ 100 PSI	Max PSI	Reduced Pressure Range	Bowl Type	Bowl Capacity	Drain	Gauge Port Size"	Series	Price /Each
TLZ608	51.250	1/4 (F) NPT	19 SCFM	150	5-125 PSI	Polycarbonate w/steel guard	0.5 fl.oz.	Semi-auto	1/8 (F) NPT	200	
TLZ627	51.350	1/4 (F) NPT	70 SCFM	150	5-125 PSI	Polycarbonate w/steel guard	0.7 fl.oz.	Semi-auto	1/8 (F) NPT	300	
TLZ629	51.355	3/8 (F) NPT	70 SCFM	150	5-125 PSI	Polycarbonate w/steel guard	0.7 fl.oz.	Semi-auto	1/8 (F) NPT	300	
TLZ653	51.450	3/8 (F) NPT	141 SCFM	150	5-125 PSI	Polycarbonate w/steel guard	1.6 fl.oz.	Semi-auto	1/4 (F) NPT	400	
TLZ655	51.455	1/2 (F) NPT	141 SCFM	150	5-125 PSI	Polycarbonate w/steel guard	1.6 fl.oz.	Semi-auto	1/4 (F) NPT	400	



## Airflo Modular Filters

- Removes water through centrifugal force
- Filters contaminants down to 5 micrometres
- Mounting bracket included

**TOPRING**

Model No.	Mfg. No.	Port Size"	Max Air Flow @ 100 PSI	Max PSI	Bowl Type	Bowl Capacity	Drain	Series	Price /Each
TLZ609	51.260	1/4 (F) NPT	27 SCFM	150	Polycarbonate w/steel guard	0.5 fl.oz.	Semi-auto	200	
TLZ631	51.360	1/4 (F) NPT	70 SCFM	150	Polycarbonate w/steel guard	0.7 fl.oz.	Semi-auto	300	
TLZ633	51.365	3/8 (F) NPT	70 SCFM	150	Polycarbonate w/steel guard	0.7 fl.oz.	Semi-auto	300	
TLZ657	51.460	3/8 (F) NPT	141 SCFM	150	Polycarbonate w/steel guard	1.6 fl.oz.	Semi-auto	400	
TLZ659	51.465	1/2 (F) NPT	141 SCFM	150	Polycarbonate w/steel guard	1.6 fl.oz.	Semi-auto	400	
TLZ675	51.560	3/4 (F) NPT	247 SCFM	150	Die cast alum w/sight glass	4.4 fl.oz.	Semi-auto	500	
TLZ677	51.565	1 (F) NPT	247 SCFM	150	Die cast alum w/sight glass	4.4 fl.oz.	Semi-auto	500	



## Airflo Modular Regulators

- Removable locking Push/Pull adjusting knob
- Accurate pressure control
- Pressure gauge and mounting bracket included

**TOPRING**

Model No.	Mfg. No.	Port Size"	Reduced Pressure Range	Max Air Flow @ 100 PSI	Max PSI	Gauge Port Size"	Series	Price /Each
TLZ605	51.240	1/4 (F) NPT	5-125 PSI	19 SCFM	150	1/8 (F) NPT	200	
TLZ621	51.340	1/4 (F) NPT	5-125 PSI	70 SCFM	150	1/8 (F) NPT	300	
TLZ624	51.345	3/8 (F) NPT	5-125 PSI	70 SCFM	150	1/8 (F) NPT	300	
TLZ647	51.440	3/8 (F) NPT	5-125 PSI	212 SCFM	150	1/4 (F) NPT	400	
TLZ650	51.445	1/2 (F) NPT	5-125 PSI	212 SCFM	150	1/4 (F) NPT	400	
TLZ669	51.540	3/4 (F) NPT	5-125 PSI	282 SCFM	150	1/4 (F) NPT	500	
TLZ672	51.545	1 (F) NPT	5-125 PSI	282 SCFM	150	1/4 (F) NPT	500	



## Airflo Modular Lubricators

- Lubrication automatically proportioned to air flow
- Mounting bracket included

**TOPRING**

Model No.	Mfg. No.	Port Size"	Max Air Flow @ 100 PSI	Max PSI	Bowl Type	Bowl Capacity	Series	Price /Each
TLZ604	51.230	1/4 (F) NPT	28 SCFM	150	Polycarbonate w/steel guard	0.85 fl.oz.	200	
TLZ619	51.330	1/4 (F) NPT	70 SCFM	150	Polycarbonate w/steel guard	1.7 fl.oz.	300	
TLZ620	51.335	3/8 (F) NPT	70 SCFM	150	Polycarbonate w/steel guard	1.7 fl.oz.	300	
TLZ645	51.430	3/8 (F) NPT	176 SCFM	150	Polycarbonate w/steel guard	1.6 fl.oz.	400	
TLZ646	51.435	1/2 (F) NPT	176 SCFM	150	Polycarbonate w/steel guard	1.6 fl.oz.	400	
TLZ667	51.530	3/4 (F) NPT	247 SCFM	150	Die cast alum. w/sight glass	4.4 fl.oz.	500	
TLZ668	51.535	1 (F) NPT	247 SCFM	150	Die cast alum. w/sight glass	4.4 fl.oz.	500	



## Airflo Modular Piping Adaptors

- Each item listed below includes two adaptors

**TOPRING**

Model No.	Mfg. No.	Port Size"	Series	Price /Each
TLZ690	51.950	1/4 (F) NPT	200	
TLZ691	51.951	1/4 (F) NPT	300	
TLZ692	51.952	3/8 (F) NPT	300	
TLZ693	51.953	3/8 (F) NPT	400	
TLZ694	51.954	1/2 (F) NPT	400	
TLZ695	51.955	3/4 (F) NPT	500	
TLZ696	51.956	1 (F) NPT	500	

