

### **CFC Free Electro** Contact Cleaner

- Fast evaporation
- No residue
- Low odour
- Non-conductive
- Safe on plastics
- Inverta spray valve allows you to spray in an upright or inverted position
- NSF registered category code K2



Model No.	Mfg. No.	Size	Price /Each	Qty	Qty Price /Each
AA784	C03116	11 oz.			
AB546	C03101	1 gal.			
AB544	C03105	5 gal.		-	-
AB545	C03155	55 gal.		-	-



- Reduced VOC's (Volatile Organic Compounds) content and conforms to CARB (California Air Resources Board). OTC (Ozone Transport Commission) and LADCO (Lake Michigan Air Directors Consortium) VOC regulations
- Removes dirt, flux, moisture, dust, and other contaminants from electrical equipment
- Fast evaporating, safe on plastics
- Will not leave a residue

C05416

NSF registered category code K2



				_	
		Price	(	ty Price	
	Size	/Each	Qty	/Each	
(	11 07				

## Revo 66® **Contact Cleaner**

- Ideal for removing dirt, moisture, flux or oxides from the internal components of electronic equipment
- Non-flammable precision cleaning
- Does not contain brominated solvents
- Fast evaporating
- Non-conductive
- Quick penetration
- No rinsing and no residue
- Safe to use on most surfaces
- NSF registered category code K2 Accepted for use in Canadian food processing facilities



Model	Mfg.		Price	(	ty Price
No.	No.	Size	/Each	Qty	/Each
AD010	(04416	12 07			

### Electro 140° Contact Cleaner

- Flash point above 140°F (60°C)
- Superior wetting and penetrating action
- Controlled evaporation
- No residue
- Non-conductive
- Safe to use on most surfaces
- Inverta spray valve allows you to spray in an upright or inverted position





Model	Mfg.		Price	(	ty Price
No.	No.	Size	/Each	Qty	/Each
AA836	C00916	11 oz.			

#### NoFlash® NU Precision Contact Cleaner

- Does not contain chlorinated solvents
- Non-flammable precision cleaning
- No flash point
- Fast drying

AD177

- Quick penetration and evaporation
- No rinsing and no residue
- Safe to use on most surfaces





-	75	

Model No.	Mfg. No.	Size	Price /Each	Qty	Qty Price /Each
AA860	C04015	12 oz.			

#### **Micro-X Fast Evaporating Contact Cleaner**

- Fast evaporation
- Quick penetration
- No residue
- Low odour
- Safe on plastics
- No rinsina
- Inverta spray valve allows you to spray in an upright or inverted position



Model	Mfg.		Price	(	(ty Price
No.	No.	Size	/Each	Qty	/Each
AA837	C04516	11 oz.			
AB549	C04555	55 gal.		-	-

#### **QB Precision Duster**

- Quick blast precision duster removes contaminants, dirt, dust and other soils
- Moisture free
- No residue
- No flash point
- Odourless





## **Electro Contact Cleaner**

- No ozone depletion potential
- Fast penetration
- Quick evaporation
- Penetrates into minute spaces
- Cleans/degreases delicate mechanisms
- Ideal for electrical/electronic fine parts
- Removes light greases, oils,
- dirt and organic soils

C00416

No rinsing and no residue Safe to use on most surfaces









•	sale Cleaner
	Formulated for contact clea
•	Fast evaporation

**PSC Plastic** 

- anina
- No flash point
- No rinsing and no residue
- Displaces moisture
- Very low odor
- No CFC's



Model	Mfg.		Price	(	ty Price
No.	No.	Size	/Each	Qty	/Each
AB700	C04620	18 oz.			

# Lectra Clean® **Heavy-Duty Electrical Parts** Degreaser

- A chlorinated based degreaser that quickly removes grease, oil and dirt from motor parts and other similar equipment
- NSF Registered K2





Model	Mfg.		Price	(	Qty Price
No.	No.	Size	/Each	Qty	/Each
AF103	72018	539 g			

## **QD™** Contact Cleaner

14 07

- Plastic safe: Yes
- Flashpoint: Less than -18°C
- Very fast evaporation rate
- Suitable for cleaning sensitive electronics and electrical equipment
- Use where lower flashpoint cleaners are acceptable
- Accepted for use in Canadian food processing facilities

NSF Registered K2



	R	

Model	Mfg.		Price	(	ty Price
No.	No.	Size	/Each	Qty	/Each
MLN874	72130	312 g			

# Freeze Spray

- Plastic Safe: Yes
- No flashpoint
- Very fast evaporation rate
- Aerosol coolant system that instantly freezes surfaces to -60°F, dissipating heat and cooling equipment
- Assists in locating thermal intermittent components, failures and shorts
- Safe to use on sensitive components and all surfaces finishes



	(₩	
lah	Mfm	

	y /Each
<b>NE971</b> 74086 284 g	