



Tools - Fits C-31IW, C-32IW, C-33IW, C-44IW & C-45IW

1/2" IW (INTEGRAL WOUND) SOLID CORE CABLES (12 MM)



Model No.	Mfg. No.	Cat No.	Description	Price /Each	Replacement Blade
TPX284	62990	T-201	Straight Auger, 5" Long		-
TPX285	62995	T-202	Bulb Auger, 1 1/8" O.D.		-
TPX286	63000	T-203	Bulb Auger 7/8" O.D.		-
TPX299	63065	T-217	Drop Head, 4" Long		-
TPX287	63005	T-205	"C" Cutter 1 3/8"		TTX939
TPX288	63010	T-206	Funnel Auger, 3" Long		-
TPX289	63015	T-207	Spiral Cutter, 1 1/4"		TTX940
TPX290	63020	T-208	Spiral Cutter, 1 1/2"		TTX958
TPX291	63025	T-209	Spiral Cutter, 2"		TTX960
TPX292	63030	T-210	Grease Cutter, 1"		TTX962
TPX293	63035	T-211	Grease Cutter, 1 3/8"		TTX936
TPX294	63040	T-212	Grease Cutter, 1 3/4"		TTX174
TPX295	63045	T-213	4-Blade Cutter, 1"		TTX926
TPX296	63050	T-214	4-Blade Cutter, 1 3/8"		TTX963
TPX297	63055	T-215	4-Blade Cutter, 1 3/4"		TTX964
TPX298	63060	T-216	Chain Knocker, 2"		TTX988
TMX014	49002	T-260	Tool Set (3/8") - T-202 Bulb Auger - T-205 "C" Cutter - T-211 Spade Cutter - A-13 Pin Key		-
TCX075	12128	T-240	Tool Set (3/8") - T-202 Bulb Auger - T-211 Spade Cutter - A-13 Pin Key		-

ACCESSORIES

Model No.	Mfg. No.	Cat No.	Description	Weight		Price /Each
				lbs.	kg	
TNX424	59230	A-13	Pin Key For 3/8" Cable	-	-	
TNX422	59225	A-12	Pin Key For 1/2" Cable	-	-	
TNX566	59782	-	Two-Wheel Transport Cart	18	8.2	
TSX317	87077	-	K-380 Drum Assembly	10.0	4.5	
TTX116	92607	-	3/8" x 1/2" Tool Adaptor	0.5	0.2	
TTX136	92682	-	3/8" x 1/2" Drop Head Adaptor	0.5	0.2	
TTX138	92687	-	Coupling 1/2" Drop Head Tool	0.5	0.2	

K-6200 Drain Cleaners

FOR 3" TO 6" (75-150 MM) DRAIN/SEWER LINES

- Superior manoeuvrability and a small footprint allow easy access to tight work areas
- New more kink-resistant solid core alternative cable
- Torque limiter - Causes the drum to slow down when the blade becomes lodged in a blockage
- 4/10 HP universal motor and gearbox
- Drum requires no adjustments to stay aligned
- Easy maintenance construction
- Low centre of gravity frame design and custom kickstand keep machine firmly anchored during operation
- Powerful feed mechanism is built to last
- Autofeed, toolbox, and selection of cutters included in all models
- CSA approved
- Approved to UL standards (NRTLCL)

SPECIFICATIONS:

Line Capacity:	3"-6" lines, up to 200'
Drum Capacity:	100' of 5/8" cable
Motor:	
Type:	115 V/60 Hz, Reversible, Universal AC Motor
Rating:	4/10 HP, 285 RPM
Amps:	5.6
Weight (Machine & 100 ft of Cable):	180 lbs.
Length:	29 1/2"
Height:	43.5" (Max.)
Width:	18 3/4"

MACHINE OPTIONS - POWER FEED

Model No.	Mfg. No.	Cat No.	Description	Weight		Price /Each
				lbs.	kg	
TTX648	95737	K-6200	Machine w/5/8" Pigtail and Standard Accessories	98	44.54	
TTX647	95732	K-6200 w/C-24	Machine, Standard Accessories and w/ C-24 5/8" x 100' Inner Core Cable	180	81.81	
TTX323	93557	K-6200 w/C-24-HD	Machine, Standard Accessories and w/ C-24-HD 5/8" x 100' HD Inner Core Cable	180	81.81	

