



High-Lift Transmission Jack

- Ideal for larger vehicles such as trucks and buses
- Oversized base and heavy wall tubing provide better stability
- Convenient foot-operated air pump provides smoother handling and positioning
- Base Dimension: 46"D x 46"W
- Maximum Forward Tilt: 50°
- Maximum Backward Tilt: 38°
- Maximum Side Tilt: 14°
- Manufacturer Warranty: OTC Lifetime Marathon Warranty®



OTC

Model No.	Mfg No.	Lifting Capacity	Lowered Height"	Raised Height"	Price /Each
LW001	5078	1 Ton	41-1/2	65	

High-Lift Transmission Jack

- Safety overload feature prevents use beyond its rated capacity
- Universal mounting head can be tilted for better alignment and features adjustable corner brackets
- Includes safety chain to securely hold mechanism in place
- Caster Material: Polyurethane
- Caster Type: 2 swivel casters and 2 locking swivel casters
- Base Dimension: 37-1/8"D x 37-1/8"W
- Maximum Forward Tilt: 24°
- Maximum Backward Tilt: 19°
- Maximum Side Tilt: 20°



OTC

Model No.	Mfg No.	Lifting Capacity	Lowered Height"	Raised Height"	Price /Each
LW012	1793A	0.5 Tons	35	71-5/8	

Two-Stage Transmission Jack

- Air-assist primary stage is designed to quickly raise mounting head
- Hydraulic secondary stage is used to accurately align the adapter with the transmission
- Safety overload feature prevents use beyond its rated capacity
- Includes safety chain to securely hold mechanism in place
- Foot pedal is used during the primary stage and hand pump is used during the secondary stage
- Caster Material: Polyurethane
- Caster Type: 2 swivel casters and 2 locking swivel casters
- Base Dimension: 37-1/8"D x 37-1/8"W
- Maximum Forward Tilt: 42°
- Maximum Backward Tilt: 46°
- Maximum Side Tilt: 12°



OTC

Model No.	Mfg No.	Lifting Capacity	Lowered Height"	Raised Height"	Price /Each
LW010	1794A	0.5 Tons	37-5/8	76-1/2	

Two-Stage Transmission Jack

- Features two-stage hydraulic cylinder design
- Includes folding foot pedal for added precision and control
- Features universal mounting head with wide tilt range for better alignment
- Base Dimension: 41"L x 41"W
- Maximum Forward Tilt: 50°
- Maximum Backward Tilt: 20°
- Maximum Side Tilt: 10°
- Handle Type: Ergonomic
- Compliant: ANSI & PALD



OTC

Model No.	Mfg No.	Lifting Capacity	Lowered Height"	Raised Height"	Price /Each
LW009	5237	0.5 Tons	34-1/2	75	

Two-Stage Transmission Jack

- Air-assist primary stage is designed to quickly move adapter into position
- Hydraulic secondary stage is used to accurately align the adapter with the transmission
- Safety overload feature prevents use beyond its rated capacity
- Convenient foot pedal provides smoother and faster handling
- Caster Type: Locking swivel casters
- Base Dimension: 41"D x 41"W
- Maximum Forward Tilt: 50°
- Max Backward Tilt: 20°
- Maximum Side Tilt: 10°
- Manufacturer Warranty: OTC Lifetime Marathon Warranty®



OTC

Model No.	Mfg No.	Lifting Capacity	Lowered Height"	Raised Height"	Price /Each
LW008	1728	0.5 Tons	34-1/2	75	



SAFETY PRODUCTS FOR INDUSTRY