




Saf-T-Lok Bars

- Designed for economy and ease of operation
- Constructed with high strength industrial round tubing
- Easy to close and lock with its heavy-duty steel rack, handle and cast aluminum housing
- Replaceable molded pivoting rubber feet, 2" x 4" that grip firmly to trailer walls
- Easy to open trigger release
- Adjusts from 90" to 105"
- Optional cargo hoop set, two hoops, which bolts quickly and easily to provide greater area of holding surfaces (installation hardware included)
- Available in either steel or aluminum versions
- Extra long steel version is available upon request



KH575



KH574

KINEDYNE
The Cargo Control People!™

Model No.	Mfg. No.	Description	Wt. lbs.	Price /Each
ND698	10085	Steel Saf-T-Lok Bar	11.4	
KH574	10088	Aluminum Saf-T-Lok Bar	8.5	
KH575	10096	Cargo Hoop Set	13.3	

Jack Bars

- Designed to hold securely in place
- Constructed with high strength industrial square tubing
- Patented quick-release handle assembly which allows the operator to quickly adjust the length of the bar
- Durable jacking mechanism that securely hold the bar in place
- Replaceable molded pivoting 4" x 4" rubber feet, that grip firmly to trailer walls
- Adjusts from 86" to 114"
- Galvanized finish



PE108


KINEDYNE
The Cargo Control People!™

Model No.	Mfg. No.	Description	Wt. lbs.	Price /Each
PE108	JB101XL	Square One Piece Jack Bar	17.2	

Logistic Tracks

SERIES E TRACK HORIZONTAL

- Material: High strength 12-gauge steel
- Minimum Yield: 50 000 PSI
- Finished: Galvanized
- Weight: 16.2 lb.
- Length: 10 ft.



Model No. ND359
Mfg. No. 43001
Price/Each \$

KINEDYNE
The Cargo Control People!™

Warning:

Welding galvanized material may form toxic fumes. Welding should be done with adequate ventilation.

Rope Tie-Offs

- Made with 2" wide 4900G webbing and include 1-27 D-Ring hardware
- Are tagged to comply with North America Cargo Securement Standards
- Working Load Limit: 1,000 lbs.
- Fitting Length: 6"




Model No. PG110
Mfg. No. 660001
Price/Each \$

KINEDYNE
The Cargo Control People!™

Corner Protectors

- Designed to protect both straps and cargo from damage caused by the load
- Steel protectors feature a corner recess to protect cargo edges
- Material: Steel
- Length: 5"
- Width: 5"



PG096

Model No. PG096
Mfg. No. 1863
Price/Each \$



PG097

Model No. PG097
Mfg. No. 1865
Price/Each \$

KINEDYNE
The Cargo Control People!™

Aluminum Decking/Shoring Beams

- For 96" and 102" trailers
- Made from extruded high strength aluminum
- Designed to give maximum strength at the least possible weight
- Keyhole slot allows the beams to be hung and stored in the trailer out of the way when they are not in use
- Decking/Vertical Rating: 2200 lbs. uniformly distributed working load limit
- Head assemblies are all steel, zinc-plated and tapered for ease of operation
- Shoring/Horizontal Rating: 2000 lbs. uniformly distributed working load limit

Note: Working load limits are 1/3 of the ultimate breaking strength.

Model No. ND360
Mfg. No. FE8066-3
Price/Each \$



KINEDYNE
The Cargo Control People!™



Chains

Kinedyne® allows consumers to buy chain pre-cut and assembled with grab hook in an "Easy to Carry - Easy to Store Box"

- All Chain is Transportation Grade 70
- Precut to either 16, 20 or 25 foot lengths
- Comes fully assembled with installed grab hooks
- Gold dichromate finish
- All markings & ratings are compliant with the National Association of Chain Manufacturers (NACM)



KINEDYNE
The Cargo Control People!™

Model No.	Mfg. No.	Length'	Chain Size"	Working Load Limit lbs.	kg	Price /Each
PE963	10034-16BX	16	5/16	4700	2135	
PE964	10034-20BX	20	5/16	4700	2135	
PE965	10034-25BX	25	5/16	4700	2135	
PE966	10038-16BX	16	3/8	6600	3000	
PE967	10038-20BX	20	3/8	6600	3000	
PE968	10038-25BX	25	3/8	6600	3000	