



Edge® FTT Motor Oil

- Three times stronger against viscosity breakdown
- The unique titanium technology physically changes the way oil behaves under extreme pressures doubling its film strength
- preventing oil from breaking down and reducing friction to maximize engine performance.
- Oil Type: Synthetic
- Motor Type: Gasoline

AF646



AF655



Model No.	Mfg. No.	Format	Container Type	SAE Grade	Price /Each
AF642	201738	1 L	Bottle	0W20	
AF643	020173A	5 L	Jug	0W20	
AF644	201715	60 L	Drum	0W20	
AF645	201706	208.2 L	Drum	0W20	
AF646	201238	1 L	Bottle	0W30	
AF647	201838	1 L	Bottle	0W40	
AF648	020183A	5 L	Jug	0W40	
AF649	201806	208.2 L	Drum	0W40	
AF650	200938	1 L	Bottle	5W20	
AF651	020093A	5 L	Jug	5W20	
AF652	200915	60 L	Drum	5W20	
AF653	200906	208.2 L	Drum	5W20	
AF654	201138	1 L	Bottle	5W30	
AF655	020113A	5 L	Jug	5W30	
AF656	201115	60 L	Drum	5W30	
AF657	201106	208.2 L	Drum	5W30	
AF658	201438	946 ml	Bottle	5W40	
AF659	020143A	5 L	Jug	5W40	
AF660	201406	208.2 L	Drum	5W40	
AF661	201038	1 L	Bottle	5W50	
AF662	020103A	5 L	Jug	5W50	
AF663	201006	208.2 L	Drum	5W50	
AF664	201338	1 L	Bottle	10W30	
AF665	020133A	5 L	Jug	10W30	

Vecton® CK-4 Motor Oil

- Castrol Vecton provides outstanding resistance to nitration and oxidation
- Castrol Vecton provides improved cold-temperature engine starting
- Reduced oil consumption relative to single-grade natural gas-fueled engine oils
- Oil Type: Part Synthetic
- Motor Type: Gasoline

AF588



AF589



Model No.	Mfg. No.	Format	Container Type	SAE Grade	Price /Each
AF588	15AEA9	946 ml	Bottle	15W-40	
AF589	15AA34	3.78 L	Jug	15W-40	
AF590	15AEA8	18.9 L	Pail	15W-40	
AF591	15AEEA	208 L	Drum	15W-40	

Edge® EP Motor Oil

- The strength to perform for 24,000 kilometers between oil changes
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures
- Proprietary titanium additive provides unsurpassed wear protection
- Oil Type: Synthetic
- Motor Type: Gasoline

AF666



AF671



Model No.	Mfg. No.	Format	Container Type	SAE Grade	Price /Each
AF666	206038	1 L	Bottle	0W20	
AF667	206089	4.4 L	Jug	0W20	
AF668	206566	1 L	Bottle	5W20	
AF669	206589	4.4 L	Jug	5W20	
AF670	206166	1 L	Bottle	5W30	
AF671	206189	4.4 L	Jug	5W30	

Vecton® CK-4 LD Motor Oil

- Excels under high-pressure: engine combustion pressures are increasing, which puts increased pressure on key engine parts
- Performs at high temperature – engine oil is subjected to areas of very high temperature in modern engines, causing oxidation and oil thickening
- Offers drain intervals of up to 80,000 miles or 1000 hours
- Oil Type: Part Synthetic
- Motor Type: Gasoline

AF592



AF593



Model No.	Mfg. No.	Format	Container Type	SAE Grade	Price /Each
AF592	15ABF6	3.78 L	Jug	10W-30	
AF593	15ABF4	18.9 L	Pail	10W-30	
AF594	15ABF3	208 L	Drum	10W-30	