



Vehicle Fitting Assortments

- Box contains six types of popular fittings
- An identifying chart is included in the cover



AA720

ASSORTMENT INCLUDES:

Model No.	Type	Thread	Quantity
AA677	Str.	1/8" P.T.F.	24
AA686	45°	1/8" P.T.F.	12
AA680	90°	1/8" P.T.F.	12
AA684	Str.	1/4"-28 Taper	24
AA683	45°	1/4"-28 Taper	12
AA689	90°	1/4"-28 Taper	12

Model No. AA720 Price/Each \$

Metric Fitting Assortments

- Box contains six types of popular metric fittings
- An identifying chart is included in the cover
- Thread conforms to German Standard DIN 71412



AB820

ASSORTMENT INCLUDES:

Model No.	Type	Thread	Quantity
AB845	Str.	6	10
AB839	45°	6	6
AB840	90°	6	6
AB844	Str.	8	6
AB841	90°	8	6
AB842	Str.	10	10

Model No. AB820 Price/Each \$

Pocket Pack Fitting Assortments

- Box contains six types of popular fittings
- An identifying chart is included in the cover



AB826

ASSORTMENT INCLUDES:

Model No.	Type	Thread	Quantity
AA677	Str.	1/8" PTF	12
AA686	45°	1/8" PTF	6
AA680	90°	1/8" PTF	6
AA684	Str.	1/4"-28 Taper	12
AA683	45°	1/4"-28 Taper	6
AA689	90°	1/4"-28 Taper	6


Model No. AB826 Price/Each \$

Lubrication Bulk Fittings 1/4" - 28 Taper Threads


- Used on most cars and trucks and on many industrial machines
- Features dirt excluding ball check
- Maximum pressure: 10 000 PSI

It is recommended that SAE-LT taper threads be assembled into 1/4" - 28 UNF, Class 3B, straight threaded holes having a modified maximum minor diameter of 0.2151" to insure 75% minimum thread height.


SAE-LT - conforms to Society of Automotive Engineers lubrication thread specification.




AA684




AA685



AA497



AA683




AA689

Model No.	Mfg. No.	Type	Overall Length"	Shank Length"	Hex Size"	Price /Each
AA684	1641-B	Str.	35/64	3/16	5/16	
AA685	1652-B	Str.	11/16	23/64	5/16	
AA497	1698-B	Str.	1 1/8	25/32	5/16	
AA683	1637-B1	45°	13/16	13/64	3/8	
AA689	1911-B1	90°	3/4	13/64	3/8	




1/8" Pipe Threads


- Used on many industrial machines and heavy equipment
- Features dirt excluding ball check
- Maximum pressure: 10 000 PSI



AA677




AA676




AA678



AA686



AA679




AA680

Model No.	Mfg. No.	Type	Overall Length"	Shank Length"	Hex Size"	Price /Each
AA677	1610-BL	Str.	11/16	19/64	7/16	
AA676	1607-B	Str.	1 1/4	25/32	7/16	
AA678	1611-B	30°	29/32	19/64	7/16	
AA686	1688-B	45°	57/64	19/64	7/16	
AA679	1612-B	65°	27/32	19/64	7/16	
AA680	1613-B	90°	27/32	19/64	7/16	

Drive Fittings


- Used extensively to avoid tapping costs in a wide variety of applications
- Alemite serrated shank grips securely and simplifies the replacement of damaged fittings in old or oversized holes
- Recommended only for low and medium pressures

IMPORTANT
Actual drill sizes cannot be shown because drilling varies with hardness of metal. Drill sizes indicated on drawings are merely a guide. Exact drill size can only be determined by sample drilling of the actual metal. When drilled to proper tolerance, the serrated edge of the fitting will provide a secure, lasting grip.



FOR 3/16" DRILL

AA687




FOR 1/4" DRILL

AA688


Model No.	Mfg. No.	Type	Overall Length"	Shank Length"	Drill Dia."	Price /Each
AA687	1728-B	Str.	33/64	1/4	3/16	
AA688	1743-B	Str.	35/64	1/4	1/4	

1/4" Pipe Threads

- Widely used for larger bearings on farm machinery and heavy industrial equipment
- Recommended for heavy lubricants in cold weather
- Features dirt excluding ball check
- Maximum pressure: 10 000 PSI



AA681



AA682

Model No.	Mfg. No.	Type	Overall Length"	Shank Length"	Hex Size"	Price /Each
AA681	1627-B	Str.	7/8	27/64	9/16	
AA682	1629-B	67 1/2°	31/32	11/32	9/16	