



FEM Industrial Light Fixture

- Created to withstand challenging environments, the fibreglass housing can handle both wet and cold locations
- Ideal for parking garages, industrial facilities, retail malls, multi-purpose centres and airports where low mounting heights and wide fixture spacings are common
- Lamp not included
- Bulb Type: Fluorescent
- Voltage: 120 V
- Overall Dim.: 52" L x 7" W x 4.75" H
- Manufacturer's Warranty: 1 Year Limited



Model No.	Mfg. No.	Wattage	Bulb Shape	Bulb Length"	No. of Lamps	Price /Each
XI384	26148L	54 W	T5, T5HO	46	2	
XI385	260SKE	32 W	T8	48	8	

FHE Food Processing Light Fixture


- Designed for use in food and beverage processing environments
- Rated for both cold weather and wet-location environments
- The one-piece fibreglass enclosure creates a safe environment for the fixture, while being easy to service and clean
- Bulb Type: Fluorescent
- Wattage: 54 W
- Overall Dim.: 52" L x 14.38" W x 6" H
- Bulb Shape: T5, T5HO
- Manufacturer's Warranty: 1 Year Limited



Model No.	Mfg. No.	Voltage	No. of Lamps	Price /Each
XI386	239EE2	347 V	4	
XI387	210UPN	120 - 277 V	6	

I-Beam® IBE High Bay Light Fixture

- Designed to meet the challenges of warehouse and light industrial applications
- Mounting heights up to 40'
- Replaces traditional metal halide light fixtures
- Dimmable LEDs extend the life of the fixture
- Versatile mounting including suspension by chain, cable, surface-mounting bracket, hook monopoint or single (pendant) monopoint
- Die-formed aluminum alloy made of heavy-duty code gauge (20-gauge) steel, which is powder coated after fabrication
- Designed for durability with standard clear diffuse acrylic lens
- 6kV surge protection and cUL certified in the USA and Canada and listed for Damp Locations, meets industrial ANSI standards for added protection against electrical over-stresses
- Rated for 45°C high ambient temperatures up to 55°C with thermal foldback
- Voltage: 120 - 277 V
- Overall Dim.: 22" L x 14.88" W x 4.75" H
- CRI: 80
- Colour Temperature: 4000 K
- Manufacturer's Warranty: 5 Year Limited



Model No.	Mfg. No.	Wattage	Lumens	Price /Each
XI391	25108E	83 W	12000	
XI392	2503P2	107 W	15000	
XI393	25109C	166 W	22000	

XVML Vapour Tight Light Fixture

- Ideal for outdoor venues, canopies, locker rooms, passageways, under eaves, covered patios, open bays and most other applications where moisture and dirt are a concern
- UV-stabilized, high-impact, frosted polycarbonate lens for uniform light output and high-impact resistance
- Replaces up to 4-lamp 32W T8 fluorescent fixtures
- 0 - 10 volt dimming driver, dims to 10%
- UL/C-UL listed and code compliant CSA certified to US and Canadian safety standards, wet location listed, DLC qualified
- Light grey, fully gasketed, polycarbonate housing with ten polycarbonate captive latches provides a watertight seal
- Voltage: 120 - 277 V
- Wattage: 49 W
- Lumens: 5000
- Overall Dim.: 47.75" L x 3.25" W x 3" H
- CRI: 80
- Ingress Protection Rating: IP66
- Manufacturer's Warranty: 5 Year Limited



Model No.	Mfg. No.	Colour Temperature	Price /Each
XI424	262EYT	4000 K	
XI425	262EYU	5000 K	

I-Beam® IBZ High Bay Light Fixture

- Works well in manufacturing facilities, warehouses and other indoor commercial applications
- Quick and easy installation, coupled with high light output
- Mounting heights between 15' to 40'
- Bulb Type: Fluorescent
- Wattage: 54 W
- Bulb Shape: T5, T5HO
- Colour Temperature: 4100 K
- Manufacturer's Warranty: 1 Year Limited



Model No.	Mfg. No.	Voltage	Overall Dim. L" x W" x H"	No. of Lamps	Price /Each
XI394	201FNL	120 - 277 V	48.06 x 13.25 x 2.38	4	
XI395	210E2H	347 - 480 V	48.06 x 13.25 x 2.38	4	
XI396	210G4K	347 - 480 V	48.06 x 18.13 x 2.38	6	

JEBL High Bay Light Fixture

- Unique round design makes the JEBL extremely versatile and highly durable and delivers comfortable and uniform lighting
- Can be used in multiple indoor and outdoor applications, for use under covered ceilings
- 0 - 10 volt dimming driver, dims to 10%
- UL/C-UL listed to US and Canadian Safety Standards, wet location listed
- Features a white die-cast aluminum housing, quick-disconnect driver housing and 6kV surge protection
- Mounting heights up to 30'
- Bulb Type: LED
- Voltage: 120 - 277 V
- CRI: 80
- Colour Temperature: 4000 K
- Operating Temperature: -40°F - 131°F (-40°C - 55°C)
- Ingress Protection Rating: IP65
- Manufacturer's Warranty: 5 Year Limited



Model No.	Mfg. No.	Wattage	Overall Dim. L" x W" x H"	Lumens	Price /Each
XI397	264JLH	92 W	13 x 15 x 7	12000	
XI398	2501PP	136 W	13 x 12 x 5	18000	
XI399	2501PS	181 W	15.75 x 12 x 5.18	24000	