



Open Frame Portable Generator

- Recoil pull start
- Low oil shutdown protects the engine from damage
- Onboard CO-Protect Technology automatically shuts down the generator if CO levels become unsafe or rapidly increase
- Equipped with covered outlets to protect from elements and features never-flat wheels for maximum portability and durability
- Fold-down/locking handle for sturdy portability and compact storage
- Fuel Tank Capacity: 3.4 gal.
- Weight: 119 lbs.
- Overall Dimensions: 23" W x 23-7/8" D x 21-2/5" H
- Surge Power: 5000 W
- Rated Power: 4000 W
- Voltage Output: 120 V
- Engine Type: Dewalt 223cc
- Run Time at 50% Load: 10 Hours
- No. of Outlets: 5
- Outlet Type: 120V 20A, 120V 30A



Model No.	Mfg. No.	Price /Each
XI347	PMC164000	

Commercial Portable Generator

- Features a smart runtime meter and wattage meter that displays fuel level and time remaining at the current power level
- Durable wheels, and a hassle-free electric start-up
- Idle control conserves fuel and reduces noise on the job site
- Low-oil level shutdown automatically safeguards engine from damage
- Fuel Tank Capacity: 7.5 gal.
- Weight: 192.2 lbs.
- Overall Dimensions: 27-2/5" W x 27-1/5" D x 28-1/2" H
- Surge Power: 8750 W
- Rated Power: 7000 W
- Voltage Output: 120 V, 240 V
- Engine Displacement: 420 CC



Model No.	Mfg. No.	Price /Each
XI286	PMC167000.01	

Commercial Generator

- Designed for the professional contractor or rental operator
- Premium alternator provides low harmonic distortion
- Runs up to 13 hours at 50% load
- Features include a hydraulic/magnetic circuit breaker, a digital hour meter for monitoring run time and tracking maintenance, and an idle control to reduce noise and save fuel
- Steel frame is job site tested and includes a lifting hook
- Fuel Tank Capacity: 8 gal.
- Weight: 206 lbs.
- Overall Dimensions: 22-3/10" W x 31-2/5" D x 26-3/10" H
- Surge Power: 7200 W
- Rated Power: 6100 W
- Voltage Output: 120 V, 240 V
- Engine Displacement: 389 CC



Model No.	Mfg. No.	Price /Each
XI284	PD612MHB005.02	

Portable Gasoline Generator

- Powered by a 270cc Honda GX270 manual start OHV engine with auto shut-off for low oil
- Never flat, durable wheels for maximum portability and durability
- Covered outlets for protection from the elements and rugged working conditions
- Electric start (battery included) provides hassle-free start-up
- Fold-down locking handle for sturdy portability and compact storage
- Smart runtime meter shows fuel level and time remaining at current power level
- Wattage meter gives instant feedback on how much power is being used
- Idle control conserves fuel and reduces noise on the job site
- Hour meter tracks maintenance intervals
- Fuel Tank Capacity: 7 gal.
- Weight: 160 lbs.
- Overall Height: 24-1/10"
- Overall Width: 21-3/10"
- Overall Depth: 28-1/5"
- Surge Power: 4500 W
- Rated Power: 4200 W
- Voltage Output: 120 V
- Run Time (50% Load): 15 hours
- Noise Level @7m (22 ft.): 76 dBA



Model No.	Mfg. No.	Price /Each
XH078	PD422MH1005.02	

Generator Adaptors

- Enables user to draw a full 20 A load
- Flame retardant
- Ultra-flexible in extreme temperatures from -58°F up to +221°F (-50°C up to +105°C)
- Used for lighting, small air conditioners, air compressors, water pumps, power tools and equipment with 1 HP rating



Model No. XC999

- 30 A locking plug connects to three 20 A T-slot connectors
- 2' 12/3 STOW wire
- Primelight® power indicator light shows when power is on

Price/Each \$

Model No. XD001

- 20 A T-blade plug to 20 A T-slot connectors
- 25' 12/3 STOW wire
- 20 A / 125 V / 2500 W
- Primelight® power indicator light shows when power is on
- For use with virtually all generators

Price/Each \$

XD001



Model No. XD002

- 20 A T-blade plug to 20 A T-slot triple tap connector
- 2' 12/3 STOW wire
- 20 A / 125 V / 2500 W
- For use with virtually all generators

Price/Each \$

