



MLT4080 Light Towers

- Built and designed for the most extreme environments
- Adjustable and fully-rotational mast
- Robust 14-gauge steel enclosure
- Broad-based design for stable transport in rough terrain
- Withstands winds up to 105 kph
- Equipped with a Kubota® D1105-E3BG 3 cylinder engine
- Automatic low oil/high temperature shutdown system
- CSA approved
- 56.4 gal. fuel capacity
- Power Type: Diesel • Running Watts: 8000 Watts
- Total Lumens: 462,000 • Voltage: 120/240 VAC
- Amperage: 66/33 Amps



GENERAC®

Model No.	Mast Height'	Mast Type	Standby Power Rating	Prime Power Rating	Full Load Fuel Consumption	Lights only Fuel Consumption	Max. Run Time Lights Only (hrs)	Price /Each
XG902	30	Horizontal	15.4 hp @ 1800 rpm	13.5 hp @ 1800 rpm	0.70 gph	0.35 gph	161	P.O.A.
XG903	25	Vertical	15.4 hp @ 1800 rpm	13.5 hp @ 1800 rpm	0.70 gph	0.35 gph	161	P.O.A.

MLT4150 Light Towers

- Built and designed for the most extreme environments
- Adjustable and fully-rotational mast
- Robust 14-gauge steel enclosure
- Withstands winds up to 105 kph
- Equipped with a Mitsubishi® S4L2-W461ML 4 cylinder engine
- Automatic low oil/high temperature shutdown system
- CSA approved
- 56.4 gal. fuel capacity
- Power Type: Diesel • Running Watts: 20000 Watts
- Total Lumens: 462000 • Voltage: 120/240 VAC
- Amperage: 167/83 Amps



GENERAC®

Model No.	Mast Height'	Mast Type	Standby Power Rating	Prime Power Rating	Full Load Fuel Consumption	Lights only Fuel Consumption	Max. Run Time Lights Only (hrs)	Price /Each
XG906	30	Horizontal	40.2 hp @ 1800 rpm	36.2 hp @ 1800 rpm	2.10 gph	1.05 gph	48	P.O.A.
XG907	25	Vertical	40.2 hp @ 1800 rpm	36.2 hp @ 1800 rpm	2.10 gph	1.05 gph	48	P.O.A.

MLT5060 Light Towers

- Built and designed for the most extreme environments
- Adjustable and fully-rotational mast
- Robust 14-gauge steel enclosure
- Withstands winds up to 105 kph
- Automatic low oil/high temperature shutdown system
- CSA approved • 56.4 gal. fuel capacity
- Power Type: Diesel • Running Watts: 8000 Watts
- Total Lumens: 462,000 • Voltage: 120/240 VAC
- Amperage: 50/25 Amps



GENERAC®

Model No.	Mast Height'	Mast Type	Standby Power Rating	Prime Power Rating	Full Load Fuel Consumption	Lights only Fuel Consumption	Max. Run Time Lights Only (hrs)	Equipped With	Price /Each
XG908	30	Horizontal	13.1 hp @ 1800 rpm	11.7 hp @ 1800 rpm	0.50 gph	0.25 gph	225	Kubota® D1005-E3BG1-MGM-1 3 cylinder engine	P.O.A.
XG909	25	Vertical	13.1 hp @ 1800 rpm	11.7 hp @ 1800 rpm	0.50 gph	0.25 gph	225	Kubota® D1005-E3BG1-MGM-1 3 cylinder engine	P.O.A.
XG910	30	Horizontal	12.2 hp @ 1800 rpm	10.5 hp @ 1800 rpm	0.47 gph	0.24 gph	235	Mitsubishi® L3E-W461ML 3 cylinder engine	P.O.A.
XG911	25	Vertical	12.2 hp @ 1800 rpm	10.5 hp @ 1800 rpm	0.47 gph	0.24 gph	235	Mitsubishi® L3E-W461ML 3 cylinder engine	P.O.A.

MLT4150 Light Towers

- Built and designed for the most extreme environments
- Adjustable and fully-rotational mast
- Robust 14-gauge steel enclosure
- Withstands winds up to 105 kph
- Equipped with a Kubota® D1105-E3BG 3 cylinder engine
- Automatic low oil/high temperature shutdown system
- CSA approved • 56.4 gal. fuel capacity
- Power Type: Diesel • Running Watts: 8000 Watts
- Total Lumens: 462,000 • Voltage: 120/240 VAC
- Amperage: 66/33 Amps



GENERAC®

Model No.	Mast Height'	Mast Type	Standby Power Rating	Prime Power Rating	Full Load Fuel Consumption	Lights only Fuel Consumption	Max. Run Time Lights Only (hrs)	Price /Each
XG912	30	Horizontal	15.4 hp @ 1800 rpm	13.5 hp @ 1800 rpm	0.70 gph	0.35 gph	161	P.O.A.
XG913	25	Vertical	15.4 hp @ 1800 rpm	13.5 hp @ 1800 rpm	0.70 gph	0.35 gph	161	P.O.A.