



Double-Sided Polyester Film Tape

- Ideal for general mounting and holding
- Polyester film coated on both sides with a high shear strength adhesive; silicone paper liner
- Ideal for carpet laying, trophies, mouldings and picture frames
- Bonds to paper, foil and plastic film
- 180' (55 m) per roll
- Thickness: 6.5 mils



Priced per Roll

Model No.	Width	Rolls/Case	Price/Each	Qty	Qty Price/Each
PE826	24 mm (1")	48			
PE827	48 mm (2")	24			

Double-Sided Paper Tape

- Made of thin kraft and rope fibre tissue, coated on both sides with an aggressive high shear strength adhesive; silicone paper liner
- Features include thinness and ease of application
- 108' (33 m) per roll
- Thickness: 5 mils



Priced per Roll

Model No.	Width	Rolls/Case	Price/Each	Qty	Qty Price/Each
PA677	12 mm (1/2")	72			
PA678	24 mm (1")	36			
PA679	48 mm (2")	24			

Vinyl Tape 471

- Ideal for many colour coding, abrasion protection, sealing, patching, splicing, wrapping and general purpose applications
- For use around fire extinguishers, electrical equipment
- 33 m (36 yards) per roll




Priced per Roll

Model No.	Width	Colour	Rolls/Case	Price/Each	Qty	Qty Price/Each
PC589	1/2" (12 mm)	Red	72			
PC590	1/2" (12 mm)	Blue	72			
PC591	1/2" (12 mm)	Yellow	72			
PC592	1/2" (12 mm)	White	72			
AMC510	3/4" (18 mm)	Red	48			
AMC461	3/4" (18 mm)	Blue	48			
AMC547	3/4" (18 mm)	Yellow	48			
AMC533	3/4" (18 mm)	White	48			

Double Coated Polyethylene Foam Tape 4466

- 1/16", thick closed cell polyethylene foam carrier
- High tack rubber adhesive
- 3.0-mils, densified kraft liner
- Temperature and environmental resistant
- Colour: White



Priced per Roll

Model No.	Dimensions	Rolls/Case	Price/Each	Qty	Qty Price/Each
PB921	1/2" x 36 yds.	18			

Scotch® ATG Adhesive Applicators

- Pressure sensitive two-way adhesive can be applied exactly where needed
- Ideal for mounting, splicing or bonding
- Can be used in a broad range of industries, including printing, furniture manufacturing, electronics, appliances, signs and displays, automotive and others
- ATC system applies 2-mils reinforced clear acrylic adhesive and simultaneously rewinds the tape liner inside the dispenser



Priced per Roll

Model No. PA974

Mfg. No. ATG-700

Price/Each \$

TAPE

Model No.	Mfg. No.	Description	Rolls/Case	Price/Each	Qty	Qty Price/Each
PA612	924-12	1/2" x 108' Tape	72			
PA613	924-19	3/4" x 108' Tape	48			

Teflon Tape

WATER LINES THREADS

- Provides fast positive seal for water lines, sewage, and sprinkler systems
- Effective on metal or plastic threads
- 3-mils thick, density 1.35-1.50 grams/cubic centimetre
- Complies with MIL-T-27730A
- Colour: Pink



GAS LINES THREADS

- Especially for natural gas, propane, butane, water, oil and chemical lines
- 4-mils thick, density 1.35-1.50 grams/cubic centimetre
- Complies with MIL-T-22230A (ASG), UL 31 RO, AGA 3226 and CAN/ULC-S642
- Colour: Yellow



Priced per Roll

Model No.	Dimensions"	Colour	Rolls/Case	Price/Each	Qty	Qty Price/Each
PD095	1/2 x 260	Pink	50			
AG605	1/2 x 260	Yellow	100			

Teflon Thread Sealant Tape

- For use in sealing threaded pipe joints
- Non-toxic composition suitable for solvents, chemicals, oxygen and on food lines
- Permits easy disassembly even after years of service
- Works under pressures up to 10000 PSI and temperatures from -450°F to 550°F



Priced per Roll



Model No.	Dimensions"	Rolls/Case	Price/Each	Qty	Qty Price/Each
PA684	1/2 x 520	144			
PA685	3/4 x 520	144			

Teflon Sealing Tape

- Commonly used in plumbing for sealing pipe threads
- Ensures a tight seal
- Works for both water and air
- Colour: White
- Tape Material: PTFE
- Thickness: 3 mils (0.0762mm)
- Density: 0.37 grams/cubic centimeter
- Working Temperatures Range: -190°C to 260°C (-310°F to 500°F)



Model No.	Dimensions	Price/Each	Qty	Qty Price/Each
PG148	1/2 x 520			
PG149	3/4 x 520			