



Gorilla Construction Adhesive

- Tough, versatile and all-weather adhesive
- 100% adhesive formula creates heavy-duty bonds
- 100% waterproof
- Holds in 30 seconds
- Low-odor
- Gap filling up to 1"
- Can be painted with latex paint within 2 days of application
- Container Type: Cartridge
- Colour: White
- Application Time: 10 min.
- For use on: Wood, Metal, Stone, Ceramic, Glass, Most Plastics, PVC Sheet, Brick, Paper, Rubber



Model No.	Size	Price /Each	Qty	Qty Price /Each
AF413	9 oz.			

Nuflex® 458 Sub-Floor Construction Adhesive

- Ideal for particleboard, OSB and engineered lumber as well as wet, frozen and treated lumber
- Provides superior adhesive strength and remains permanently flexible
- Fills gaps and irregularities between materials and provides a more solid backup surface
- Reduces the amount of nailing, increases floor rigidity and helps eliminate squeaky floors
- Exceeds AFG-01 specifications
- Freeze-thaw stable
- Superior extreme temperature adhesive; works extremely well in colder temperatures and offers excellent water-resistance



Model No.	Mfg. No.	Size	Price /Each
AE622	45880	828 ml	

Carpenter's® Wood Glue

- Made for furniture repair and general indoor household projects
- Best for soft and hardwoods, particle board and porous materials
- Cleans up with soap and water when wet, and scrape and sand when glue is dry
- Open time: 10-15 minutes before clamping
- Clamp time: 12 hours
- Light colour for natural and light stained woods
- Pourable
- Colour when dry: Yellow



Model No.	Mfg. No.	Size	Price /Each
AE610	60615TR	118 mL	
AE611	60613TR	236 mL	
AE612	60617TR	473 mL	
AE614	6155060619	3.8 L	

Ten Bond Contact Cement

- Brush-able, neutral-colored contact adhesive for bonding many decorative laminates, aluminum, steel, plywood, panels, wood and wood veneer, masonry, rubber, canvas and other porous and non-porous materials
- Air drying adhesive which bonds immediately and permanently upon application of contact pressure
- No clamping or fixturing required



Model No.	Mfg. No.	Size	Price /Each
AMC295	10-1L	1 L	
AMC294	10-1GAL	1 gal.	

Nuflex® 480 Polyurethane Construction Adhesive

- Excellent adhesion strength
- 100% polyurethane based, VOC compliant adhesive
- Can be used for interior or exterior projects and is three times as strong as conventional solvent based construction adhesives
- Ideal for wood, hardwood flooring, concrete, stone, marble, slate, masonry, brick, foam insulation, carpets, metal, lead, cement-based products, ceramics, fiberglass, drywall and mirrors
- Contributes to LEED credit
- Low-odor
- Adheres to dry, wet and frozen lumber
- Waterproof, paintable and cures even in cold temperatures
- AFG-01 approved



Model No.	Mfg. No.	Size	Price /Each
AE623	48000	296 ml	
AE624	48080	828 ml	

Probond® Max Wood Glue

- Made for furniture repair and general indoor and outdoor household projects
- Best on wood
- Contains real wood fibers for superior staining, painting, and sanding
- Open time: 10-15 minutes before clamping
- Clamp time: 12 hours
- Easy to clean-up with water
- Pourable and waterproof
- Colour when dry: Beige



Model No.	Mfg. No.	Size	Price /Each
AE615	69220	118 mL	
AE616	69221	236 mL	
AE617	69222	473 mL	
AE618	69224	3.8 L	

Original Gorilla Glue

- Incredibly strong and versatile glue
- Water-activated
- 100% waterproof
- Expands by about 3-4 times the applied amount
- Unaffected by extreme heat or cold
- For use indoors and outdoors
- Colour: Tan
- Application Time: 10 min.
- Full Cure Time: 24 hrs.
- Open Working Time: 10-15 minutes
- Clamp time: 1-2 hours
- Drying Time: 24 hours
- For use on: Wood, Metal, Stone, Ceramic, Glass, Most Plastics, PVC Sheet, Brick, Paper



Model No.	Format	Container Type	Price /Each	Qty	Qty Price /Each
NKA481	4 x 3 g	Tube			
NKA497	2 oz.	Squeeze Bottle			
NKA480	4 oz.	Squeeze Bottle			
NKA498	8 oz.	Squeeze Bottle			

White Glue

- Washable no-run glue; easy to clean up
- Safe and non-toxic
- Pourable
- Recommended for wood, wood compositions, veneer, paper, cardboard, leather, fabric and cork
- Not recommended for joints that require gap filling, bonding non-porous substrates (i.e. plastic or metal)
- Colour: White



Model No.	Mfg. No.	Size	Price /Each
AE606	60307W8	120 ml	
AE607	60310Q	225 ml	
AE608	6155060331	950 ml	
AE609	6155060341	3.8 L	

PL® Premium

- Bonds well to dry, wet, frozen or treated lumber
- Water resistant, low odour, long open time
- Recommended for wood, hardwood flooring, concrete, stone, marble, slate, masonry, brick, foam insulation, carpets, metal, lead, cement-based products, ceramic, fiberglass, drywall and mirrors
- Not recommended for polystyrene tub surrounds, water submersion applications, polystyrene, polyethylene or polypropylene; certain materials such as rubbers and plastics may have bonding difficulties
- Container Type: Cartridge
- Colour: Bronze



Model No.	Mfg. No.	Size	Price /Each
AD434	1403222	825 ml	