



Rite-On™ Harnesses

Designed with two things in mind: Simplicity and Comfort. It's constructed to shape around the user with ease. The harnesses are engineered with a lumbar support to make the donning of a harness a breeze. The comfort pad also eliminates the tangling of the straps which are common with traditional harnesses. The bayonet style connectors allow users to connect their chest and legs straps in a single action.

RITE-ON™ HARNESSES

- Integrated back and shoulder pad – Conforms to the wearers' shape to provide all-day comfort
- Fast-action bayonet style connectors – Allow quick and easy donning
- Extended D-ring option – Makes lanyard connection easier and safer
- Sweat wicking pad fabric – Keeps wearers comfortable in hot conditions
- Tangle-free pad design – Harness keeps its shape between use, aiding quick and easy donning
- Lightweight polyester webbing – Offers superior UV and chemical resistance
- Universal size with full adjustability – One size fits most
- Weight capacity: 400 lbs. (181.4 kg)
- Certified to CSA standard Z259.10

Honeywell

NORTH

Model No.	Mfg. No.	D-Rings	CSA Class	Price /Each
SAK490	FP81F/1DBA	Back	A	
SAO631	FP81F/1EDBA	Extended-back	A	
SAO632	FP81F/3DDA	Back and Side	A, P	
SAO633	FP81F/3EDDA	Extended-back and Side	A, P	
SAO634	FP81F/4DLA	Back, Side and Front	A, P, L	
SAO635	FP81F/4EDLA	Extended-back, Side and Front	A, P, L	

SAK490



RITE-ON™ II HARNESSES

- Designed for more simplicity and comfort, this series is constructed to shape around the user with ease
- Open cell foam padding wicks sweat away from the body, keeping workers cool and dry throughout the day, and improving productivity
- Integral back and shoulder pad eliminates tangling of the harness's straps
- Lumbar pad decreases back injuries
- Removable 11" comfort leg pad reduces of pinch point and strain while in work position
- Quick-connect buckles allow easy, single action secure connection
- Protective label pouch makes identification and inspection easier
- Fall arrest indicator makes it easier for a worker to identify if a large load has been applied to the harness
- Weight capacity: 400 lbs. (181.4 kg)
- Certified to CSA standard Z259.10

Honeywell

NORTH

Model No.	Mfg. No.	D-Rings	Belted	Size	CSA Class	Price /Each
SEA288	FP81T/1DBA/SM	Back	No	Small/Medium	A	
SEA287	FP81T/1DBAL/XL	Back	No	Large/X-Large	A	
SEA290	FP81T/1EDBA/SM	Extended-back	No	Small/Medium	A	
SEA296	FP81V/6D3A/SM	Back, Front, Side and Shoulder	Yes	Small/Medium	A, P, L, E	
SEA295	FP81V/6D3AL/XL	Back, Front, Side and Shoulder	Yes	Large/X-Large	A, P, L, E	

SEA295



SEA290



Vest-Style Universal Harnesses

- Adjustable shoulder straps and chest strap can be positioned in the optimum location for the user, eliminating the need for stretchable webbing
- Proven polyester webbing provides added UV protection and chemical resistance
- Sub-pelvic strap adds comfort and helps distribute the forces generated in a fall
- Universal fit (X-Large available upon request)
- Weight capacity: 400 lbs. (181.4 kg)
- Certified to CSA standard Z259.10

Honeywell

NORTH

Model No.	Mfg. No.	D-rings	Leg Connections	CSA Class	Special Feature	Price /Each
SN128	FP759/1DP	Back	Quick-Connect	A	-	
SN129	FP759/1DGP	Back	Tongue Buckle	A	-	

SN128

