



Document Storage Boxes

- Weather resistant, no metal parts to corrode - keeps papers clean and dry in dusty, harsh environments
- High density polyethylene is durable, rustproof and easy to clean
- Mounts on cabinets, machinery, equipment or walls for fast, easy access to information at point of use
- Lock holes on medium and large units accept padlock or zip ties
- Four built-in mounting holes on medium and large sized units provide added mounting options
- Designated area to add your own labels or optional label pack available
- Keeps MSDS documents for compliance with OSHA 29 CFR 1910.1200
- Optional label pack includes 4 yellow labels (2 blank, 1 SDS and 1 Instruction Manual), sold separately
- Includes heavy-duty tape for drill-free mounting



Model No.	Mfg. No.	Description	Int. Dim. (approx)					Ext. Dim.					Gasketed Closure	Lock Hole Dia."	Price /Each
			W"	x	D"	x	H"	W"	x	D"	x	H"			
SAN581	23303	Medium Top Opening	8 3/4	x	1 5/8	x	11 1/2	10 1/4	x	2 1/4	x	12 1/2	No	1/4	
SAN582	23304	Medium Front Opening	8 5/8	x	1	x	12 1/4	11	x	2 1/8	x	14 1/2	Yes	3/8	
SAN584	23306	Large Front Opening	10 3/4	x	2 1/4	x	13 1/4	13 1/8	x	3 9/16	x	15 3/4	Yes	3/8	
SAN585	23310	Label Pack - 4 Yellow Labels: 2 Blank, 1 SDS and 1 Instruction Manual													
SAN583	23305	Tube, Twist-On Lid	12"	x	3"	dia.	12 1/2" x 3 3/4" dia.					Yes	-		

PK-Series Storage Lockers

- Constructed with UL approved 2-hour rated firewall design
- Complies with fire rating requirements for storage of flammables within 10 feet of your facility

DRUMS

- Drums can be easily accessed with a fork or optional ramp
- Use multiple lockers to separate incompatible materials
- Certification: FM Approved

IBCS

- Designed for secure, convenient outdoor placement of Totes near your facility
- Sumps are sized to provide compliant spill volumes for 350-gallon totes
- Built to carry higher loads from IBCs
- Sump volumes meet EPA and UFC requirements
- Standard(s) Met: UL



N-Series Storage Lockers

- Durable 11-gauge welded, steel construction
- Lockable, hinged doors with inside release provides added safety
- Galvanized grating above a spill compliant sump
- Passive ventilation
- Exterior grounding lug and anchoring point
- NFPA placard
- Colour: White
- Material: Steel
- Certification: FM Approved

CALL US FOR PRICING TODAY!



DRUMS

Model No.	Mfg. No.	No. of Drums	Exterior Dimensions				Capacity US Gal.	Price /Each	
			W"	x	D"	x			H"
SFW342	P19-1000	2	58	x	88	x	96	65	P.O.A.
SFW344	P19-1050	4	70	x	88	x	96	97	P.O.A.
SFW346	P19-1100	6	70	x	88	x	118	135	P.O.A.
SFW348	P19-1150	8	70	x	88	x	143	178	P.O.A.

IBCS

Model No.	Mfg. No.	No. of IBCs	Exterior Dimensions				Capacity US Gal.	Price /Each	
			W"	x	D"	x			H"
SFW350	P19-1250	1	99	x	74	x	100	438	P.O.A.
SFW352	P19-1300	2	153	x	70	x	88	423	P.O.A.

Model No.	Mfg. No.	No. of Drums	Exterior Dimensions			Capacity US Gal.	Price /Each		
			W"	x	D"			x	H"
NON-COMBUSTIBLE									
SFW327	N05-3004	2	96	x	58	x	98	103	P.O.A.
SFW328	N05-3009	4	96	x	70	x	98	128	P.O.A.
SFW329	N05-3015	6	118	x	70	x	98	170	P.O.A.
SFW330	N05-3020	8	143	x	70	x	98	218	P.O.A.
2-HOUR FIRE RATED									
SFW335	N05-4004	2	96	x	58	x	98	77	P.O.A.
SFW336	N05-4009	4	96	x	70	x	98	99	P.O.A.
SFW337	N05-4015	6	118	x	71	x	98	125	P.O.A.
SFW338	N05-4020	8	143	x	71	x	98	165	P.O.A.
ACCESSORIES									
SFW334	N05-4030	Ramp, Yellow						P.O.A.	