



Drum Closures

STEEL DRUM CLOSURES

- Made from premium deep-drawing quality steel
- Visegrip® plugs have a hexagonal shoulder for easy opening (no tools required)
- Titegrip™ plugs compatible with other opening types also available

STEEL DRUM FUSIBLE CLOSURES

- Used for drums containing combustible materials
- Made of reinforced nylon material
- Centre melts away when exposed to extreme heat allowing venting, thus reducing risk of explosion
- Titegrip™ plugs compatible with other opening types also available

POLY-DRUM CLOSURES

- Poly-Visegrip® closure specially designed for use in lined containers
- Requires no gaskets

STEEL DRUM CLOSURES

Model No.	Size"	Price/Each
DB891	3/4	
DC648	2	

STEEL DRUM FUSIBLE CLOSURES

Model No.	Size"	Torque req. (ft.-lbs.)	Price/Each
DB893	3/4	9	
DB894	2	20	

POLY-DRUM CLOSURES

Model No.	Size"	Threads	Price/Each
DB895	2	NPS	
DB896	2	BSP	



DC648



DB894



DB896

Manual Crimping Tools

- DB903 is used for 2" cap seals
- DB904 is used for 3/4" cap seals

Model No. DB903
Price/Each

Model No. DB904
Price/Each



Tamper-Evident Cap Seals

SAFESEAL® PLASTIC CAP SEALS

- Requires DB903 or DB904 tool to be applied
- Titegrip™ compatible Safeseal® plastic caps also available

ALL PLASTIC CAP SEALS

- Easy-to-use pop-on feature
- Can be applied without tools

Model No.	Size"	Price/Each
DB899	3/4	
DB900	2	

SAFESEAL® PLASTIC CAP SEALS

DB899	3/4	
DB900	2	

ALL PLASTIC CAP SEALS

DB901	3/4	
DB902	2	



Horizontal Drum Gauges

Instant, accurate information on the amount of liquid in a 45-gallon drum. Mounts through 2" bung hole; seals tight, won't leak. Reads in 5-gallon intervals. Wt. 2 lbs.



Model No. DA067
Price/Each \$

Graduated Drum Gauges

Combination gauge and faucet permits uninterrupted draining of drum contents with gauge in place. Mounts through 3/4" bung hole. Constructed of heavy gauge glass in plated steel body with Buna-N seals. Weight: 3 lbs.



Model No.	Description	Price/Each
DA064	Gauge only	
DA065	Gauge with faucet*	

* Zinc Die Cast Faucet FM approved for viscous liquids only; no flame arrestor.

Vertical Drum Gauges

Accurate "At-A-Glance" monitoring. Graduated in gallons, litres, quarters and eighths full. Heavy steel and plastic construction with leak-proof duro nitrile gaskets. Resistant to oil and many chemicals. Weight: 1 lb



Model No.	Size"	Price/Each
DA068	2	
DA069	3/4	

Drum Fill Gauges

Provides a low cost solution to over-filling drums. When the drum is almost full, the indicator "Pops-up" to warn you. Fits in standard 3/4" bung opening. Bright red and yellow molded polyethylene. 5" length. Weight: 0.20 oz.



Model No. DA066
Price/Each \$



Safety Funnels with Fill Vent

9" diameter polyethylene funnel comes with brass safety vent and 6" flame arrestor. Cap comes with safety chain to prevent loss. 2" NPS. FM approved.



Model No.	Wt. lbs.	Price/Each
DA103	2.5	

Safety Drum Funnels

Suitable for handling flammables. Large 10 3/4" mouth provides quick dumping. Steel construction with 6" flame arrestor for the DA102 and 32" flame arrestor for the DA101. Hinged cover with fusible link reduces spread of vapours. 2" NPS/NPT. FM approved.



Model No.	Description	Wt. lbs.	Price/Each
DA102	6" flame arrestor w/funnel	7.5	
DA101	32" flame arrestor w/funnel	12	

Horizontal Brass Vents

- Horizontal vents are for use with drums in the horizontal pouring position
- Automatically relieves pressure at 5 PSI
- Flame arrestor prevents sparks and flame from igniting contents
- Manual vacuum relief by lifting and rotating the valve stem
- Maximum flow of 220 CFM at 20 PSI
- Fits 2" NPS bung in steel or plastic drums



Model No. PE362
Price/Each \$



Vertical Vents

FM approved vents are for use with drums in the upright position. Valve automatically opens to relieve internal pressure at 5 PSI. Automatic vacuum relief permits 4 GPM flow through 3/4" faucet. Fits 2" NPT bung opening.



Model No.	Description	Application	Wt. lbs.	Price/Each
DA607	Brass Vent	Petroleum-Based	0.5	
DA605	Non-metallic Vent,	Petroleum-Based	0.5	
	Cad-plated flame arrestor			
DA606	Non-metallic Vent,	Chlorinated Solvents	1.0	
	Stainless steel flame arrestor			