



Fibreglass Scaffolding

Tested in conformity to CSA standard S269.2 M87

THE TOWER FIBREGLASS SCAFFOLDING

Features:

- Non-conductive
- Light weight
- Corrosion resistant
- Prevents static electricity
- Use every frame as base, building or guard-rail frame
- Quick and easy assembly
- 500-lb. capacity

Ideal for:

- Electricity substation
- Railway stations
- Building sites
- Battery rooms
- Chemical environment
- Computer rooms
- Foundries
- Aircraft maintenance
- Mines



Model No.	Size	Components																Price /Each		
		VC159: 0.7 m x 1 m frame	VC160: 0.7 m x 1.5 m frame	VC162: 1.2 m x 1 m frame	VC162: 1.2 m x 1.5 m frame	VC163: 2.4 m horizontal brace (Yellow)	VC164: 2.4 m diagonal brace (Blue)	VC165: Brace plan for 0.7 m wide frame 2.4 m span (Red)	VC166: Brace plan for 1.2 m wide frame 2.4 m span (Red)	VC167: 2.4 m platform (500-lb. cap)	VC168: 2.4 m platform with trap door (500-lb. cap)	VC169: 0.2 m caster with screw jack 0.34 m	VC170: 2 m outrigger	VC171: 3.05 m outrigger	VC172: 2.4 m - 3.65 m access ladder (330-lb. cap)	VC173: 0.7 m toeboard	VC174: 1.2 m toeboard		VC175: 2.4 m toeboard	VC176: Toeboard bracket
VC177	1.5 m x 0.7 m	2	2	-	-	4	2	1	-	1	-	4	-	-	-	2	-	2	4	
VC178	2 m x 0.7 m	-	4	-	-	6	4	1	-	1	-	4	4	-	-	2	-	2	4	
VC179	2.5 m x 0.7 m	4	2	-	-	6	4	1	-	-	1	4	4	-	1	2	-	2	4	
VC180	3 m x 0.7 m	2	4	-	-	6	6	1	-	-	1	4	4	-	1	2	-	2	4	
VC181	3.5 m x 0.7 m	-	6	-	-	6	6	1	-	-	1	4	-	4	1	2	-	2	4	
VC182	4 m x 0.7 m	4	4	-	-	6	8	1	-	-	1	4	-	4	1	2	-	2	4	
VC183	4.5 m x 0.7 m	2	6	-	-	6	8	1	-	-	1	4	-	4	1	2	-	2	4	
VC184	5 m x 0.7 m	-	8	-	-	8	8	1	-	-	2	4	-	4	2	2	-	2	4	
VC185	1.5 m x 1.2 m	-	-	2	2	4	2	-	1	2	-	4	-	-	-	-	-	-	-	
VC186	2 m x 1.2 m	-	-	-	4	6	4	-	1	2	-	4	-	-	-	-	2	2	4	
VC187	2.5 m x 1.2 m	-	-	4	2	6	4	-	1	1	1	4	-	-	1	-	2	2	4	
VC188	3 m x 1.2 m	-	-	2	4	6	6	-	1	1	1	4	-	4	1	-	2	2	4	
VC189	3.5 m x 1.2 m	-	-	-	6	6	6	-	1	1	1	4	-	4	1	-	2	2	4	
VC190	4 m x 1.2 m	-	-	4	4	6	6	-	1	1	1	4	-	4	1	-	2	2	4	
VC191	4.5 m x 1.2 m	-	-	2	6	6	8	-	1	1	1	4	-	4	1	-	2	2	4	
VC192	5 m x 1.2 m	-	-	-	8	8	10	-	1	1	2	4	-	4	2	-	2	2	4	
VC193	5.5 m x 1.2 m	-	-	4	6	8	10	-	1	1	2	4	-	4	2	-	2	2	4	
VC194	6 m x 1.2 m	-	-	2	8	8	12	-	1	1	2	4	-	4	2	-	2	2	4	
VC195	6.5 m x 1.2 m	-	-	6	6	8	12	-	1	1	2	4	-	4	2	-	2	2	4	
VC196	7 m x 1.2 m	-	-	4	8	8	14	-	1	1	2	4	-	4	2	-	2	2	4	

COMPONENTS FOR THE TOWER FIBREGLASS SCAFFOLDING:

Model No.	Description	Weight/ lbs.	Price/Each
VC159	Frame 0.7 m x 1 m	8.8	
VC160	Frame 0.7 m x 1.5 m	11.9	
VC162	Frame 1.2 m x 1.5 m	15	
VC163	Horizontal brace 2.4 m - Colour ID: Yellow	5.3	
VC164	Diagonal brace 2.4 m - Colour ID: Blue	6.2	
VC165	Brace plan for 0.7 m wide frame, 2.4 m span - Colour ID: Red	6.2	
VC166	Brace plan for 1.2 m wide frame, 2.4 m span - Colour ID: Red	6.4	
VC167	Platform 2.4 m - 500-lb. capacity	49.1	
VC168	Platform with trap door 2.4 m - 500-lb. capacity	44.7	
VC169	Caster 0.2 m with screw jack 0.34 m	13.5	
VC170	Outrigger 2 m	6.6	
VC171	Outrigger 3.05 m	8.8	
VC172	Access ladder 2.4 m - 3.65 m - 330-lb. capacity	34.1	
VC173	Toeboard 0.7 m	2.4	
VC174	Toeboard 1.2 m	4.8	
VC175	Toeboard 2.4 m	9.2	
VC176	Toeboard bracket	0.8	

