



Model		Dimensions	Door				Wt.	Price
No.	Description	W" x D"	Colour	Hook	Shelf	Тор	lbs.	/Each
FH725	12" H locker (usually stacked 6 units high)	12 x 15	Grey	No	No	Flat	6	
FH726	12" H locker (usually stacked 6 units high)	12 x 15	Clear	No	No	Flat	6	
FH727	12" H locker (Sloped top)	12 x 15	Grey	No	No	Slope	8	
FH728	12" H locker (Sloped top)	12 x 15	Clear	No	No	Slope	8	
FC689	18" H locker (usually stacked 4 units high)	15 x 15	Grey	No	No	Flat	10	
FC691	18" H locker (Sloped top)	15 x 15	Grey	No	No	Slope	12	
FC693	36" H locker (usually stacked 2 units high)	12 x 15	Grey	Yes	No	Flat	16	
FH729	36" H locker (Sloped top)	12 x 15	Grey	Yes	No	Slope	21	
FC695	Full size 60" H locker	15 x 18	Grey	Yes	Yes	Slope	42	

Note: All dimensions and weight are nominal and may vary due to molding tolerances. Mounting hardware not included. Lockers are individually sold per opening.

## **General Security Combination Padlocks**

- Features Blockguard<sup>™</sup> anti-shim technology
- Double-reinforced stainless steel case with cold-rolled steel construction
- shields locking mechanism from physical attack
- Easy 3-number dialing with automatic scrambling feature to prevent reopening of lock
- School standard's in combination padlock
  Hardened steel shackles resists cutting and r
- Hardened steel shackles resists cutting and prying
  Dial automatically is also used as the state of t
- Dial automatically locks under shackle tension to prevent "feeling out" the combination and automatically scrambles when closed to prevent accidental opening The leaves the second secon
- Fits lockers with a padlock eye of at least 5/16" (8 mm) in diameter

	and the second	Master Lock					
12 5 49 OF 42-13	SR914	BLOCK CUARD Anti-Shim Technology					
e Clearance	Shipping	Price					

Model	Mfg.	Body Size		Body	Shackle Clearance			Shipping	Price
No.	No.	Width"	Thickness"	Material	Α"	В"	<b>C</b> "	Weight (lbs.)	/Each
SR914	1500	1 7/8 Dia.	3/4	Stainless Steel	9/32	3/4	13/16	0.50	
SAL506	1500LH	1 7/8 Dia.	3/4	Stainless Steel	9/32	2	13/16	0.50	

1804

## 1-800-661-2400

www.tenaquip.com