



## Ventis® MX4 Confined Space Kit with Integral Pump

- Includes: Ventis® MX4 with pump monitor, Desktop charger, Carrying case, Calibration tubing, Dust filter/water stop, Calibration fitting, Sample tubing, Calibration gas (appropriate mix) with regulator, Rugged carrying case
- No. of Detectable Gases: 4
- Hazard: LEL - O<sub>2</sub> - CO - H<sub>2</sub>S



**INDUSTRIAL SCIENTIFIC**

Model No.	Mfg. No.	Colour	Price /Each
HZ787	VK-K123211111	Orange	
HZ788	VK-K1232110111	Black	

## MX6 iBrid® Multi-Gas Detector

- Monitor up to six gases
- Tailor for your unique application with 24 sensor options including PID and IR
- Pre-screen entries for benzene with an optional convertible kit (not included)
- Simplify maintenance and reporting with the DSXi™ Docking Station (not included)
- Includes: Rechargeable extended runtime lithium-ion battery, Pump, Universal charger, Nylon carrying case, Belt clip, Calibration cup (diffusion), Wrist strap, Manual, Quick start guide, Calibration tubing, Dust filter/water stop (aspirated), Sample tubing (aspirated)
- No. of Detectable Gases: 5
- Hazard: LEL - O<sub>2</sub> - H<sub>2</sub>S - CO - VOCs



**INDUSTRIAL SCIENTIFIC**

Model No. HZ505  
Mfg. No. MX6-K123R211  
Price/Each \$

## Tango® TX2 Gas Detector

- Reduce unexpected project shutdowns from false alarms by increasing alarm accuracy with two individual sensors
- Eliminate the hassle of charging with a single, replaceable battery that offers a two-year lifespan
- Increase worker's sense of ownership and save time managing your gas detector fleet by assigning each worker one monitor
- Increase compliance and willingness to use the lightweight and hassle-free design
- Three strobe-emitting visual alarm LEDs (two red and one blue), 100 decibel audible alarm at a distance of 10 cm, and vibration alarm
- No. of Detectable Gases: 2
- Manufacturer's Warranty: Guaranteed for Life™ (Detector Only)
- Display Type: LCD
- Dimensions: 99 mm x 51 mm x 35 mm (3.9" x 2" x 1.4")
- Weight: 126 g (4.4 oz.)
- Temperature Range: -40 °C - 50 °C (-40 °F - 122 °F)
- Humidity Range: 15% to 95% Non-Condensing (Continuous)
- CSA Certification: C22.2 No. 157



HZ608

**INDUSTRIAL SCIENTIFIC**

Model No.	Mfg. No.	Hazard	Price /Each
HZ608	TX2-12011	H <sub>2</sub> S - CO	
HZ609	TX2-14011	CO - NO <sub>2</sub>	
HZ610	TX2-15011	CO - SO <sub>2</sub>	
HZ611	TX2-16011	CO - CO Low	
HZ612	TX2-24011	NO <sub>2</sub> - H <sub>2</sub> S	
HZ613	TX2-25011	SO <sub>2</sub> - H <sub>2</sub> S	
HZ614	TX2-26011	H <sub>2</sub> S - CO Low	
HZ615	TX2-45011	NO <sub>2</sub> - SO <sub>2</sub>	
HZ616	TX2-46011	NO <sub>2</sub> - CO Low	
HZ617	TX2-56011	SO <sub>2</sub> - CO Low	

## Ventis® MX4 Confined Space Kit with Slide-On Pump

- Includes: Ventis® MX4, Ventis® Slide-On Pump, 110 VAC desktop charger, Calibration cup and tubing with T-fitting, Dust filter/water stop, 10 feet of sample tubing, 34-litre cylinder of calibration gas, Manual regulator, Rugged hard plastic carrying case
- No. of Detectable Gases: 4
- Hazard: LEL - O<sub>2</sub> - CO - H<sub>2</sub>S
- Colour: Black

**INDUSTRIAL SCIENTIFIC**



Model No. HZ490  
Mfg. No. VKVSP4-K01111  
Price/Each

## Tango® TX1 Gas Detector

- Experience maintenance-free gas detection and improved worker safety with the Tango® TX1 single gas monitor
- Lightweight and wearable personal gas monitor
- DualSense® Technology increases worker safety by using two sensors to detect the same gas
- Spend less time replacing equipment thanks to the industry's only Guaranteed for Life™ single-gas monitor
- Optional AlarmAmp™ increases audible alarms to 110dB
- No. of Detectable Gases: Single



HZ508

Model No.	Mfg. No.	Hazard	Price /Each
HZ508	TX1-1	CO	
HZ509	TX1-2	H <sub>2</sub> S	
HZ510	TX1-4	NO <sub>2</sub>	
HZ511	TX1-5	SO <sub>2</sub>	

**INDUSTRIAL SCIENTIFIC**

## Radius® BZ1 Area Monitors

- The Radius® BZ1 Area Monitor is a rugged gas detector that connects your entire worksite
- Designed to go where the work is, Radius® can be deployed in seconds for emergency response scenarios or left in the field for up to 7 days on a single charge or for an unlimited period with the Solar Power Supply
- Radius® shares readings and alarms with other units and personal gas monitors through LENS® Wireless allowing you to create a dynamic safety network that changes with the needs of your operations
- Detect up to seven gases simultaneously using 18 sensor options including PID
- Reduce battery swapping with a typical run time of 7 days (168 hours)
- Cut through high-noise environments with alarms that sound at 108 dB
- Know what's happening at a distance thanks to the largest display of any area monitor and customizable alarm action messages such as "EVACUATE" or "VENTILATE"
- Increase worker safety with DualSense® Technology, which provides redundant protection by using two sensors to detect the same gas
- Gain real-time visibility and respond faster in an emergency by pairing with the RGX® Gateway for live monitoring
- Simplify maintenance and reporting with the DSXi™ Docking Station (not included)
- No. of Detectable Gases: 4



HZ506

**INDUSTRIAL SCIENTIFIC**

Model No.	Mfg. No.	Hazard	Pump	Price /Each
HZ601	BZ1-K123400111	O <sub>2</sub> , H <sub>2</sub> S, CO, NO <sub>2</sub>	Without Pump	
HZ506	BZ1-K123000111	LEL - O <sub>2</sub> - CO - H <sub>2</sub> S	Without Pump	
HZ507	BZ1-K123001111	LEL - O <sub>2</sub> - CO - H <sub>2</sub> S	With Pump	

## Gas Detector Single Unit Charger

- Single unit charger for the Ventis® MX4 and Ventis® Pro Gas Detectors
- This charger comes with a removable back to support all battery styles (standard, slim-extended, extended run time)
- Gas Detector Series: Ventis® Pro, Ventis® MX4
- Parts: Charger

Model No. HZ698  
Mfg. No. 18108191  
Price/Each \$



**INDUSTRIAL SCIENTIFIC**