



BW™ Max XT II Multi-Gas Detectors

- Reliably monitors up to four hazards, including H₂S, CO, O₂, and combustibles
- Straightforward one-button operation
- Robust motorized SmartSample pump for intelligent remote sampling, ideal for confined spaces
- Reliable pump block detection; water and other liquids are prevented from being drawn into the pump
- Calibration is required only two times per year with a simple one-button automatic procedure
- Tamper-proof adjustable options can be customized to suit any application
- Built-in rechargeable lithium battery
- Rugged and durable water resistant design with built-in concussion-proof boot
- Standard data logging and event logging
- Fully compatible with the MicroDock II automatic test and calibration system

HX922



Honeywell

Model No.	Mfg. No.	Description	Price/Each
HX922	XT-XWHM-Y-NA	Gas Detector	
HX923	XT-CK-CC	Carrying Case with Foam Insert	

CONFINED SPACE KITS

HX924	XT-XWHM-Y-NA-CS	Standard Kit Includes: HX922 , IR Connectivity Kit, Regulator, Sampling Probe and Calibration Gas	
HX925	XT-CK-DL	Deluxe Kit Includes: IR Connectivity Kit, Regulator, 10/ 3 m Hose, Sampling Probe and Auxiliary Filter (Detector and Calibration Gas Sold Separately)	

POWER OPTIONS & SPARES

HX926	XT-C01-MC5	Five Unit Cradle Charger	
HX905	GA-PA-1-MC5	Five Unit Power Adaptor	
HX906	GA-VPA-1	12-24 VDC Vehicle Power Adaptor	
HX907	GA-PA-3	12-24 VDC Direct-Wire Power Adaptor	

BW Clip Real Time Single-Gas Detectors

- Real-time gas level display with the ability to calibrate the device
- Maintenance-free: no sensor or battery changes necessary
- Offers extended longevity with a field-replaceable battery and sensor
- Compact, lightweight design with one-button operation
- Designed for a range of harsh environments and extreme temperatures
- Hibernation mode with case accessory or IntelliDoX
- Automated self-test of battery, sensor and electronics
- Wide-angle flash, which alerts simultaneously with audible and vibrating alarm
- Automatic logging of the 35 most recent gas events and bump test results
- Compatible with MicroDock II and Fleet Manager II software
- Affordable, with low cost of ownership
- BW recommends performing a bump test prior to each day's use to confirm sensor response and alarm



Honeywell

Model No.	Mfg. No.	Hazard	Measuring Range	Default Alarm Setpoints Low	High	Price /Each
-----------	----------	--------	-----------------	-----------------------------	------	-------------

BW CLIP REAL TIME 2-YEAR DETECTORS

HZ270	BWC2R-H	Hydrogen sulfide (H ₂ S)	0-100 ppm	10 ppm	20 ppm	
HZ271	BWC2R-H510	Hydrogen sulfide (H ₂ S)	0-100 ppm	5 ppm	20 ppm	
HZ273	BWC2R-M	Carbon monoxide (CO)	0-300 ppm	35 ppm	200 ppm	
HZ274	BWC2R-M50200	Carbon monoxide (CO)	0-300 ppm	50 ppm	200 ppm	
HZ275	BWC2R-X	Oxygen (O ₂)	0-25%	19.5% vol.	23.5% vol.	
HZ276	BWC2R-S	Sulfur Dioxide (SO ₂)	0-100 ppm	5 ppm	20 ppm	
HZ277	BWC2R-S24	Sulfur Dioxide (SO ₂)	0-100 ppm	2 ppm	20 ppm	

BW CLIP REAL TIME 3-YEAR DETECTORS

HZ278	BWC3R-H	Hydrogen sulfide (H ₂ S)	0-100 ppm	10 ppm	20 ppm	
HZ279	BWC3R-M	Carbon monoxide (CO)	0-300 ppm	35 ppm	200 ppm	

BW Clip 4 Multi-Gas Detectors

- Alarm Setpoints: 5-10 ppm
- Maintenance-free: no sensor or battery changes necessary
- Compact, lightweight design with one-button operation
- Designed for a range of harsh environments and extreme temperatures
- Automated self-test of battery, sensor and electronics
- Wide-angle flash, which alerts simultaneously with audible and vibrating alarm
- Automatic logging of the 70 most recent gas events and bump test results
- IntelliDoX compatible
- Affordable, with low cost of ownership



HZ284

Honeywell



HZ285

Model No.	Mfg. No.	Hazard	Colour	Price /Each
HZ284	BWC4-B-N	O ₂ , H ₂ S, CO/LEL	Black	
HZ285	BWC4-Y-N	O ₂ , H ₂ S, CO/LEL	Yellow	

BW Clip Single-Gas Detectors

- Maintenance-free: no sensor or battery changes necessary
- Offers extended longevity with a field-replaceable battery and sensor
- Compact, lightweight design with one-button operation
- Designed for a range of harsh environments and extreme temperatures
- Hibernation mode with case accessory or IntelliDoX
- Automated self-test of battery, sensor and electronics
- Wide-angle flash, which alerts simultaneously with audible and vibrating alarm
- Automatic logging of the 35 most recent gas events and bump test results
- Compatible with MicroDock II and Fleet Manager II software
- Affordable, with low cost of ownership
- BW recommends performing a bump test prior to each day's use to confirm sensor response and alarm
- Note: Monitors do not have a continuous display of the gas concentration, the concentration of the gas will only be displayed when an alarm point is reached



Honeywell

Model No.	Mfg. No.	Hazard	Measuring Range	Default Alarm Setpoints Low	High	Price /Each
-----------	----------	--------	-----------------	-----------------------------	------	-------------

BW CLIP 2-YEAR DETECTORS

HZ174	BWC2-H	Hydrogen sulfide (H ₂ S)	1-100 ppm	10 ppm	15 ppm	
HZ175	BWC2-H510	Hydrogen sulfide (H ₂ S)	1-100 ppm	5 ppm	10 ppm	
HZ176	BWC2-H515	Hydrogen sulfide (H ₂ S)	1-100 ppm	5 ppm	15 ppm	
HZ177	BWC2-M	Carbon monoxide (CO)	0-300 ppm	35 ppm	200 ppm	
HZ178	BWC2-M50200	Carbon monoxide (CO)	0-300 ppm	50 ppm	200 ppm	
HZ181	BWC2-X	Oxygen (O ₂)	0-25%	19.5% vol.	23.5% vol.	
HZ179	BWC2-S	Sulfur Dioxide (SO ₂)	0-100 ppm	5 ppm	10 ppm	
HZ180	BWC2-S24	Sulfur Dioxide (SO ₂)	0-100 ppm	2 ppm	4 ppm	

BW CLIP 3-YEAR DETECTORS

HZ183	BWC3-H	Hydrogen sulfide (H ₂ S)	0-100 ppm	10 ppm	15 ppm	
HZ184	BWC3-M	Carbon monoxide (CO)	0-300 ppm	35 ppm	200 ppm	

ACCESSORIES

Model No.	Mfg. No.	Description	Qty /Pkg	Price /Each
HZ185	CLIPHB-CASE	Hibernation Case for BW Clip	1	
HZ186	CLIPHB-CASE-B50	Hibernation Case for BW Clip	50	