



Shockwave™ 2 Shock Absorbing Lanyards

- Tubular core style lanyards uniquely designed to expand and contract in reaction to a workers movements
- Stays out of your way when not in use, avoiding trips and snags
- Built in impact indicator provides visual evidence if the lanyard has been involved in a fall
- Length: 6'
- Certification(s): CSA Standard Z259.11



SEB868



Fall Protection

Model No.	Mfg. No.	No. of Legs	Harness Connection	Anchorage Connections	CSA Mass lbs. min.	max.	Price /Each
SEB868	1244306C	One	Snap Hook	Snap Hook	133	253	

EZ-Stop™ Shock Absorbing Lanyards

- Features the lightest, smallest, and strongest shock absorber in the world; 66% smaller and 40% lighter than previous EZ-Stop™ models
- Lightest and strongest rebar hooks on the market
- Thinnest-ever webbing using HI-10™ Vectran® energy management material for reduced weight and bulk
- Vectran® is a multifilament high tenacity performance fibre spun from liquid crystal polymer that is five times stronger than steel
- Repel™ webbing repels water to reduce the attraction of mold and dirt
- High abrasion resistance
- Excellent chemical and cut resistance
- High impact resistance
- High visibility accents keep you safe in low-light conditions
- Protected labels for durability and longevity
- Rugged and durable soft shock absorber cover is designed to last
- Certification(s): CSA Standard Z259.11



SEJ419

SEJ423



Fall Protection

Model No.	Mfg. No.	Length'	No. of Legs	Harness Connection	Anchorage Connections	CSA Mass lbs. min.	max.	Price /Each
SEJ418	1246012C	3	One	Snap Hook	Snap Hook	122	308	
SEJ419	1246017C	4	One	Snap Hook	Snap Hook	122	308	
SEJ421	1246102C	6	One	Snap Hook	Rebar Hook	122	308	
SEJ422	1246022C	6	Two	Snap Hook	Snap Hooks	122	308	
SEJ423	1246024C	6	Two	Snap Hook	Rebar Hooks	122	308	

Pro™ Pack Shock Absorbing Lanyards

- Pack-type shock absorber limits fall arrest forces to 900 lbs. for added safety
- Durable 1" polyester web construction
- Durable alloy steel, zinc-plated hardware
- Harness Connection: Snap Hook
- Certification(s): CSA Standard Z259.11



SEB872

SEB384



Fall Protection

Model No.	Mfg. No.	Length'	No. of Legs	Anchorage Connections	CSA Mass lbs. min.	max.	Price /Each
SEB871	1341004C	4	One	Snap Hook	122	308	
SEB872	1341001C	6	One	Snap Hook	122	308	
SEB384	1340125C	6	One	Gate Hook	122	308	

PRO™ Pack Hot Work Shock Absorbing Lanyard

- Lightweight user friendly design
- Fire resistant Kevlar® fiber webbing
- PVC shock pack with Kevlar® cover
- Energy absorbing design limits fall arrest forces
- User friendly self locking snap hooks at each end
- Impact indicator
- Harness Connection: Snap Hook
- Certification(s): CSA Standard Z259.11



SDP386



Fall Protection

Model No.	Mfg. No.	Length'	No. of Legs	Anchorage Connections	CSA Mass lbs. min.	max.	Price /Each
SDP386	1340129C	6	One	Rebar Hook	122	308	
SDP388	1340186C	4	Two	Rebar Hooks	122	308	

Web Adjustable Positioning Lanyard

- 6 ft. (1.8m) adjustable single-leg lanyard
- Ideal for work positioning or restraint
- Abrasion resistant polyester webbing
- Built-in wear indicator
- User friendly self locking snap hooks at each end
- Equipped with i-Safe™
- CSA standard Z259.11, Class B



Fall Protection

Model No.	Mfg. No.	No. of Legs	Harness Connection	Anchorage Connection	Price /Each
SEPB22	1231016C	One	Snap Hook	Snap Hook	

Suspension Trauma Safety Straps

- They are deployed when needed, hook together in seconds, and let a suspended worker stand up in harness, relieving downward pressure
- You can quickly attach them to most harness brands right in the field
- Compact, lightweight design stays out of your way
- Weight capacity: 310 lbs. (141 kg)
- Sold per pair



Fall Protection

Model No.	Mfg. No.	Price /Each
SEB436	9501403C	