


The Safety Company

Arc-Rated Shock-Absorbing Lanyards

- Designed to protect workers from electric arc-flash and arc-blast exposure
- Arc-rated Kevlar® webbing
- Available with Kevlar® choke-off loop for a "metal-less" connection
- Arc-Flash Standards: ASTM F887-05
- Connectors' Gate Load Capacity: 3600 lbs.
- Shock Absorber Type: Pack
- CSA Minimum Mass: 120 lbs.
- CSA Maximum Mass: 335 lbs.
- Certification(s): CSA Standard Z259.11

Honeywell



SGT531

V-Series Standard Lanyards

- The New V-Series shock absorbing lanyard line simplifies product selection by offering a concise line of standard lanyards that meet a wide range of customer needs
- Includes a clear, durable protective cover on the labels to increase service life, and allow for easy inspection
- Meets the new CSA Z259.11-17 standard for shock absorbing safety lanyards, with a current selection of standard (150-310 lbs.) and lightweight (100-230 lbs.) worker options



Model No.	Mfg. No.	Number of Legs	Anchorage Connections	Length'	Price /Each
CSA (150-310 LBS.)					
SGK246	10188100	One	36C Small Snap Hook	6	
SGK956	10188102	Two	36C Small Snap Hook	6	
SGK957	10188103	0ne	36L Large Snap Hook	6	
SGK958	10188101	Two	36L Large Snap Hook	6	
LIGHTWE	IGHT CSA (100	-230 LBS.)			
SGK959	10190397	One	36C Small Snap Hook	6	
SGK960	10190399	Two	36C Small Snap Hook	6	
SGK961	10190398	One	36L Large Snap Hook	6	
SGK962	10190400	Two	36L Large Snap Hook	6	

V-Series Tie-Back Lanyards

- A new easy identifiable symbol system to indicate the type of lanyard
- 5000 pound gate strength in any direction allows the FP5K carabiner to be tied directly to the lanyard
- Unique carabiner body shape that helps avoid confusion with standard connectors not designed for tie-back applications
- Meets the new CSA Z259.11-17 standard for shock absorbing safety lanyards, with a current selection of standard (150-310 lbs.)

Model No.	Mfg. No.	Number of Legs	Anchorage Connection	Length'	Price /Each
SGK963	10193943	0ne	36C Small Snap Hook	6	
SGK964	10193944	Two	36C Small Snap Hook	6	



Rebel[™] Self Retracting Lifelines

- Lifeline Material: Galvanized Cable
- Harness Connection: Snap Hook
- Anchorage Connection: Carabiner Certification(s): CSA Standard Z259.2.2
- Rugged and extremely lightweight thermoplastic housing
- Stackable housing design
- Built-in carrying handle
- Galvanized steel cable lifeline is abrasion resistant and extremely durable

- system that helps maintain lifeline integrity over abrasive edges









Model No.	Mfg. No.	Length'	Thickness"	Price /Each
SES695	3590541	20	7/32	
SEE717	3590502	33	3/16	
SEE718	3590552	50	3/16	

Nano-Lok™ Self-Retracting Lifelines

- Extremely compact, lightweight design
- Tough and impact-resistant thermoplastic housing Swiveling anchorage loops
- Quick-activating speed-sensing brake systems
- Protected labels, equipped with i-Safe™
- Lifeline Length: 6'
- Certified to CSA standard Z259.2.2







SEE928



	Fall P	rotection			C.
Model No.	Mfg. No.	No. of SRLs	Harness Connection	Anchorage Connection	Price /Each
SEE929	3101230	1	Direct	Aluminum Carabiner	
SEP794	3101232	1	Direct	Aluminum Rebar Hook	
SEP904	3101245	1	Direct	Steel Snap Hook	
SEE928	3101258	1	Direct	Steel Swivel Hook	
SES651	3101222	1	Direct	Steel Rebar Hook	
SES652	3101223	1	Direct	Steel Snap Hook	
SGD985	3101676	1	Direct	Aluminum Rebar Hook	
SEE930	3101286	2	Direct	Steel Rebar Hooks	
SEE931	3101283	2	Direct	Aluminum Rebar Hooks	
NJS982	3101311	2	Direct	Aluminum Snap Hooks	