



Lad-Saf™ Cable Vertical Safety System

- Designed to meet the requirements of the new ANSI Z359.16 standard, along with OSHA 1910.140 and 1926.502, when used with our Lad-Saf X3 Detachable Cable Sleeve (6160054) and Lad-Saf X2 Detachable Cable Sleeve (6160030)
- Reengineered to simplify and speed up the installation process
- Integrated fall arrest-rated anchor point on top bracket rated to 3,600 lbs provides 100% tie-off capability
- Galvanized steel bracket fits up to 1-1/8" (2.85 cm) rung diameter and attaches to two rungs
- Integrated tension-indicating bottom bracket takes the guesswork out of installation
- Compatible with Lad-Saf™ X3 Detachable Cable Sleeve for better climbing performance and fall protection (sold separately)
- Non-metallic Cable Guide hardware for easy-to-use hand operation, with mounting hardware for systems up to 199' (60.6 m), fits up to 1-1/8" (2.85 cm) rung diameter (recommended one every 25' / 7.6 m)
- Material: Galvanized Steel
- Installation Type: Permanent
- Maximum No. of Users: 2
- Single Point Anchor Rating: 3600 lbs.
- Weight Capacity (2 Users): 620 lbs. (281 kg)
- Weight Capacity (1 User): 310 lbs. (140 kg)
- Specification(s) Met: ANSI Z359.16, OSHA 1910.29, OSHA 1926.1053, RR-W-410
- Diameter: 3/8"



SGY439



Fall Protection

| Model No. | Mfg. No. | Length' | Price /Each |
|-----------|----------|---------|-------------|
| SGY439 | 6118020 | 20 | |
| SGY440 | 6118030 | 30 | |

Rollgliss™ R550 Rescue & Descent Device

- Emergency rescue and evacuation from a wide variety of elevated work areas
- Fully automatic controlled descent
- Bidirectional design enables multiple rescues
- Built-in rescue lifting wheel
- 100 ft. (30.5 m) 3/8" (9.5 mm) kernmantle rope lifeline
- Rated for up to 1 640 ft. (500 m) height for one user, 575 ft. (175 m) for two users
- Compact and lightweight design
- High strength corrosion resistant construction
- Integrated rope ears
- Dual brake design
- Equipped with i-Safe™
- Kit also contains 4 ft. (1.2 m) anchor sling, two carabiners and carrying bag
- No. of users: 2
- Lifeline material: Kernmantle
- Harness connection: Carabiner
- Anchorage connection type: Snap hook
- CSA Standard Z259.2.2



Model No. **SDL610**
Mfg. No. 3327100
Price/Each \$

PULLEY - ROLLGLISS™ R550

- Single
- 9-16 mm

Model No. **SDL611**
Mfg. No. 9504733
Price/Each \$



Fall Protection

Lad-Saf™ X3 Detachable Cable Sleeve

- Sleeve for Lad-Saf™ fixed ladder safety system
- For use on 3/8" (9.5 mm) 1x7 or 7x19 solid core cable
- Mobile design follows user for convenient climbing protection
- Easy to install and detach anywhere along lifeline
- Dual independent locking system
- Built-in energy absorber and fall indicator with swivel
- Saflok™ steel carabiner for secure connection to harness
- Extremely rugged and corrosion resistant construction
- Extremely compact, lightweight design
- Integrated RFID tag, equipped with i-Safe™



Fall Protection

| Model No. | Mfg. No. | Price /Each |
|-----------|----------|-------------|
| SGP408 | 6160054 | |

Roof Anchors

- Fast and easy installation
- Installs to sloped or flat wood and metal decking roofs
- Non-penetrating design
- Swiveling self-retracting lifeline bracket
- Compact and lightweight design
- Secondary D-ring anchor point
- Adjustable legs, 360-degree swiveling
- Pair the DBI-SALA® roof anchors with the 3M™ DBI-SALA® Smart Lock SRLs



SGJ694



Fall Protection

| Model No. | Mfg. No. | Description | Price /Each |
|-----------|----------|-----------------------------------------|-------------|
| SGJ694 | 2190073 | 3M™ DBI-SALA® Standing Seam Roof Anchor | |
| SGJ695 | 2190071 | 3M™ DBI-SALA® Swiveling Roof Anchor | |
| SGJ696 | 2190074 | 3M™ DBI-SALA® Construction Roof Anchor | |
| SGJ697 | 2190072 | 3M™ Protecta® Standing Seam Roof Anchor | |
| SGJ698 | 2190070 | 3M™ Protecta® Swiveling Roof Anchor | |