

Carabiners

- · Twist-lock gates
- 400-lb. (181.4 kg) maximum capacity.



Honeywell MILLER

Model No.	Mfg. No.	Material	Gate Opening "	Price/Each
SAK327	17D-1	Steel	1	
SAK328	17D-2-Z7/	Aluminum	1	
SAK330	18D-1	Steel	2	
SAK331	18D-2-Z7/	Aluminum	2 1/4	

PointGuard™ Anchorage Straps

• Durable polyester webbing is economical, quick and easy to install

 When anchorage connector is no longer needed, simply cut strap and throw away

- · Available in two models:
- Residential construction (3' length)
- Concrete construction (4' length,
- includes protective sheath) 400-lb. (182 kg) capacity





SGC228

Model No.	Mfg. No.	Туре	Anchorage Connector	Length'	Price /Each
SAM476 SAM477	10042792 10042793	Residential Residential	D-Ring Web Loop	3	
SAM478 SAM479	10042794 10042795	Concrete Concrete	D-Ring Web Loop	4 4	

FP Stryder Beam Anchors

- Easy, single hand installation
- · Lightweight 4.5 lbs. unit
- Low friction wear pads with Teflon* allows the anchor to glide effortlessly along the beam flange
- Integral load indicator alerts the user if the unit has been exposed to a fall
- Versatile design allows for mounting overhead or at worker's feet
- Easy to use, push-button adjustment with 1/4" adjustment intervals
- 400 lbs. work capacity



Model No.	Mfg. No.	Fits Beams"	Price /Each
SGC228	10144431	4 to 13.5	
SA0684	10144432	14 to 23.5	

Permanent Roof Anchor

- · All steel construction
- Fits all pitches of roof trusses or rafters
- · Easy to install without special tools
- Type: Permanent
- Style: Roof

MSA



Model No.	Mfg. No.	Size"	Price /Each
SAM494	10016468	2 x 4	
SAM495	10017593	2 x 6	

Anchorage Straps

D-ring on one end and a sewn loop on the other end
 Length: 5'



Model No.	Mfg. No.	Material	Price/Each
SAM474	505282	Nylon	
SAM475	505298	Polyester	

SAM474

D-Plate Anchorage Connectors

- Provides permanent anchorage point
- Bolts to beams or columns



AVA	
A'A	-/=1

Model	Mfg.	Material	Price
No.	No.		/Each
SAM483	506632	Zinc-Plated Steel	

Rope Grab Fall Arrester

- Hands-free operation while ascending or descending
- · Ultra-smooth travel action
- Cam and hinge design allows for a quick,
 any installation on the rope
- easy installation on the rope
- Rope Diameter: 5/8"





Model No. SGC222 Mfg. No. 10077718 Price/Each \$

Carabiners

- Auto-locking
- · Minimum breaking strength of 5000 lbs.
- Material: Steel







MSA

SGD364

SAM500

SGD362

Model No.	Mfg. No.	Gate Opening"	Price /Each
SGD364	10089205	9/16	
SAM500	10089207	1	
SGD362	10089209	2.1	