



## ShopStar Electric Hoists

- Rugged construction and compact design makes this unit ideal for a variety of commercial and industrial applications
- The H4 duty cycle rating allows the hoist to be used in production and maintenance environments
- Rugged cast aluminum alloy hoist frame
- Fully enclosed non-ventilated hoist frame protects motor from environmental contamination
- Includes a standard protector overload device
- 6 1/2' power cord molded 3-prong plug on 115 V units
- Gear train lifetime lubricated with non-oxidizing grease
- 10-pocket oblique lay liftwheel provides longer chain wear
- Alloy load chain • Standard Lift: 10'
- Hook mount suspension
- Epoxy powder coat finish
- **Lifetime warranty**
- cUL approved and meets ASME B30.16



Model No.	Lift Speed FPM	Voltage	Phase	Capacity lbs.	Weight lbs.	Price /Each
LT598	16	115	1	250	28	
LT599	16	115	1	300	28	
LT600	8	115	1	500	34	
LT601	8	115	1	600	34	
LT602	6	115	1	1000	34	
LT603	24	575	3	250	28	
LT604	16	575	3	300	34	
LT605	16	575	3	500	28	
LT606	12	575	3	600	34	
LT607	20	575	3	600	32	

**Note:** Additional lifts & capacities available on request

## ShopAir Chain Hoists

- Rugged cast aluminum alloy hoist frame and industrial-duty air motor makes this unit an ideal hoist for a workstation and/or production line
- Includes a standard protector overload device
- Fully enclosed non-ventilated hoist frame protects motor from environmental contamination
- 10-pocket, oblique lay liftwheel provides longer chain life
- Hook mount suspension
- Variable flow, two lever pendant for precise load spotting
- Gear train lifetime lubricated with non-oxidizing grease
- Hardened forged steel, latch-type lower hook rotates 360°
- Alloy load chain • Standard Lift: 10'
- Epoxy powder coat finish provides a durable exterior
- **Lifetime warranty**
- Meets ASME B30.16



Model No.	Lift Speed FPM	Headroom"	Capacity lbs.	Weight lbs.	Price /Each
LT608	16	11-15/16"	500	32	
LT609	31	10-7/8"	300	28	
LT610	16	10-7/8"	600	30	
LT611	21	10-7/8"	500	34	
LT612	11	11-15/16"	1000	45	

**Note:** Additional lifts & capacities available on request

## Electric Chain Hoist

- Multi-disc magnetic brake for positive load holding and spotting
- Adjustable upper and lower limit switches
- Overload limiting clutch and latch-type ridged top hook
- 24-volt pushbutton station fits easily in your hand to allow thumb, trigger or two-handed operation
- Made in the USA
- **5 year warranty**
- Max Lift Speed (ft./min): 16 FPM
- Min Lift Speed (ft./min): 16 FPM
- Voltage: 115V/230V
- Chain Material: Steel
- Phase: 1



Model No.	Mfg No.	Lift'	Capacity	Price /Each
TEA071	9560	10	1000 lbs. (0.5 tons)	
TEA072	9561	15	1000 lbs. (0.5 tons)	
TEA073	9562	20	1000 lbs. (0.5 tons)	
TEA074	9565	10	2000 lbs. (1 tons)	
TEA075	9566	10	2000 lbs. (1 tons)	
TEA076	9567	15	2000 lbs. (1 tons)	
TEA077	9568	20	2000 lbs. (1 tons)	
TEA078	9570	10	4000 lbs. (2 tons)	
TEA080	9572	15	4000 lbs. (2 tons)	
TEA081	9573	20	4000 lbs. (2 tons)	

## Adjustable Trolleys

- Easily adjusts to fit various flanges, I-beams and H-beams
- Use on straight or curved track
- Can be installed or removed at any position on the beam
- Heavy-duty cast iron wheels
- Deep width flange provides superior contact with the beam
- Geared trolleys include two geared wheels operated by hand chain
- Safety plate included
- Meets ASME B30.16



### Adjustable Plain Trolley



Model No.	Fits I beams"	Cap. lbs.	Wt. lbs.	Price /Each
LS551	2 11/16 - 5 3/8	1000	10	
LS552	3 1/8 - 6 1/4	2000	17	
LS553	3 1/8 - 6 1/4	4000	28	
LS554	3 7/16 - 7 3/8	6000	46	
LS555	4 13/16 - 9 9/16	10000	73	

### GEARED

Model No.	Fits I beams"	Cap. lbs.	Wt. lbs.	Price /Each
LS556	2 11/16 - 5 1/4	1000	18	
LW558	3 1/8 - 5 15/16	2000	25	
LS558	3 1/8 - 7 1/16	4000	36	
LW560	3 7/16 - 7 3/8	6000	54	
LS560	4 3/4 - 7 3/4	10000	81	



### Adjustable Geared Trolley

## CBT Adjustable Trolleys

- Adjustable trolleys are available in plain and geared to fit most applications up to 8.7" beam flange widths
- Dual tread wheels will fit either tapered or flat beam flanges and include permanently lubricated, shielded ball bearings for long life and reduced maintenance
- **Lifetime warranty**



Model No.	Stand Beam Height"	Stand Beam Width"	Wt. lbs.	Capacity Tons lbs.	Price /Each
-----------	--------------------	-------------------	----------	--------------------	-------------

### PLAIN

LT300	8-24	3.0-8.7	86	3 6000	
LT301	10-24	3.5-8.7	130	5 10000	

### GEARED

LT302	5-24	2.3-8.7	26	1 2000	
LT305	8-24	3.0-8.7	86	3 6000	
LT306	10-24	3.5-8.7	130	5 10000	



## HTG Geared Clevis Trolley

- CM HTP and HTG Clevis Trolleys can easily be installed in seconds for exactpositioning or seamless traversing of loads with manual or powered hoists
- These universal trolleys are compatible with nearly any Columbus McKinnon hoist brand or model
- Adjust the flange width in a matter of seconds by turning the trolley axle, eliminating the need for loose parts, including spacer washers, when installing the trolley
- Adjustments are made by rotating the clevis load bar, ensuring the centered positioning of the hoist in the clevis to prevent creeping to the left or right
- Trolley wheels are pre-lubricated with encapsulated ball bearings for smooth rolling
- Available for all capacities, spark-resistant trolleys are equipped with bronze wheels, rubber bumpers as standard equipment, and stainless steel hand chain on geared trolleys
- Capacity: 4409 lbs. (2 tons)
- I-Beam Flange Width: 2-39/64" - 8-43/64"
- Flange Thickness: 0.99"
- Min. Radius: 45.28"
- Weight: 40 lbs.

**Model No. LW530**  
**Mfg. No. HTG0200A**  
**Price/Each \$**

