



Polyester Slings

- Mainly used outdoors and can withstand increases in temperature and direct sunlight (i.e. improved UV degradation resistance)
- Used in conjunction with overhead cranes, hoists or winches
- Polyester slings are available in single or double ply to protect heavy, irregular sized loads from scratching or marring
- Slings must be checked frequently
- Should any surface area show signs of wear or cutting, the sling must be replaced immediately
- Each is tagged with manufacturer's name and capacity



Type 3



Type 4



Type 5

DOUBLE EYE SLING TYPE 3

Commonly used as a basket and/or choker hitch or for choker hitch pass one eye through the other flat eye, also makes for easy withdrawal from beneath loads

TWISTED EYE SLING TYPE 4

Reverse eyes make full functional contact with lifting hooks without the use of hardware. Widely used for both choker and basket hitches

ENDLESS SLING TYPE 5

Most versatile and widely used sling. The economical answer to most lifting problems. Ideal for vertical, choker and basket hitches

LOAD LIMIT FOR TYPE 3-4 (LBS.)

Width"	Vertical		Choker		Basket	
	Single	Double	Single	Double	Single	Double
1	1600	3200	1280	2400	3200	6400
2	3100	6200	2480	4960	6200	12 400
3	4700	8800	3760	7040	9400	17 600
4	6200	11 000	4960	8800	12 400	22 000

LOAD LIMIT FOR TYPE 5 (LBS.)

Width"	Vertical		Choker		Basket	
	Single	Double	Single	Double	Single	Double
1	3200	6200	2560	4960	6400	12 400
2	6200	12 400	4960	9930	12 400	24 800
3	9400	17 600	7520	14 080	18 800	35 200
4	12 400	22 000	9920	17 600	24 800	44 000

Type	Width"	Ply	3' Model No.	Price /Each	4' Model No.	Price /Each	6' Model No.	Price /Each	8' Model No.	Price /Each	10' Model No.	Price /Each	12' Model No.	Price /Each	
TYPE 3	1	Single	LU116		LU117		LU118		LU119		LU120		LU121		
		Double	LU140		LU141		LU142		LU143		LU144		LU145		
	2	Single	LU122		LU123		LU124		LU125		LU126		LU127		
		Double	LU146		LU147		LU148		LU149		LU150		LU151		
	3	Single	LU128		LU129		LU130		LU131		LU132		LU133		
		Double	LU152		LU153		LU154		LU155		LU156		LU157		
	4	Single	LU134		LU135		LU136		LU137		LU138		LU139		
		Double	LU158		LU159		LU160		LU161		LU162		LU163		
TYPE 4	1	Single	LU164		LU165		LU166		LU167		LU168		LU169		
		Double	LU188		LU189		LU190		LU191		LU192		LU193		
	2	Single	LU170		LU171		LU172		LU173		LU174		LU175		
		Double	LU194		LU195		LU196		LU197		LU198		LU199		
	3	Single	LU176		LU177		LU178		LU179		LU180		LU181		
		Double	LU200		LU201		LU202		LU203		LU204		LU205		
	4	Single	LU182		LU183		LU184		LU185		LU186		LU187		
		Double	LU206		LU207		LU208		LU209		LU210		LU211		
	TYPE 5	1	Single	LU212		LU213		LU214		LU215		LU216		LU217	
			Double	LU236		LU237		LU238		LU239		LU240		LU241	
2		Single	LU218		LU219		LU220		LU221		LU222		LU223		
		Double	LU242		LU243		LU244		LU245		LU246		LU247		
3		Single	LU224		LU225		LU226		LU227		LU228		LU229		
		Double	LU248		LU249		LU250		LU251		LU252		LU253		
4		Single	LU230		LU231		LU232		LU233		LU234		LU235		
		Double	LU254		LU255		LU256		LU257		LU258		LU259		

Chain Slings

- Quality grade 80 alloy steel assembled, feature a design factor of 4:1
- Proof tested and certified to twice the working load limit
- Proof test certificate issued with each sling
- Available with sling hook or grab hook
- Slings comes with identification tag indicating size, description and working load limit



Sling Hook



Grab hook



Chain Size"	Hook Type	5' Sling Model No.	Price /Each	8' Sling Model No.	Price /Each	10' Sling Model No.	Price /Each
DOUBLE CHAIN							
9/32	Sling	LV840		LV852		LV864	
9/32	Grab	LV804		LV816		LV828	
3/8	Sling	LV842		LV854		LV866	
3/8	Grab	LV806		-		LV830	
1/2	Sling	-		-		LV867	
1/2	Grab	LV807		LV819		LV831	
5/8	Grab	-		-		LV832	

Note: Other lengths, hook types and chain types available upon request

Chain Size"	Hook Type	5' Sling Model No.	Price /Each	8' Sling Model No.	Price /Each	10' Sling Model No.	Price /Each
-------------	-----------	--------------------	-------------	--------------------	-------------	---------------------	-------------

SINGLE CHAIN

9/32	Sling	LV732		LV744		LV756	
9/32	Grab	LV696		LV708		LV720	
3/8	Sling	LV734		LV746		LV758	
3/8	Grab	LV698		LV710		LV722	
1/2	Sling	LV735		LV747		LV759	
1/2	Grab	LV699		LV711		LV723	
5/8	Grab	LV700		LV712		LV724	

CAPACITY LBS.

Chain Size"	Single			
	90°	60°	45°	30°
9/32	3500	6100	4900	3500
3/8	7100	12 300	10 000	7100
1/2	12 000	20 800	17 000	12 000
5/8	18 100	31 300	25 600	18 100