

Polyolefin Casters

- Rolls easily on most floors
- Lightweight and economical
- Non-marking, easy to maintain, steam cleanable
- High impact strength
- Superior resistance to most oils, chemicals, grease and acids

Model No.	Wheel Dia."	Style	Cap. Ibs.	Tread Width"	Overall Height"	Price /Each
ML391	3	Swivel	250	1-1/4	4-1/2	
ML392	3	Rigid	250	1-1/4	4-1/2	
ML393	4	Swivel	250	1-1/4	5-1/4	
ML394	4	Rigid	250	1-1/4	5-1/4	
ML395	5	Swivel	250	1-1/4	6-1/8	
ML396	5	Rigid	250	1-1/4	6-1/8	

Blue Elastic Rubber Casters

- High load capacity, rolls easily and quietly on all floors
- Non-marking, excellent floor protection
- Zinc chrome plated finish provides corrosion resistance
- Elastic rubber tread rejects floor debris •
- Sealed double ball raceway

•	Thread guards
	Pall bearing

- Ball bearing
- Total locking brake locks the wheel
- and keeps the swivel from turning

Model No.	Wheel Dia."	Style	Cap. Ibs.	Tread Width"	Overall Height"	Price /Each
M0511*	3	Swivel	285	1-1/4	4-1/4	
M0512*	3	Rigid	285	1-1/4	4-1/4	
M0513*	3	Swivel w/Brake	285	1-1/4	4-1/4	
ML333	4	Swivel	350	1-3/8	5	
ML334	4	Rigid	350	1-3/8	5	
ML342	4	Swivel w/Brake	350	1-3/8	5	
ML337	5	Swivel	400	1-3/8	6	
ML338	5	Rigid	400	1-3/8	6	
ML345	5	Swivel w/Brake	400	1-3/8	6	

* Roller Bearing

Nylon Sandwich Casters

Polyurethane Casters

Resistant to most chemicals, moisture friendly

Die cast aluminum core with brown polyurethane tread

Smooth rolling, low noise operation

Non-marking, cut & tear resistant

- Non-marking white nylon elastic rubber cushion
- ring layer reduces noise and vibration
- Chrome zinc-finish for corrosion resistance .
- Double raceway • Ball bearing
- Total locking brake locks the wheel and keeps the swivel from turning

Model	Wheel		Cap.	Tread	Overall	Price
No.	Dia."	Style	lbs.	Width"	Height"	/Each
MN441	4	Swivel	440	1-3/8	5-1/8	
MN442	4	Rigid	440	1-3/8	5-1/8	
MN443	4	Swivel W/Brake	440	1-3/8	5-1/8	
MN444	5	Swivel	440	1-3/8	6-1/8	
MN445	5	Rigid	440	1-3/8	6-1/8	
MN446	5	Swivel W/Brake	440	1-3/8	6-1/8	

SURFACE APPLICATIONS:

Concrete, brick, carpet and steel Plate Size: **Bolt hole centers:** Bolt hole size:

5/16"

3-1/3" x 4-1/8" 3-1/8" x 2-1/3"

MN443



• Total locking brake locks the wheel

Annular ball bearing

- and keeps the swivel from turning
- Butterfly side brake locks the wheel preventing it from rolling

Model No.	Wheel Dia."	Style	Cap. Ibs.	Tread Width"	Overall Height"	Price /Each			
MP696	3	Swivel	230	1-1/4	4-1/4		Plate size:	Bolt hole centres:	Bolt hole size:
MP695	3	Rigid	230	1-1/4	4-1/4		3 = 2-5/8" x 3-3/4"	3 = 1-3/4" x 2-3/4"	3 = 5/16"
ML045	4	Swivel	440	1-1/2	5-3/8		4 = 3-1/8" x 4-1/8"	4 = 2-3/8" x 3-1/16"	4 = 5/16"
ML046	4	Rigid	440	1-1/2	5-3/8		4 HD = 4" x 4-1/2"	4 HD = 3-1/4" x 2-3/4"	4 HD = 3/8"
ML441	4HD	Swivel	550	1-5/8	5-5/8		5 = 4" x 4-1/2"	5 = 3-1/4" x 2-3/4"	5 = 3/8"
ML442	4HD	Rigid	550	1-5/8	5-5/8		6 = 4" x 4-1/2"	6 = 3-1/4" x 2-3/4"	6 = 3/8"
MN264	4HD	Swivel w/brake	550	1-5/8	5-5/8		8 = 4" x 4-1/2"	8 = 3-1/4" x 2-3/4"	8 = 3/8"
ML397	5	Swivel	650	1-1/2	6-1/2				
ML398	5	Rigid	650	1-1/2	6-1/2				
MN265	5	Swivel w/brake	650	1-1/2	6-1/2				There
ML399	6	Swivel	850	1-1/2	7-1/2				
ML400	6	Rigid	850	1-1/2	7-1/2			1 aug -	noto ma
MN266	6	Swivel w/brake	850	1-1/2	7-1/2		The second		Series States
MN449	6	Butterfly side brake	850	1-1/2	7-1/2			and the second	
ML401	8	Swivel	1000	1-5/8	9-1/2				
ML402	8	Rigid	1000	1-5/8	9-1/2				
MN267	8	Swivel w/brake	1000	1-5/8	9-1/2				
MN450	8	Butterfly side brake	1000	1-5/8	9-1/2		ML045	ML046	MN264

www.tenaquip.com

ML342 SURFACE APPLICATIONS:

SURFACE APPLICATIONS: Concrete, brick, carpet and steel

2-5/8" x 3-3/4"

2-3/4" x 1-3/4"

5/16"

ML391

Plate size:

Bolt hole centres:

Bolt hole size:

Concrete, brick, carpet, steel, tile, asphalt, wood and linoleum

Plate size: 3-3/8" x 4" 2-3/8" x 3-1/8" **Bolt hole centres:** Bolt hole size: 3/8"



MN441

ML334

ML394

ML333

MN442

