



Hi-Temp Nylon Casters

- Smooth rolling, non-marking
- Zinc chrome plated finish provides corrosion resistance
- Superior resistance to most oils, chemicals, and grease
- Double ball raceway
- Ball bearing
- Max. temperature: 230°C
- Total locking brake locks the wheel and keeps the swivel from turning
- Butterfly side brake locks the wheel preventing it from rolling

SURFACE APPLICATIONS:

Concrete, brick, carpet and steel

Plate Size: 4" x 4-1/2"

Bolt hole centers: 3" x 3-1/3"

Bolt hole size: 7/16"



ML862

ML863

Model No.	Wheel Dia."	Style	Cap. lbs.	Tread Width"	Overall Height"	Price /Each
ML861	6	Swivel	800	1-3/4	7-5/8	
ML862	6	Rigid	800	1-3/4	7-5/8	
ML863	6	Swivel W/Brake	800	1-3/4	7-5/8	
MN453	6	Butterfly side brake	800	1-3/4	7-5/8	
ML864	8	Swivel	850	1-3/4	9-1/2	
ML865	8	Rigid	850	1-3/4	9-1/2	
ML866	8	Swivel W/Brake	850	1-3/4	9-1/2	
MN454	8	Butterfly side brake	850	1-3/4	9-1/2	

Mold-On Rubber Casters

- Molded rubber wheel permanently bonded to spoked cast iron core
- Iron centre gives it strength while the molded rubber offers smooth and quiet operation
- Protects loads and surfaces
- Won't damage warehouse or factory floors
- Total locking brake locks the wheel and keeps the swivel from turning
- Butterfly side brake locks the wheel preventing it from rolling

SURFACE APPLICATIONS:

Concrete, brick, carpet, steel, tile, asphalt, wood and linoleum

Plate Size: 4" x 4-1/2"

Bolt hole centers: 2-7/8" x 3-1/3"

Bolt hole size: 7/16"



ML851

ML852

ML853

Model No.	Wheel Dia."	Style	Cap. lbs.	Tread Width"	Bearing Type"	Price /Each
ML846	5	Swivel	400	2	Roller	
ML847	5	Rigid	400	2	Roller	
ML849	6	Swivel	500	2	Roller	
ML850	6	Rigid	500	2	Roller	
ML851	6	Swivel w/Brake	500	2	Roller	
MN451	6	Butterfly side brake	500	2	Roller	
ML852	8	Swivel	600	2	Roller	
ML853	8	Rigid	600	2	Roller	
ML854	8	Swivel w/Brake	600	2	Roller	
MN452	8	Butterfly side brake	600	2	Roller	

Pneumatic Casters

- Four ply pneumatic casters offer smooth and quiet rolling over the roughest surfaces and outdoor terrain
- Shock absorbing properties give the greatest possible protection to both the load and floor
- The "Air cushion" feature will transport the most fragile material and instruments without damage
- Not recommended for floors with metal shavings or corrosive chemicals

SURFACE APPLICATIONS:

Concrete, brick, carpet, steel, tile, asphalt, wood and linoleum

Plate Size: 4" x 4-1/2"

Bolt hole centers: 2-3/4" x 3-3/8"

Bolt hole size: 13/32"



MN221

MN222



Model No.	Wheel Dia."	Style	Cap. lbs.	Tread Width"	Overall Height"	Price /Each
MN222	8	Swivel	350	2	10	
MN221	8	Rigid	350	2	10	
MN224	10	Swivel	400	3	12	
MN223	10	Rigid	400	3	12	

Note: For optimum use pneumatic wheels must be properly inflated

Flat-Free Casters

- Solid polyurethane wheel never runs flat
- Same bounce feel and weight of a pneumatic caster
- Smooth and quiet rolling over rough terrain and surfaces
- Less costly than traditional foam-filled tires
- Ball bearing

SURFACE APPLICATIONS:

Concrete, brick, carpet, steel, tile, asphalt, wood and linoleum

Plate Size: 4" x 4-1/2"

Bolt hole centers: 2-3/4" x 3-3/8"

Bolt hole size: 13/32"



MN228

MN227



Model No.	Wheel Dia."	Style	Cap. lbs.	Tread Width"	Overall Height"	Price /Each
MN226	8	Swivel	275	2	10	
MN225	8	Rigid	275	2	10	
MN228	10	Swivel	300	3	12	
MN227	10	Rigid	300	3	12	

Semi-Pneumatic Wheel

- Soft rubber tread with steel hub and ball bearings for quiet movement
- Excellent for dollies, floor protection, quiet operation, light duty stock trucks
- Wheel Diameter: 10"
- Capacity: 200 lbs.
- Bearing Type: Ball
- Bore Size: 3/4"
- Tread Width: 2-1/2"
- Temperature: -20°F to 130°F
- Durometer: 85 - 90 A scale
- Hub Type: Offset

Model No. MO888
Price/Each \$

