



Graduated Drum Gauges

Combination gauge and faucet permits uninterrupted draining of drum contents with gauge in place. Mounts through 3/4" bung hole. Constructed of heavy gauge glass in plated steel body with Buna-N seals. Weight: 3 lbs.



Model No.	Description	Price/Each
DA064	Gauge only	
DA065	Gauge with faucet*	

* Zinc Die Cast Faucet FM approved for viscous liquids only; no flame arrestor.

Drum Fill Gauges

Provides a low cost solution to over-filling drums. When the drum is almost full, the indicator "Pops-up" to warn you. Fits in standard 3/4" bung opening. Bright red and yellow molded polyethylene. 5" length. Weight: 0.20 oz.



Model No.	Price/Each
DA066	

Safety Drum Funnels

Suitable for handling flammables. Large 10 3/4" mouth provides quick dumping. Steel construction with 6" flame arrestor for the DA102 and 32" flame arrestor for the DA101. Hinged cover with fusible link reduces spread of vapours. 2" NPS/NPT.FM approved.



Model No.	Description	Wt. lbs.	Price /Each
DA102	6" flame arrestor w/funnel	7.5	
DA101	32" flame arrestor w/funnel	12	

Horizontal Brass Vents

- Horizontal vents are for use with drums in the horizontal pouring position
- Automatically relieves pressure at 5 PSI
- Flame arrestor prevents sparks and flame from igniting contents
- Manual vacuum relief by lifting and rotating the valve stem
- Maximum flow of 220 CFM at 20 PSI
- Fits 2" NPS bung in steel or plastic drums



Model No. PE362
Price/Each \$



Vertical Vents

FM approved vents are for use with drums in the upright position. Valve automatically opens to relieve internal pressure at 5 PSI. Automatic vacuum relief permits 4 GPM flow through 3/4" faucet. Fits 2" NPT bung opening.



Model No.	Description	Application	Wt. lbs.	Price /Each
DA607	Brass Vent	Petroleum-Based	0.5	
DA605	Non-metallic Vent, Cad-plated flame arrestor	Petroleum-Based	0.5	
DA606	Non-metallic Vent, Stainless steel flame arrestor	Chlorinated Solvents	1.0	

