



Pull Type Drum Pumps

Chemical compatibility of a drum or barrel pump should be checked for EACH LIQUID BY CHEMICAL NAME!

No single drum pump can be universally chemical resistant. Some blends of chemicals may not be suitable for any of these drum pumps. Remember to have your MSDS for each chemical that will be pumping when calling your our representative.

We will be able to help you select the right pump for your application.

Polypropylene

KLETON

Wetted components:

Polyethylene, polypropylene, silicone and steel

- For use with most corrosive chemicals and non-flammable solvents
- Adapts to 3/4" or 2" bung adaptor for 5 to 55-gallon drums
- 360° discharge spout orientation
- Transfer Rate: 16 oz. per stroke

Model No. DC115
Price/Each \$



Wetted components:

Polypropylene, steel and Viton®

- For use with most antifreeze, detergents, windshield fluids, glycerin, and mild acids
- Fits 15 to 55-gallon drums with 2" bung adaptor
- Transfer Rate: 14 oz. per stroke

Model No. DC127
Price/Each \$



Wetted components:

Polyethylene, polypropylene and nylon

- For use with most corrosive chemicals, water, and non-flammable solvents
- Good insulation from spark and fire
- Fits 55-gallon drums with a 2" bung adaptor
- Transfer Rate: 22 oz. per stroke

Model No. DC117
Price/Each \$



Wetted components:

Polypropylene, polyethylene, silicone and steel

- For use with most corrosive chemicals and non-flammable solvents
- Adapts to 3/4" or 2" bung adaptor for 5 to 55-gallon drums
- 360° discharge spout orientation
- Transfer Rate: 8 oz. per stroke

Model No. DA532
Price/Each \$



PVC

KLETON

Wetted components:

Polypropylene, PVC, nylon and Viton®

- For use with most mild acids, detergents, water and solvents
- Good insulation from spark and fire
- Transfer rate: 8 oz. per stroke

Model No. DC116
Price/Each \$

Wetted components:

PVC, nylon and Viton®

- For use with most mild acids, detergents, water and solvents
- Good insulation from spark and fire
- Fits 55-gallon drums with a 2" bung adaptor
- Transfer Rate: 22 oz. per stroke

Model No. DC118
Price/Each \$



Nylon

Wetted components:

Polypropylene, nylon, 304 stainless steel and PTFE

- For use with most lacquer thinners, mild acids, detergents, water and light viscosity petroleum liquids
- Fits 15 to 55-gallon drums with 2" bung adaptor
- Transfer Rate: 14 oz. per stroke

Model No. DC128
Price/Each \$

KLETON



FM Approved Pull Type Drum Pump

- For fast transfer of most solvents, acids and corrosives chemicals
- Fits 15-55-gallon drums with a 2" bung adaptor
- Pump body made from 316 Stainless Steel with PTFE Piston & PTFE Sealing Gasket
- Heavy-Duty bonding and grounding wires prevent hazardous static charge
- Wires are secured by locknut and have heavy-duty alligator clips
- Built-in internal flame arrestor prevents flame flashback
- Wetted components: 316 Stainless Steel, PTFE
- Transfer Rate: 7 oz./Stroke
- Fits Gallon Size: 15 - 55 gal.
- Body Material: Stainless Steel
- Adaptor Type: 2" Bung

Model No. DC765
Price/Each \$

KLETON

