



Gas Powered Water Pump

- Powerful air-cooled engine
- 92' total head lift (total height at sea level, to which water can be raised above original water level)
- Oil sensor shuts off engine when oil level is low
- Self-priming pump for easy operation
- Cast iron impeller and aluminum alloy high pressure pump body casting
- Easy start recoil starter
- Heavy-duty roll cage protects engine and pump
- Includes: (3) Wire clamps, (4) Hose adaptors, (4) Rubber gaskets, (1) Strainer basket, (1) Strainer basket adaptor
- Engine Size: 196 cc
- Engine Type: 4-Stroke OHV
- Engine HP: 7.0 HP
- Engine Speed: 3600 RPM
- Fuel Tank: 3.6 L
- Oil Capacity: 0.6 L



UAJ264



Model No.	UAJ265 2" Water Pump	UAJ264 3" Water Pump
Engine:	Honda GX160 OHV, 5.5 HP	Honda GX240 OHV, 8.0 HP
Port Size:	2"	3"
Maximum Capacity:	600 L/min.	835 L/min.
Maximum Head:	96'	96'
Dimensions:	17-1/2" x 14-1/2" x 15"	20" x 14-3/4" x 17-1/4"
Weight:	52 lbs.	56 lbs.
Price/Each:	\$	\$

Reinforced Suction Hose Kit for Water Pump

- Includes: Hose, Stainless steel strainer basket, Camlock, Threaded camlock adaptor
- Length: 25'
- Colour: Clear
- Material: PVC



Model No.	CAM Size"	Max. Pressure PSI	Weight lbs.	Price /Each
TMA094	2	100	20	
TMA095	3	72	28	

Lay-Flat Discharge Hose Kit for Water Pump

- Camlock adapter allows two discharge hoses to be attached together
- Includes: Hose, Type A threaded camlock adapter
- Length: 50'
- Colour: Blue
- Material: PVC



Model No.	CAM Size"	Max. Pressure PSI	Weight lbs.	Price /Each
TMA096	2	58	15	
TMA097	3	58	24.5	

Need help?

Have one of our qualified specialists visit you.

1-800-661-2400

