



High Performance V7400 DTM

- Get outstanding protection and color
- Resists chipping, fading, weathering
- Protects against mild chemicals — ideal for moderate to slightly severe industrial environments
- Two-year rust-proof guarantee — maximum corrosion protection
- For use on: General plant maintenance, machinery, equipment, structural steel, pipes, metal cabinets, lockers, railings, trim, doors, gates, vents, outdoor signage, water towers, agriculture, drilling, coastal applications, vehicle refinishing
- Size: 1 Gal.
- Accepted for use in Canadian food processing facilities

| Model No. | Mfg. No. | Colour | Price /Each |
|-----------|----------|--------|-------------|
|-----------|----------|--------|-------------|

SURFACE COVERAGE:
275-510 SQ. FT./GAL. (6.8-12.5 M²/L)

| | | | |
|-------|--------|------------|--|
| KP410 | 245387 | Flat Black | |
| KP411 | 245533 | Flat White | |

SURFACE COVERAGE:
230-450 SQ.FT./GAL. (5.7-11.1 M²/L)

| | | | |
|-------|--------|---------------|--|
| KP412 | 245403 | Gloss Black | |
| KP413 | 245406 | Gloss White | |
| KP415 | 245443 | Navy Grey | |
| KP421 | 245484 | Silver Grey | |
| KP416 | 245474 | Safety Blue | |
| KP417 | 245476 | Safety Green | |
| KP418 | 245477 | Safety Orange | |
| KP419 | 245478 | Safety Red | |
| KP420 | 245479 | Safety Yellow | |



KP410



High Performance 9100 DTM Epoxy Mastic

- Quickly creates a tough, durable, protective surface
- Direct-to-metal (DTM) self priming formula — adheres to a variety of substrates
- Superior long-term resistance to solvents, chemicals, abrasion and impact
- Convenient 1:1 mixing ratio of base and activator - no measuring required
- Two-year rust-proof guarantee — maximum corrosion protection
- For use on: Steel beams, structural steel, towers, concrete floors, conveyors, industrial equipment, storage tanks, sewage treatment basins, non-potable water storage facilities, steel handrails
- Size: 1 Gal.
- Accepted for use in Canadian food processing facilities

| Model No. | Mfg. No. | Colour | Price /Each |
|-----------|----------|--------|-------------|
|-----------|----------|--------|-------------|

COLOURS

| | | | |
|-------|---------|---------------|--|
| KP424 | 9144402 | Safety Yellow | |
| KP425 | 9179402 | Black | |
| KP426 | 9182402 | Silver Grey | |
| KP427 | 9192402 | White | |

ACTIVATORS

| | | | |
|-------|----------|---------------------|--|
| KP428 | 9101402 | Standard Activator | |
| KP429 | V7696402 | Immersion Activator | |



KP424



C740 DTM Alkyd Maintenance Paint

- Ready-to-use formula provides an easy-to-maintain, high-gloss finish specifically for commercial applications
- Multi-purpose direct-to-metal (DTM) coating
- Convenient — requires no measuring or mixing; can be brushed, rolled or sprayed
- Resists rust, chipping, general weathering, mild chemical fumes and light abrasion
- For use on: Interior & exterior commercial metal applications, metal trim (doors & structural steel), handrails, fixtures, fire escapes, vents, fences, hydrants, cabinets, channels
- Surface coverage: 265-440 sq. ft./gal. (6.5-10.8 m²/L)
- Accepted for use in Canadian food processing facilities



KP478



| Model No. | Mfg. No. | Colour | Price /Each |
|-----------|----------|--------|-------------|
|-----------|----------|--------|-------------|

| | | | |
|-------|--------|---------------|--|
| KP478 | 255554 | Black | |
| KP479 | 255558 | White | |
| KP480 | 255550 | Safety Yellow | |

Rust Tough® Acrylic Alkyd Enamels

AEROSOLS

- Complete coverage with one coat
- Dries to touch in 25 minutes; dries to handle in 1 hour
- Superior appearance and colour retention
- Ideal for small touch-up jobs, painting irregular shapes or covering hard-to-reach areas
- For both indoor and outdoor use
- Tough, high-gloss finish resists chipping and peeling
- Acrylic enamels and primers are equipped with EZ Touch® Fanspray® nozzle
- Case Qty: 6 cans



Applications: Steel, aluminum, properly primed metal and wood, structural steel, storage tanks, bar joists, handrails, piping, pipe racks, conveyors, ladders, fencing, machinery, metal doors and marine applications above boot topping.

Note: Not recommended for immersion.

| Model No. | Colour | Size Can (Net) | Price /Each |
|-----------|--------|----------------|-------------|
|-----------|--------|----------------|-------------|

AEROSOLS

| | | | |
|-------|-------------------------------|--|-----------------|
| NA356 | Flat Black | | 20 oz. (15 oz.) |
| NA360 | Gloss Black | | 20 oz. (15 oz.) |
| NA393 | Gloss White | | 20 oz. (15 oz.) |
| NA352 | Semi-Gloss Black | | 20 oz. (15 oz.) |
| ZB013 | Semi-Gloss White | | 20 oz. (15 oz.) |
| NA273 | Safety Blue (OSHA) | | 20 oz. (15 oz.) |
| NA286 | Safety Green (OSHA) | | 20 oz. (15 oz.) |
| NA322 | Safety Orange (OSHA) | | 20 oz. (15 oz.) |
| NA330 | Safety Red (OSHA) | | 20 oz. (15 oz.) |
| NA302 | Safety Yellow (OSHA) | | 20 oz. (15 oz.) |
| NA326 | Equipment Orange | | 20 oz. (15 oz.) |
| NA318 | Equipment Yellow | | 20 oz. (15 oz.) |
| NA314 | Industrial Yellow | | 20 oz. (15 oz.) |
| NA306 | Federal Safety Railing Yellow | | 20 oz. (15 oz.) |
| NA368 | Light Machinery Grey (Asa-61) | | 20 oz. (15 oz.) |
| NA294 | Bright Green | | 20 oz. (15 oz.) |
| NA298 | Dark Green | | 20 oz. (15 oz.) |
| NA334 | Bright Red | | 20 oz. (15 oz.) |
| NA264 | Aluminum | | 20 oz. (15 oz.) |
| NA269 | Light Blue | | 20 oz. (15 oz.) |
| NA277 | Deep Blue | | 20 oz. (15 oz.) |
| NA346 | Chestnut Brown | | 20 oz. (15 oz.) |
| NA342 | Tan | | 20 oz. (15 oz.) |
| NA435 | Fluorescent Green | | 20 oz. (14 oz.) |
| NA436 | Fluorescent Yellow | | 20 oz. (14 oz.) |
| NA437 | Fluorescent Orange | | 20 oz. (14 oz.) |
| NA438 | Fluorescent Red | | 20 oz. (14 oz.) |
| NA348 | Hi-Temp Black | | 20 oz. (15 oz.) |

PRIMERS

| | | | |
|-------|----------------------------------|--|-----------------|
| NA364 | Grey Primer | | 20 oz. (15 oz.) |
| NA338 | Red Oxide Primer | | 20 oz. (15 oz.) |
| NA375 | Zinc-Rich Cold Galvanized Primer | | 20 oz. (15 oz.) |

3800 High-Performance DTM Acrylic Enamel

- Dries to touch in 15 minutes
- Excellent corrosion resistance
- Applies directly to metal
- Applies with very little brush drag
- Container Type: Gallon
- Container Size: 1 gal.
- Net Volume: 1 gal.
- Finish: Gloss
- VOC: 250 g/L



KP775



| Model No. | Mfg. No. | Colour | Price /Each |
|-----------|----------|--------|-------------|
|-----------|----------|--------|-------------|

| | | | |
|-------|--------|-------------------|--|
| KP767 | 314594 | Light Tint Base | |
| KP768 | 314593 | Deep Tint Base | |
| KP769 | 314592 | Mastone Tint Base | |
| KP770 | 314389 | White | |
| KP771 | 314388 | Navy Blue | |
| KP772 | 314387 | Black | |
| KP773 | 314410 | Safety Red | |
| KP774 | 314409 | Safety Yellow | |
| KP775 | 314407 | Safety Green | |
| KP776 | 314209 | Safety Blue | |
| KP777 | 315506 | Silver Grey | |
| KP780 | 315510 | Safety Orange | |