

# 4 V M4<sup>™</sup> 1/4" Hex Screwdrivers

- 21-position clutch setting
- with auto shut-off Includes: (2x) M4<sup>™</sup> 2.0 battery

## and M4<sup>™</sup> charger

### **SPECIFICATIONS**

Voltage: **Chuck Size:** Maximum Torque: # of Speed Settings: # of Speed Settings: No Load RPM Setting #1: No Load RPM Setting #2: **Clutch Settings: Tool Weight: Replacement Battery** Model No.:

4 V 1/4" Hex 44 in-lbs 2 2 0-200 0-600 21 0.85 lbs. TLV691 Milwaukee



# 1/4" Cordless Driver/Drill

- Auto stop system indicates battery power reduction and stops operation when battery reaches minimal capacity in order to prevent incomplete fastening
- Locking feature prevents accidental start up and enables use as a hand-held screwdriver
- Adjustable handle with enhanced hinge mechanism for operational versatility
- LED job light illuminates work area and features independent on/off switch
- Includes: Two 7.2 V Li-Ion (1.5 ah) batteries, charger, Phillips bit 1-50, Phillips bit 2-50, battery plastic case, plastic carrying case

#### **SPECIFICATIONS**

Voltage:	7.2 V
Chuck Size:	1/4"
Battery Type:	Lithium-lo
Max Torque:	71 in-lbs.
# of Speed Settings:	2
No Load RPM Setting #1:	0-200
No Load RPM Setting #2	0-650
Tool Weight:	0.9 lbs.

Model No. TYW999 Mfg. No. DF012DSE Price/Each \$

# 18 V M18<sup>™</sup> 1/2" Compact Drill/Drivers

-lon

- Compact, ergonomic drill/driver with an
- all-metal gear case for maximum durability Most compact drill/driver in its class
- Includes: (2) M18<sup>™</sup> Redlithium<sup>™</sup> compact battery, multi-voltage 12 V-18 V charger and carrying case

#### SDECIEIC ATIONS

SPECIFIC	CATION	S					
Voltage:			18 V				
Chuck Size	e:		1/2"				Contraction of the
Max Torqu	ie:	5	00 in-lbs.				
# of Speed	Settings	:	2			Milwauk	ee
No Load R	PM Settir	ng #1:	0-450			Illuoun	2 2 - 8
No Load R	PM Settir	ng #2:	0-1800				
Max BPM:		(	0-29000				Company of the local division of the local d
Clutch Set	tings:	A	djustable				<b>D</b> . V
Chuck Typ	e:	1,	/2" metal		-		
Tool Weig	ht:		3.6 lbs.	35.00			
Replacem		ry		Se I Im	61	AT AT	
Model N	lo.:		TLZ453		9/		
Model No.	Mfg. No.	Desc.	Price/Each				
TYD849	2606-20	Tool Only		1			
TLV700	2606-22	Tool & Ki	t				

# 12 V Lithium-Ion Sub-Compact **Cordless Drill/Driver Kits**

- Clutch settings: 14+1
- Features: Light compact design Built-in LED light
- Battery Fuel gauge
- Includes: (2x) 1.4 Ah Lithium-Ion Batteries, Charger and Tool bag
- Battery Type: Lithium-Ion

#### **SPECIFICATIONS**

Voltage: 12 V Chuck Size: 1/4" Max Torque: 150 in-lbs. # of Speed Settings: 1 No Load RPM Setting #1: 0-500 Chuck Type: Hex quick change Tool Weight: 2.1 lbs. **Replacement Battery** Model No.: TLZ368



# Xtreme<sup>™</sup> Brushless Screwdriver Kit

- Designed for hard to reach fastening applications that require clutch control
- Brushless motor for Maximum runtime and durability
- Quick release drop and load hex that accepts 1" bit tips
- 3 LED lights on nose for work surface illumination Includes: (1) 12 V Max\* brushless 1/4" screwdriver.
- (2) 12 V Max\* 2 Ah batteries with state of charge indicator, (1) 12 V and 20 V Max\* charger, (1) Belt clip, (1) Kit bag

#### SPECIFICATIONS

DEWALT

Thakita

Milwaukee

Thakita

Voltage: 12 V Chuck Size: 1/4" 200 UWO Max Torque: No Load RPM Setting: 0-1100 Tool Weight: 1.5 lbs

Model No.	Mfg. No.	Desc.	Price/Each
UAF547	DCF601B	Tool Only	
UAF542	DCF601F2	Tool & Kit	



Milwaukee

# 12 V M12<sup>™</sup> Fuel<sup>™</sup> 1/4" Hex 2-Speed Screwdrivers



- Redlithium<sup>™</sup> Battery Technology delivers more work per charge and more work over pack life than any battery on the market
- Redlink Plus<sup>™</sup> Intelligence provides optimized performance and overload protection using total system communication between tool, battery and charger LED light
- Includes: (2x) M12<sup>™</sup> Redlithium<sup>™</sup> 2.0 compact battery pack, M12<sup>™</sup> Lithium-Ion battery charger, belt clip and hard carrying case

#### SPECIFICATIONS

2402-22

TLV679

01 2011	OAnon	•			
Voltage:			12 V		
Chuck Siz	e:		1/4"		
Max Torq	ue:	3	25 in-lbs.		
# of Speed	d Settings	:	2		
No Load R	PM Settir	ng #1:	0-450		
No Load R	PM Settir	ng #2:	0-1700		
Chuck Typ	be:	- Hex d	quick change		
Tool Weight:			2.0 lbs.		
Replacem		ry			
Model I	No.:		TLV694		
Model No.	Mfg. No.	Desc.	Price/Each		
TMB553	2402-20	Tool Onl	/		

Tool & Kit



# 2024 © TENAQUIP Limited

#### 1-800-661-2400

www.tenaquip.com

