



7 1/4" Circular Saws w/High Strength Base

- High strength base will withstand a one story drop
- 56° beveling capacity with stops at 45° and 22.5°
- Electric brake stops blade after use
- Includes: Carbide tipped blade, blade wrench and contractor bag

Model No. TSW598
Mfg. No. DWE575SB
Price/Each \$

SPECIFICATIONS

Amperage: 15.0
No Load RPM: 5200
Depth of Cut at 45°: 1 3/4"
Depth of Cut at 90°: 2 1/2"
Tool Weight: 8.8 lbs.



8" Metal Cutting Saws

- Durable blade shield with integral chiptank deflects hot chips and sparks
- Quick-release shield latch for fast waste disposal and blade changes
- Lever's location ensures user has both hands firmly on the saw
- Includes: Case, circular saw blade and hex blade wrench

Model No. TEX280
Mfg. No. 6370-21
Price/Each \$

SPECIFICATIONS

Amperage: 13.0
No Load RPM: 3700
Depth of Cut at 90°: 2 9/16"
Tool Weight: 13.3 lbs.



Worm Drive 7 1/4" Circular Saws

- Lightweight magnesium and aluminum construction including durable magnesium foot plate
- Extra wide saw hook accepts materials up to 2-3/4"
- ToughCord™ cord protection system with cord jerk protection
- Electric brake stops the blade after trigger is released
- Accepts DWS5100 Dual Port Rip Guide (sold separately)
- Includes: Worm drive circular saw with grounded plug, 7-1/4" Carbide blade, Blade changing wrench

Model No. UAI800
Mfg. No. DWS535B
Price/Each \$

SPECIFICATIONS

Blade Diameter: 7-1/4"
No Load RPM: 4800
Amps: 15 A
Voltage: 120 V
Bevel Capacity: 53°
Bevel Stops: 22.5°, 45°



8 1/4" Circular Saws

- High performance magnesium blade casing and base
- Bevel adjustment with positive stops at 22.5°, 45°, and 50°
- Electric brake, two built in LED lights, rubberized grips
- Includes: Carbide tipped blade, guide rule, hex wrench

Model No. TLY363
Mfg. No. 5008MGA
Price/Each \$

SPECIFICATIONS

Amperage: 15.0
No Load RPM: 5200
Depth of Cut at 45°: 2 1/4" (2" at 50°)
Depth of Cut at 90°: 3
Tool Weight: 11.2 lbs.



7 1/4" Circular Saws

- High power, maximum cutting depth of 2 1/2"
- Electric brake, twin LED lights, heavy gauge aluminium base with ruler markings
- Bevel adjustment with positive stops at 22.5° and 45°
- Includes: Guide rule, hex wrench, carbide tipped black M-Force saw blade

Model No. TLV574
Mfg. No. 500FA
Price/Each \$

SPECIFICATIONS

Amperage: 15.0
No Load RPM: 5800
Depth of Cut at 45°: 1 3/4" (1 3/8" at 50°)
Depth of Cut at 90°: 2 1/2"
Tool Weight: 11.1 lbs.



7 1/4" Circular Saws

- Heavy-duty aluminum base plate for jobsite durability
- Well balanced design for better control from above or behind the saw
- Bevel capacity of 45°
- Includes: 1 ea. 7-1/4" Blade 24T, Wrench 13 (782016-4)

Model No. TF382
Mfg. No. 5007NB
Price/Each \$

SPECIFICATIONS

Amperage: 15.0
No Load RPM: 5800
Depth of Cut at 45°: 1 3/4"
Depth of Cut at 90°: 2 3/8"
Tool Weight: 11.2 lbs.



Compact Jobsite Table Saw

- Compact size for easy transportation and storage
- Rack and pinion telescoping fence rails make fence adjustments fast, smooth, and accurate
- 24.5" of rip capacity for ripping 4x8 plywood or OSB sheets
- Power-loss reset prevents accidental restarts following a power disruption when the tool is left in the on position
- Metal roll cage base for jobsite durability
- Site-Pro Modular Guarding System allows for tool-free adjustments of the guarding
- On-board storage for guard, fence, wrenches, and miter gauge
- Blade brake
- Overall Dim.: 26-3/4" L x 14-9/50" W x 27-1/4" H
- Manufacturer's Warranty: 3-Year Limited Warranty
- Includes: (1) 8-1/4" Table Saw, (1) 8-1/4" Blade, (1) Fence, (1) Non-Through Cut Riving Knife, (1) Anti-Kickback Pawls, (1) Blade-Change Wrenches, (1) Miter Gauge, (1) Modular Guard System, (1) Push Stick

Model No. AUW216
Mfg. No. DWE7485
Price/Each \$

SPECIFICATIONS

Voltage: 120 V
Amperage: 15
No Load RPM: 5800
Max. Depth of Cut at 90°: 2.563"
Max. Depth of Cut at 45°: 1.75"
Blade Diameter: 8-1/4"
Max. Ripping Capacity: 24.5"
Tool Weight: 53.4 lbs.

