



SDS Plus Rotary Hammer Kits

- Thin Wall Core Bit Capacity: 3"
- Vibration: 10.6 m/s²
- Drilling mode: 3-mode: Rotary hammer, hammer only, rotation only
- Get up to 85% faster drilling and 85% harder hitting while reducing vibration
- Equipped with an all metal gear case and mechanical clutch to provide maximum durability
- Powerful and lightweight
- Kit includes a side handle, depth rod and carrying case

Model No. TYO341
Mfg. No. 5268-21
Price/Each \$

SPECIFICATIONS

Solid Bit Capacity: 1 1/8"
Amperage: 8.0
No Load RPM: 0-1500
No Load BPM: 0-5500
Impact Energy: 3.6 ft.-lbs.
Tool Weight: 7.5 lbs.



7/8" SDS Plus Rotary Hammer Kit

- Three modes of operation: Rotary hammer, hammer only and rotation only
- Mechanical clutch: Protects the motor when the bit binds
- Variable position chisel stop: Allows material to be adjusted, regardless of orientation
- Includes: (1) Carrying case, (1) depth rod, (1) side handle

Model No. TLV204
Mfg. No. 5262-21
Price/Each \$

SPECIFICATIONS

Solid Bit Capacity: 7/8"
Amperage: 7.0
No Load RPM: 0-1500
No Load BPM: 0-5625
Impact Energy: 1.8 ft.-lbs.
Tool Weight: 5.8 lbs.



SDS Max Rotary Hammers

- Thin wall core bit capacity: 4"
- Drilling mode: 2-mode: Rotary hammer and hammer only
- Heavy-duty 5.5 ft.-lbs. of impact energy for solid performance
- Constant Power Technology ensures consistent drilling power for the toughest applications
- A 12-position chipping adjustment lets you maintain the optimum hammer position while chipping in any orientation
- A mechanical clutch protects the motor when the bit binds
- Two-mode operation offers maximum versatility regardless of the application
- Tool comes with a side handle and carrying case

Model No. TMB675
Mfg. No. 5317-21
Price/Each \$

SPECIFICATIONS

Solid Bit Capacity: 1 9/16"
Amperage: 10.5
No Load RPM: 0-450
No Load BPM: 0-3000
Impact Energy: 5.5 ft.-lbs.
Tool Weight: 15 lbs.



5/8" SDS+ Rotary Hammers

- Lightweight, 4.6 lbs, compact, 10 1/4" length: Allows for work in tight spaces
- Mechanical clutch: Protects tool when bit binds up
- AVS - Anti vibration system: Delivers maximum comfort by minimizing vibration
- 2-mode operation: Rotary hammer and rotation only for maximum versatility
- Includes: Side handle, depth rod and carrying case

Model No. TLV203
Mfg. No. 5263-21
Price/Each \$

SPECIFICATIONS

Solid Bit Capacity: 5/8"
Amperage: 5.5
No Load RPM: 0-3700
No Load BPM: 0-4400
Impact Energy: 1.5 ft.-lbs.



L-Shape SDS Plus Rotary Hammer

- Wide optimal drilling range for a single-hammer solution
- SHOCKS Active Vibration Control® technology reduces vibration felt at the handles for less user fatigue and greater productivity
- Factory-set clutch reduces sudden, high-torque reactions if bit jams
- Variable speed trigger for accurate hole starting
- Optimized ergonomic design provides excellent control in all orientations
- OSHA Table 1 Compliant dust extraction compatible
- Includes: Rotary Hammer D25333, Kit Box

Model No. UAD826
Mfg. No. D25333K
Price/Each \$

SPECIFICATIONS

Bit Capacity: 3/16" - 7/8"
Amps: 8.5 A
No Load BPM: 0-5200 BPM
No Load RPM: 0-1150 RPM
Impact Energy: 2.58 ft.-lbs.
Power Tool Type: Corded
Tool Weight: 8.16 lbs.



Demolition Hammers w/Anti-Vibration

- Anti-Vibration Technology enabled to reduce fatigue and injury due to exposure to vibration
- Extra long auto cut off carbon brushes provides reduced maintenance
- Electronic speed and variable control gives efficient hammering at the desired speed
- Includes: Side handle, bull point and carrying case

Model No. TLY750
Mfg. No. HM1214C
Price/Each \$

SPECIFICATIONS

Amperage: 14.0
BPM: 950-1900
Impact Energy: 18.95 ft.-lbs.
Tool Weight: 27.1 lbs.



Pavement Breakers

- Active Vibration Control reduces user fatigue and increases comfort and productivity
- Electronic soft start increases productivity by reducing bit walking
- Rubber coated handles provide greater comfort and control

Model No. TLY751
Mfg. No. D25980
Price/Each \$

SPECIFICATIONS

Amperage: 15.0
BPM: 900
Impact Energy: 61 ft.-lbs.
Tool Weight: 68.3 lbs.

