



## Mini Milling & Drilling Machine

- Powerful, 3/4 HP, single-phase DC motor
- Variable speed gear drive
- Spindle depth fine feed control with micro downfeed dial
- Emergency stop button
- Includes: 1/2" chuck, chuck key, R8-JT#33 chuck arbor, chuck guard, 2 T-slot nuts, oil bottle, adjustment wrenches and hex keys



<b>Model No.</b>	<b>UAD693</b>
<b>Mfg. No.</b>	KC-15VS
<b>Drilling Capacity:</b>	1/2"
<b>Max. distance spindle nose to table:</b>	11-1/4"
<b>Speeds:</b>	2
<b>Face mill capacity:</b>	1-1/8"
<b>End mill capacity:</b>	5/8"
<b>Working area of the table:</b>	3-5/8" x 15-3/4"
<b>Size of T-slot on table:</b>	7/16"
<b>Dimensions:</b>	19-1/2" x 22" x 30"
<b>Price/Each</b>	\$

## Milling Drilling Machine with Digital Readout

- Comes with 1/2" chuck, chuck key, R8 chuck arbor, safety guard, 2 T-bolts, oil bottle, adjustment wrenches, hex keys and tool box
- Safety guard with limit switch protection
- Magnetic line interruption switch needs a restart after a power failure
- Spindle depth digital readout and control panel with metric and imperial readings
- Forward/reverse switch and variable-speed selector dials



<b>Model No.</b>	<b>TMA116</b>
<b>Mfg. No.</b>	KC-20VS-2
<b>Drilling capacity:</b>	5/8"
<b>No. of Speeds:</b>	2
<b>Table Size:</b>	7-1/16" W x 27-1/2" L x 2-1/2" H
<b>Overall Width::</b>	29-5/8"
<b>Overall Length:</b>	27-1/2"
<b>Overall Height:</b>	35-3/8"
<b>Price/Each</b>	\$

## Gearhead Milling Drilling Machines

- Spindle is equipped with four heavy-duty tapered roller bearings
- Forward and reverse switch
- Head tilts 90° to the left and 30° to the right
- Includes: 1/2" chuck with key, 3-1/2" angle vise and safety guard



<b>Model No.</b>	<b>BV698</b>
<b>Mfg. No.</b>	KC-40HC
<b>Drilling capacity:</b>	1-1/4"
<b>Diameter of column:</b>	4-1/2"
<b>Speeds:</b>	6 (60-1500 RPM)
<b>Table size:</b>	23" x 7-1/2"
<b>Size of T-slot on table:</b>	1/2"
<b>Motor:</b>	1.5 HP, 11 A, 1 phase, 60 Hz
<b>Voltage:</b>	220 V
<b>Dimensions:</b>	38" L x 37" W x 78" H
<b>Approx. shipping weight:</b>	630 lbs.
<b>Price/Each</b>	\$

## Milling Drilling Machines

- Spindle is equipped with four heavy-duty tapered roller bearings
- Table control hand wheels have large micrometer dials graduated in 0.001"
- Head swivels 360° and is easily raised and lowered
- Includes: 3" face cutter, 1/2" chuck with key, 3-1/2" angle vise and safety guard



<b>Model No.</b>	<b>TS218</b>
<b>Mfg. No.</b>	PDM-30
<b>Drilling capacity:</b>	1-1/4"
<b>Diameter of column:</b>	4-3/4"
<b>Speeds:</b>	12 (150-2500 RPM)
<b>Working area of table:</b>	8-1/4" x 28-3/4"
<b>Size of T-slot on table:</b>	5/8"
<b>Motor:</b>	11 A @ 220 V, 1 phase, 60 Hz
<b>Voltage:</b>	110/220 V
<b>Pre-wired at:</b>	110 V
<b>Dimensions:</b>	43" L x 39" W x 42" H
<b>Approx. shipping weight:</b>	600 lbs.
<b>Price/Each</b>	\$



### ACCESSORY

<b>Model No.</b>	<b>TS221</b>
<b>Mfg. No.</b>	SS-45
<b>Description</b>	Optional stand for TS218
<b>Dimensions</b>	31" x 21-1/2" x 28-1/4"
<b>Price/Each</b>	\$

