

3/8" Heavy-Duty Composite Air Impact Wrenches

- Lightweight composite design minimizes operator fatigue
- Ergonomic grip reduces vibrationExhaust air outlet directs air
- Exhaust air outlet directs air away from operator
- Forward-reverse switch, and high-low speed regulator
- Low noise, low vibration
- Overall length: 7"Weight: 2.8 lbs.

Model No. TLZ137





1/2" Heavy-Duty Composite Air Impact Wrenches

- Lightweight composite design minimizes operator fatigue
- Ergonomic grip reduces vibration
- Exhaust air outlet directs air away from operator
- Forward-reverse switch, and high-low speed regulator
- Low noise, low vibration
- Overall length: 7 3/4"
- Weight: 4.6 lbs.

Model No. TLZ138





Model No.	Square Drive in mm	Bolt Capacity in mm	Free Speed RPM	Torque Range ft-lbs.	Average Air Consumption CFM	Air Inlet	Hose Size in mm	Vibrations Less Than m/s²	Sound Pressure Level dB(A)	Price /Each
TLZ137	3/8 9.53	1/2 13	10 000	90-280	10.6	1/4" 18 NPT	3/8 9.5	3.7	91.5	
TLZ138	1/2 12.7	5/8 16	10 000	400-1000	13.7	1/4" 18 NPT	3/8 9.5	6.0	94	

Composite 3/4" Heavy-Duty Air Impact Wrenches

- Lightweight composite design minimizes operator fatigue
- Ergonomic grip reduces vibration
- · Exhaust air outlet directs air away from operator
- · Forward-reverse switch, and high-low speed regulator
- · Overall length: 8"
- Weight: 5 lbs.





Model No.	Square Drive in mm	Bolt Capacity in mm	Free Speed RPM	Torque Range ft-lbs.	Average Air Consumption CFM	Air Inlet	Hose Size in mm	Vibrations Less Than m/s²	Sound Pressure Level dB(A)	Price /Each
TLZ139	3/4 19.1	1 26	9000	450-1000	13.7	1/4" - 18 NPT	3/8 9.5	9.2	95.9	

3/4" Heavy-Duty Air Impact Wrenches

- Twin hammer impact mechanism
- Three-step forward/reverse regulator allows the operator to adjust the power to the job
- Rear exhaust directs air away from work piece and operator
- Ergonomically designed to reduce operator fatigue
- Special heat-treatment of major parts and anvil for long life
- · Soft rubber grip handle reduces fatigue
- · Weight: 11 lbs.



1/2" Heavy-Duty Air Impact Wrench

- Pin-clutch hammer mechanism
- Built-in regulator to prevent over-torquing
- Low noise, low vibration
- Forward-reverse switch, and high-low speed regulator

AURØRA

- Durability and longer life
- Weight: 5 lbs.





Т	0	0	L	S	

Model No.	Square Drive in mm	Bolt Capacity in mm	Free Speed RPM	Torque Range ft-lbs.	Average Air Consumption CFM	Air Inlet	Hose Size in mm	Vibrations Less Than m/s²	Sound Pressure Level dB(A)	Prio /Eac
THZ672	3/4 19	1 25.4	4600	565-1100	9	1/4" 18 NPT	3/8 9.5	6.1	90	
UAK133	1/2 12.7	5/8 15.9	7000	25-320	12	1/4" 18 NPT	3/8 9.5	3.1	94	